Parts & Accessories > Pumps (Water Pumps) > Udor USA > Plunger Pumps > Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Model Number: PND 1.0/20 Z
Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Manufacturer: Udor USA

Normal
0

false
false
false

EN-US
X-NONE
X-NONE

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

DefSemiHidden="false" DefQFormat="false" DefPriority="99"
LatentStyleCount="376">

UnhideWhenUsed="true" QFormat="true" Name="heading 2" />

UnhideWhenUsed="true" QFormat="true" Name="heading 3" />

UnhideWhenUsed="true" QFormat="true" Name="heading 4" />

UnhideWhenUsed="true" QFormat="true" Name="heading 5" />

UnhideWhenUsed="true" QFormat="true" Name="heading 6" />

UnhideWhenUsed="true" QFormat="true" Name="heading 7" />

UnhideWhenUsed="true" QFormat="true" Name="heading 8" />

UnhideWhenUsed="true" QFormat="true" Name="heading 9" />

Name="index 1" />

Name="index 2" />

Name="index 3" />

Name="index 4" />

Name="index 5" />

Name="index 6" />

Name="index 7" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="index 8" />

Name="index 9" />

UnhideWhenUsed="true" Name="toc 1" />

UnhideWhenUsed="true" Name="toc 2" />

UnhideWhenUsed="true" Name="toc 3" />

UnhideWhenUsed="true" Name="toc 4" />

UnhideWhenUsed="true" Name="toc 5" />

UnhideWhenUsed="true" Name="toc 6" />

UnhideWhenUsed="true" Name="toc 7" />

UnhideWhenUsed="true" Name="toc 8" />

UnhideWhenUsed="true" Name="toc 9" />

Name="Normal Indent" />

Name="footnote text" />

Name="annotation text" />

Name="header" />

Name="footer" />

Name="index heading" />

UnhideWhenUsed="true" QFormat="true" Name="caption" />

Name="table of figures" />

Name="envelope address" />

Name="envelope return" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="footnote reference" />

Name="annotation reference" />

Name="line number" />

Name="page number" />

Name="endnote reference" />

Name="endnote text" />

Name="table of authorities" />

Name="macro" />

Name="toa heading" />

Name="List" />

Name="List Bullet" />

Name="List Number" />

Name="List 2" />

Name="List 3" />

Name="List 4" />

Name="List 5" />

Name="List Bullet 2" />

Name="List Bullet 3" />

Name="List Bullet 4" />

Name="List Bullet 5" />

Name="List Number 2" />

Name="List Number 3" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Number 4" />

Name="List Number 5" />

Name="Closing" />

Name="Signature" />

UnhideWhenUsed="true" Name="Default Paragraph Font" />

Name="Body Text" />

Name="Body Text Indent" />

Name="List Continue" />

Name="List Continue 2" />

Name="List Continue 3" />

Name="List Continue 4" />

Name="List Continue 5" />

Name="Message Header" />

Name="Salutation" />

Name="Date" />

Name="Body Text First Indent" />

Name="Body Text First Indent 2" />

Name="Note Heading" />

Name="Body Text 2" />

Name="Body Text 3" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Body Text Indent 2" />

Name="Body Text Indent 3" />

Name="Block Text" />

Name="Hyperlink" />

Name="FollowedHyperlink" />

Name="Document Map" />

Name="Plain Text" />

Name="E-mail Signature" />

Name="HTML Top of Form" />

Name="HTML Bottom of Form" />

Name="Normal (Web)" />

Name="HTML Acronym" />

Name="HTML Address" />

Name="HTML Cite" />

Name="HTML Code" />

Name="HTML Definition" />

Name="HTML Keyboard" />

Name="HTML Preformatted" />

Name="HTML Sample" />

Name="HTML Typewriter" />

Name="HTML Variable" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Normal Table" />

Name="annotation subject" />

Name="No List" />

Name="Outline List 1" />

Name="Outline List 2" />

Name="Outline List 3" />

Name="Table Simple 1" />

Name="Table Simple 2" />

Name="Table Simple 3" />

Name="Table Classic 1" />

Name="Table Classic 2" />

Name="Table Classic 3" />

Name="Table Classic 4" />

Name="Table Colorful 1" />

Name="Table Colorful 2" />

Name="Table Colorful 3" />

Name="Table Columns 1" />

Name="Table Columns 2" />

Name="Table Columns 3" />

Name="Table Columns 4" />

Name="Table Columns 5" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Table Grid 1" />

Name="Table Grid 2" />

Name="Table Grid 3" />

Name="Table Grid 4" />

Name="Table Grid 5" />

Name="Table Grid 6" />

Name="Table Grid 7" />

Name="Table Grid 8" />

Name="Table List 1" />

Name="Table List 2" />

Name="Table List 3" />

Name="Table List 4" />

Name="Table List 5" />

Name="Table List 6" />

Name="Table List 7" />

Name="Table List 8" />

Name="Table 3D effects 1" />

Name="Table 3D effects 2" />

Name="Table 3D effects 3" />

Name="Table Contemporary" />

Name="Table Elegant" />

Name="Table Professional" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Table Subtle 1" />

Name="Table Subtle 2" />

Name="Table Web 1" />

Name="Table Web 2" />

Name="Table Web 3" />

Name="Balloon Text" />

Name="Table Theme" />

Name="List Paragraph" />

Name="Intense Quote" />

Steambrite Supply

Parts & Accessories > Pumps (Water Pumps) > Udor USA > Plunger Pumps > Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Steambrite Supply

Name="Subtle Emphasis" />

Name="Intense Emphasis" />

Name="Subtle Reference" />

Name="Intense Reference" />

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

UnhideWhenUsed="true" Name="Bibliography" />

UnhideWhenUsed="true" QFormat="true" Name="TOC Heading" />

Name="Grid Table 1 Light Accent 1" />

Name="Grid Table 6 Colorful Accent 1" />

Name="Grid Table 7 Colorful Accent 1" />

Name="Grid Table 1 Light Accent 2" />

Name="Grid Table 6 Colorful Accent 2" />

Name="Grid Table 7 Colorful Accent 2" />

Name="Grid Table 1 Light Accent 3" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Grid Table 6 Colorful Accent 3" />

Name="Grid Table 7 Colorful Accent 3" />

Name="Grid Table 1 Light Accent 4" />

Name="Grid Table 6 Colorful Accent 4" />

Name="Grid Table 7 Colorful Accent 4" />

Name="Grid Table 1 Light Accent 5" />

Name="Grid Table 6 Colorful Accent 5" />

Name="Grid Table 7 Colorful Accent 5" />

Name="Grid Table 1 Light Accent 6" />

Name="Grid Table 6 Colorful Accent 6" />

Name="Grid Table 7 Colorful Accent 6" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Table 1 Light Accent 1" />

Name="List Table 6 Colorful Accent 1" />

Name="List Table 7 Colorful Accent 1" />

Name="List Table 1 Light Accent 2" />

Name="List Table 6 Colorful Accent 2" />

Name="List Table 7 Colorful Accent 2" />

Name="List Table 1 Light Accent 3" />

Name="List Table 6 Colorful Accent 3" />

Name="List Table 7 Colorful Accent 3" />

Name="List Table 1 Light Accent 4" />

Name="List Table 6 Colorful Accent 4" />

Name="List Table 7 Colorful Accent 4" />

Name="List Table 1 Light Accent 5" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Table 6 Colorful Accent 5" />

Name="List Table 7 Colorful Accent 5" />

Name="List Table 1 Light Accent 6" />

Name="List Table 6 Colorful Accent 6" />

Name="List Table 7 Colorful Accent 6" />

Name="Mention" />

Name="Smart Hyperlink" />

Name="Hashtag" />

Name="Unresolved Mention" />

Name="Smart Link" />

```
/* Style Definitions */
table.MsoNormalTable
{mso-style-name:"Table Normal";
mso-tstyle-rowband-size:0;
mso-tstyle-colband-size:0;
mso-style-noshow:yes;
mso-style-priority:99;
mso-style-parent:"";
mso-padding-alt:0in 5.4pt 0in 5.4pt;
mso-para-margin-top:0in;
mso-para-margin-right:0in;
mso-para-margin-bottom:8.0pt;
mso-para-margin-left:0in;
line-height:115%;
```

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

mso-pagination:widow-orphan;
font-size:12.0pt;
font-family:"Aptos",sans-serif;
mso-ascii-font-family:Aptos;
mso-ascii-theme-font:minor-latin;
mso-hansi-font-family:Aptos;
mso-hansi-theme-font:minor-latin;
mso-font-kerning:1.0pt;
mso-ligatures:standardcontextual;}

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8” Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM
Description

Normal
0

false
false
false

EN-US
X-NONE
X-NONE

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

DefSemiHidden="false" DefQFormat="false" DefPriority="99"
LatentStyleCount="376">

UnhideWhenUsed="true" QFormat="true" Name="heading 2" />

UnhideWhenUsed="true" QFormat="true" Name="heading 3" />

UnhideWhenUsed="true" QFormat="true" Name="heading 4" />

UnhideWhenUsed="true" QFormat="true" Name="heading 5" />

UnhideWhenUsed="true" QFormat="true" Name="heading 6" />

UnhideWhenUsed="true" QFormat="true" Name="heading 7" />

UnhideWhenUsed="true" QFormat="true" Name="heading 8" />

UnhideWhenUsed="true" QFormat="true" Name="heading 9" />

Name="index 1" />

Name="index 2" />

Name="index 3" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="index 4" />

Name="index 5" />

Name="index 6" />

Name="index 7" />

Name="index 8" />

Name="index 9" />

UnhideWhenUsed="true" Name="toc 1" />

UnhideWhenUsed="true" Name="toc 2" />

UnhideWhenUsed="true" Name="toc 3" />

UnhideWhenUsed="true" Name="toc 4" />

UnhideWhenUsed="true" Name="toc 5" />

UnhideWhenUsed="true" Name="toc 6" />

UnhideWhenUsed="true" Name="toc 7" />

UnhideWhenUsed="true" Name="toc 8" />

UnhideWhenUsed="true" Name="toc 9" />

Name="Normal Indent" />

Name="footnote text" />

Name="annotation text" />

Name="header" />

Name="footer" />

Name="index heading" />

UnhideWhenUsed="true" QFormat="true" Name="caption" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="table of figures" />

Name="envelope address" />

Name="envelope return" />

Name="footnote reference" />

Name="annotation reference" />

Name="line number" />

Name="page number" />

Name="endnote reference" />

Name="endnote text" />

Name="table of authorities" />

Name="macro" />

Name="toa heading" />

Name="List" />

Name="List Bullet" />

Name="List Number" />

Name="List 2" />

Name="List 3" />

Name="List 4" />

Name="List 5" />

Name="List Bullet 2" />

Name="List Bullet 3" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Bullet 4" />

Name="List Bullet 5" />

Name="List Number 2" />

Name="List Number 3" />

Name="List Number 4" />

Name="List Number 5" />

Name="Closing" />

Name="Signature" />

UnhideWhenUsed="true" Name="Default Paragraph Font" />

Name="Body Text" />

Name="Body Text Indent" />

Name="List Continue" />

Name="List Continue 2" />

Name="List Continue 3" />

Name="List Continue 4" />

Name="List Continue 5" />

Name="Message Header" />

Name="Salutation" />

Name="Date" />

Name="Body Text First Indent" />

Name="Body Text First Indent 2" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Note Heading" />

Name="Body Text 2" />

Name="Body Text 3" />

Name="Body Text Indent 2" />

Name="Body Text Indent 3" />

Name="Block Text" />

Name="Hyperlink" />

Name="FollowedHyperlink" />

Name="Document Map" />

Name="Plain Text" />

Name="E-mail Signature" />

Name="HTML Top of Form" />

Name="HTML Bottom of Form" />

Name="Normal (Web)" />

Name="HTML Acronym" />

Name="HTML Address" />

Name="HTML Cite" />

Name="HTML Code" />

Name="HTML Definition" />

Name="HTML Keyboard" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="HTML Preformatted" />

Name="HTML Sample" />

Name="HTML Typewriter" />

Name="HTML Variable" />

Name="Normal Table" />

Name="annotation subject" />

Name="No List" />

Name="Outline List 1" />

Name="Outline List 2" />

Name="Outline List 3" />

Name="Table Simple 1" />

Name="Table Simple 2" />

Name="Table Simple 3" />

Name="Table Classic 1" />

Name="Table Classic 2" />

Name="Table Classic 3" />

Name="Table Classic 4" />

Name="Table Colorful 1" />

Name="Table Colorful 2" />

Name="Table Colorful 3" />

Name="Table Columns 1" />

Name="Table Columns 2" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Table Columns 3" />

Name="Table Columns 4" />

Name="Table Columns 5" />

Name="Table Grid 1" />

Name="Table Grid 2" />

Name="Table Grid 3" />

Name="Table Grid 4" />

Name="Table Grid 5" />

Name="Table Grid 6" />

Name="Table Grid 7" />

Name="Table Grid 8" />

Name="Table List 1" />

Name="Table List 2" />

Name="Table List 3" />

Name="Table List 4" />

Name="Table List 5" />

Name="Table List 6" />

Name="Table List 7" />

Name="Table List 8" />

Name="Table 3D effects 1" />

Name="Table 3D effects 2" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Table 3D effects 3" />

Name="Table Contemporary" />

Name="Table Elegant" />

Name="Table Professional" />

Name="Table Subtle 1" />

Name="Table Subtle 2" />

Name="Table Web 1" />

Name="Table Web 2" />

Name="Table Web 3" />

Name="Balloon Text" />

Name="Table Theme" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Paragraph" />

Name="Intense Quote" />

Steambrite Supply

Parts & Accessories > Pumps (Water Pumps) > Udor USA > Plunger Pumps > Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Subtle Emphasis" />

Name="Intense Emphasis" />

Name="Subtle Reference" />

Name="Intense Reference" />

UnhideWhenUsed="true" Name="Bibliography" />

UnhideWhenUsed="true" QFormat="true" Name="TOC Heading" />

Name="Grid Table 1 Light Accent 1" />

Name="Grid Table 6 Colorful Accent 1" />

Name="Grid Table 7 Colorful Accent 1" />

Name="Grid Table 1 Light Accent 2" />

Name="Grid Table 6 Colorful Accent 2" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Grid Table 7 Colorful Accent 2" />

Name="Grid Table 1 Light Accent 3" />

Name="Grid Table 6 Colorful Accent 3" />

Name="Grid Table 7 Colorful Accent 3" />

Name="Grid Table 1 Light Accent 4" />

Name="Grid Table 6 Colorful Accent 4" />

Name="Grid Table 7 Colorful Accent 4" />

Name="Grid Table 1 Light Accent 5" />

Name="Grid Table 6 Colorful Accent 5" />

Name="Grid Table 7 Colorful Accent 5" />

Name="Grid Table 1 Light Accent 6" />

Name="Grid Table 6 Colorful Accent 6" />

Name="Grid Table 7 Colorful Accent 6" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Table 1 Light Accent 1" />

Name="List Table 6 Colorful Accent 1" />

Name="List Table 7 Colorful Accent 1" />

Name="List Table 1 Light Accent 2" />

Name="List Table 6 Colorful Accent 2" />

Name="List Table 7 Colorful Accent 2" />

Name="List Table 1 Light Accent 3" />

Name="List Table 6 Colorful Accent 3" />

Name="List Table 7 Colorful Accent 3" />

Name="List Table 1 Light Accent 4" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Table 6 Colorful Accent 4" />

Name="List Table 7 Colorful Accent 4" />

Name="List Table 1 Light Accent 5" />

Name="List Table 6 Colorful Accent 5" />

Name="List Table 7 Colorful Accent 5" />

Name="List Table 1 Light Accent 6" />

Name="List Table 6 Colorful Accent 6" />

Name="List Table 7 Colorful Accent 6" />

Name="Mention" />

Name="Smart Hyperlink" />

Name="Hashtag" />

Name="Unresolved Mention" />

Name="Smart Link" />

```
/* Style Definitions */
table.MsoNormalTable
{mso-style-name:"Table Normal";
mso-tstyle-rowband-size:0;
mso-tstyle-colband-size:0;
mso-style-noshow:yes;
mso-style-priority:99;
```

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

mso-style-parent:"";
mso-padding-alt:0in 5.4pt 0in 5.4pt;
mso-para-margin-top:0in;
mso-para-margin-right:0in;
mso-para-margin-bottom:8.0pt;
mso-para-margin-left:0in;
line-height:115%;
mso-pagination:widow-orphan;
font-size:12.0pt;
font-family:"Aptos",sans-serif;
mso-ascii-font-family:Aptos;
mso-ascii-theme-font:minor-latin;
mso-hansi-font-family:Aptos;
mso-hansi-theme-font:minor-latin;
mso-font-kerning:1.0pt;
mso-ligatures:standardcontextual;}

UDOR Plunger Pump - PND 1.0/20-Z
Features

- Brass Manifold
- Heat Treated Crankshaft
- Stainless Steel Piston Guides
- High Strength Aluminum Alloy or Bronze Connecting Rods
- Industrial Quality Ball Bearings and Needle Bearings
- Solid Ceramic Plungers
- Stainless Steel Check Valves
- Heavy Duty Flat Base High Pressure Seals
- Dual Oil Sight Gauges
- 10 oz. Capacity Vented Oil Bath Crank Case
- 3/8″ BSP-F Inlet. 3/8″ BSP-F Outlet
- Max Fluid Temp, 160°F

Specifications

Normal
0

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

false
false
false

EN-US
X-NONE
X-NONE

DefSemiHidden="false" DefQFormat="false" DefPriority="99"
LatentStyleCount="376">

UnhideWhenUsed="true" QFormat="true" Name="heading 2" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

UnhideWhenUsed="true" QFormat="true" Name="heading 3" />

UnhideWhenUsed="true" QFormat="true" Name="heading 4" />

UnhideWhenUsed="true" QFormat="true" Name="heading 5" />

UnhideWhenUsed="true" QFormat="true" Name="heading 6" />

UnhideWhenUsed="true" QFormat="true" Name="heading 7" />

UnhideWhenUsed="true" QFormat="true" Name="heading 8" />

UnhideWhenUsed="true" QFormat="true" Name="heading 9" />

Name="index 1" />

Name="index 2" />

Name="index 3" />

Name="index 4" />

Name="index 5" />

Name="index 6" />

Name="index 7" />

Name="index 8" />

Name="index 9" />

UnhideWhenUsed="true" Name="toc 1" />

UnhideWhenUsed="true" Name="toc 2" />

UnhideWhenUsed="true" Name="toc 3" />

UnhideWhenUsed="true" Name="toc 4" />

UnhideWhenUsed="true" Name="toc 5" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

UnhideWhenUsed="true" Name="toc 6" />

UnhideWhenUsed="true" Name="toc 7" />

UnhideWhenUsed="true" Name="toc 8" />

UnhideWhenUsed="true" Name="toc 9" />

Name="Normal Indent" />

Name="footnote text" />

Name="annotation text" />

Name="header" />

Name="footer" />

Name="index heading" />

UnhideWhenUsed="true" QFormat="true" Name="caption" />

Name="table of figures" />

Name="envelope address" />

Name="envelope return" />

Name="footnote reference" />

Name="annotation reference" />

Name="line number" />

Name="page number" />

Name="endnote reference" />

Name="endnote text" />

Name="table of authorities" />

Name="macro" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="toa heading" />

Name="List" />

Name="List Bullet" />

Name="List Number" />

Name="List 2" />

Name="List 3" />

Name="List 4" />

Name="List 5" />

Name="List Bullet 2" />

Name="List Bullet 3" />

Name="List Bullet 4" />

Name="List Bullet 5" />

Name="List Number 2" />

Name="List Number 3" />

Name="List Number 4" />

Name="List Number 5" />

Name="Closing" />

Name="Signature" />

UnhideWhenUsed="true" Name="Default Paragraph Font" />

Name="Body Text" />

Name="Body Text Indent" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Continue" />

Name="List Continue 2" />

Name="List Continue 3" />

Name="List Continue 4" />

Name="List Continue 5" />

Name="Message Header" />

Name="Salutation" />

Name="Date" />

Name="Body Text First Indent" />

Name="Body Text First Indent 2" />

Name="Note Heading" />

Name="Body Text 2" />

Name="Body Text 3" />

Name="Body Text Indent 2" />

Name="Body Text Indent 3" />

Name="Block Text" />

Name="Hyperlink" />

Name="FollowedHyperlink" />

Name="Document Map" />

Name="Plain Text" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="E-mail Signature" />

Name="HTML Top of Form" />

Name="HTML Bottom of Form" />

Name="Normal (Web)" />

Name="HTML Acronym" />

Name="HTML Address" />

Name="HTML Cite" />

Name="HTML Code" />

Name="HTML Definition" />

Name="HTML Keyboard" />

Name="HTML Preformatted" />

Name="HTML Sample" />

Name="HTML Typewriter" />

Name="HTML Variable" />

Name="Normal Table" />

Name="annotation subject" />

Name="No List" />

Name="Outline List 1" />

Name="Outline List 2" />

Name="Outline List 3" />

Name="Table Simple 1" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Table Simple 2" />

Name="Table Simple 3" />

Name="Table Classic 1" />

Name="Table Classic 2" />

Name="Table Classic 3" />

Name="Table Classic 4" />

Name="Table Colorful 1" />

Name="Table Colorful 2" />

Name="Table Colorful 3" />

Name="Table Columns 1" />

Name="Table Columns 2" />

Name="Table Columns 3" />

Name="Table Columns 4" />

Name="Table Columns 5" />

Name="Table Grid 1" />

Name="Table Grid 2" />

Name="Table Grid 3" />

Name="Table Grid 4" />

Name="Table Grid 5" />

Name="Table Grid 6" />

Name="Table Grid 7" />

Name="Table Grid 8" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Table List 1" />

Name="Table List 2" />

Name="Table List 3" />

Name="Table List 4" />

Name="Table List 5" />

Name="Table List 6" />

Name="Table List 7" />

Name="Table List 8" />

Name="Table 3D effects 1" />

Name="Table 3D effects 2" />

Name="Table 3D effects 3" />

Name="Table Contemporary" />

Name="Table Elegant" />

Name="Table Professional" />

Name="Table Subtle 1" />

Name="Table Subtle 2" />

Name="Table Web 1" />

Name="Table Web 2" />

Name="Table Web 3" />

Name="Balloon Text" />

Name="Table Theme" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Steambrite Supply

Name="List Paragraph" />

Name="Intense Quote" />

Parts & Accessories > Pumps (Water Pumps) > Udor USA > Plunger Pumps > Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Steambrite Supply

Name="Subtle Emphasis" />

Name="Intense Emphasis" />

Name="Subtle Reference" />

Name="Intense Reference" />

UnhideWhenUsed="true" Name="Bibliography" />

UnhideWhenUsed="true" QFormat="true" Name="TOC Heading" />

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Grid Table 1 Light Accent 1" />

Name="Grid Table 6 Colorful Accent 1" />

Name="Grid Table 7 Colorful Accent 1" />

Name="Grid Table 1 Light Accent 2" />

Name="Grid Table 6 Colorful Accent 2" />

Name="Grid Table 7 Colorful Accent 2" />

Name="Grid Table 1 Light Accent 3" />

Name="Grid Table 6 Colorful Accent 3" />

Name="Grid Table 7 Colorful Accent 3" />

Name="Grid Table 1 Light Accent 4" />

Name="Grid Table 6 Colorful Accent 4" />

Name="Grid Table 7 Colorful Accent 4" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="Grid Table 1 Light Accent 5" />

Name="Grid Table 6 Colorful Accent 5" />

Name="Grid Table 7 Colorful Accent 5" />

Name="Grid Table 1 Light Accent 6" />

Name="Grid Table 6 Colorful Accent 6" />

Name="Grid Table 7 Colorful Accent 6" />

Name="List Table 1 Light Accent 1" />

Name="List Table 6 Colorful Accent 1" />

Name="List Table 7 Colorful Accent 1" />

Name="List Table 1 Light Accent 2" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Table 6 Colorful Accent 2" />

Name="List Table 7 Colorful Accent 2" />

Name="List Table 1 Light Accent 3" />

Name="List Table 6 Colorful Accent 3" />

Name="List Table 7 Colorful Accent 3" />

Name="List Table 1 Light Accent 4" />

Name="List Table 6 Colorful Accent 4" />

Name="List Table 7 Colorful Accent 4" />

Name="List Table 1 Light Accent 5" />

Name="List Table 6 Colorful Accent 5" />

Name="List Table 7 Colorful Accent 5" />

Name="List Table 1 Light Accent 6" />

Name="List Table 6 Colorful Accent 6" />

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Name="List Table 7 Colorful Accent 6" />

Name="Mention" />

Name="Smart Hyperlink" />

Name="Hashtag" />

Name="Unresolved Mention" />

Name="Smart Link" />

/* Style Definitions */
table.MsoNormalTable
{mso-style-name:"Table Normal";
mso-tstyle-rowband-size:0;
mso-tstyle-colband-size:0;
mso-style-noshow:yes;
mso-style-priority:99;
mso-style-parent:"";
mso-padding-alt:0in 5.4pt 0in 5.4pt;
mso-para-margin-top:0in;
mso-para-margin-right:0in;
mso-para-margin-bottom:8.0pt;
mso-para-margin-left:0in;
line-height:115%;
mso-pagination:widow-orphan;
font-size:12.0pt;
font-family:"Aptos",sans-serif;
mso-ascii-font-family:Aptos;
mso-ascii-theme-font:minor-latin;
mso-hansi-font-family:Aptos;
mso-hansi-theme-font:minor-latin;
mso-font-kerning:1.0pt;
mso-ligatures:standardcontextual;}
table.MsoTableGrid
{mso-style-name:"Table Grid";
mso-tstyle-rowband-size:0;
mso-tstyle-colband-size:0;
mso-style-priority:39;
mso-style-unhide:no;

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

border:solid windowtext 1.0pt;
mso-border-alt:solid windowtext .5pt;
mso-padding-alt:0in 5.4pt 0in 5.4pt;
mso-border-insideh:.5pt solid windowtext;
mso-border-insidev:.5pt solid windowtext;
mso-para-margin:0in;
mso-pagination:widow-orphan;
font-size:12.0pt;
font-family:"Aptos",sans-serif;
mso-ascii-font-family:Aptos;
mso-ascii-theme-font:minor-latin;
mso-hansi-font-family:Aptos;
mso-hansi-theme-font:minor-latin;
mso-font-kerning:1.0pt;
mso-ligatures:standardcontextual;}

Flow – GPM

1.0

Flow – L/min

4

RPM

1750

Steambrite Supply

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

PSI

2000

Bar

140

Power Req.

1.5 EBHP

Seal Kit

6061.07 (Kit 7)

Valve Kit

6061.01 (Kit 1)

Weight

Steambrite Supply

Parts & Accessories > Pumps (Water Pumps) > Udor USA > Plunger Pumps > Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

Udor USA PND 1.0/20 Z Direct Drive, Electric Flange Model 5/8â€• Hollow Shaft with NEMA 56C Mounting Flange 1.0 GPM/2000 PSI/1750 RPM

13 lbs.

Dimensions

Product Page

Manual

Availability: This product was added to our catalog on Thursday 10 July, 2025

Steambrite Supply