

>



Model Number: 80.612

Mosmatic 80.612, TUV-750 30 Inch Undercarriage Cleaning Wand

Manufacturer: Mosmatic Pressure Washing Equip

Due to the popularity of The Mosmatic Undercarriage Cleaner, our development has expanded the line. Mosmatic has now not only two different size undercarriage cleaner, new we have models equipped with stabilizer nozzles. This means more cleaning power and more reach!

The versions with stabilizer are equipped with longer nozzles and a higher protective ring. The diameter of 520mm or 750mm has proven itself. We recommend to use the washer TUV with a guard plate.

See and Print Brochure/Flyer

Mosmatic: TUV-750 30 Inch Undercarriage Cleaning Wand

Pressure up to 4000 psi

Temperature up to 250 degrees F

Complete Stainless Steel construction

Quality Swivel (DYF/ Maintenance Free)

Balanced Quality Rotary Arm

Ultra Solid construction

Only needs 7" of clearance to get under the vehical

Can be used with most pressure washing equipment

Can be used with most chemicals from pH 3 through 12

Optional TUV-750 Mosmatic part 80.622 to protect swivel from falling mud.

27.3 lbs use weight

3 Way X 1/8" Nptf Rotary Arm

3 X 1503 Stainless jets

1 Pressure wash gun

2 X 4" casters

1 X 2-1/4" caster

3/8" Nptf water inlet

Parts used: Swivel- 58.553 &ndash; \$235.83,

TKA - 82.9014 -&rdquo; List \$ 141.90

Gun P# 29.081, list \$ 55.62

Ships on a pallet 48&rdquo;x32&rdquo;x10&rdquo;

Box weight 40 lbs + pallet weight

>

Brochure

2012 Mosmatic Updated movie:

Question: Hello, what kind of pressure cleaner do I need for the (Mosmatic: TUW-750 30 Guard Plate for 80.612 Undercarriage cleaning wand) to work????

Answer: Minimum pressure 2000 psi  
Minimum gpm flow rate 4.5 gpm  
9,000 cleaning units or larger

The jets can also be changed out for use with smaller pressure washers.

---

*Availability: This product was added to our catalog on Wednesday 01 June, 2011*