

Parts & Accessories > Brass, Plastic, Steel, Stainless Hydraulic Fittings > Stainless Steel Fittings > Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI

Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI



Model Number: SS1404-06-06

Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI

Manufacturer: Clean Storm

Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI

Buy More Save More \$

Description

The Clean Storm SS1404-06-06 is a high-performance 316 Stainless Steel non-live pipe swivel adapter designed for demanding hydraulic, pneumatic, and industrial fluid transfer systems. Featuring a 3/8" MNPT (Male National Pipe Taper) to 3/8" FNPSM (Female National Pipe Straight Mechanical) connection, this fitting provides a secure, leak-resistant joint while easing alignment during installation.

Constructed from premium 316 Stainless Steel, this adapter offers superior corrosion resistance against harsh chemicals, saltwater, and extreme environments.

Engineered as a non-live swivel, it allows smooth rotation for easy alignment and tightening during assembly. Once fully torqued, the swivel action locks into place and does not rotate under system pressure, ensuring a rigid, reliable connection. To disassemble or adjust, the swivel action can be broken loose again without damaging the threads.

Features

- Premium 316 Stainless Steel Construction: High corrosion resistance ideal for marine, chemical, high-pressure washing, and industrial fluid applications.
- Non-Live Swivel Functionality: Swivels freely during installation and alignment, then locks rigid once assembled (not intended to rotate under active fluid pressure).
- High Pressure & Temperature Tolerances: Rated up to 5,000 PSI operating pressure and withstands extreme temperatures up to 1,000°F.
- Standardized Threading: Features precision-machined 3/8" MNPT tapered male threads and 3/8" FNPSM straight mechanical female threads for reliable sealing.
- Industry Compliance: Meets or exceeds ASME B1.20.1 and SAE AS71051 specifications.
- Buy More & Save More: Bulk pricing options available for commercial contractors and OEMs.

Product Specifications

Parts & Accessories > Brass, Plastic, Steel, Stainless Hydraulic Fittings > Stainless Steel Fittings > Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI

Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI

Brand
STAINLESS ADAPTERS / Clean Storm

Part Number / SKU
SS1404-06-06

Fitting Type
Adapter / Non-Live Pipe Swivel

Material Construction
316 Stainless Steel

Connection 1 (Size & Type)
3/8" MNPT (Male Pipe Taper)

Connection 2 (Size & Type)
3/8" FNPSM (Female Pipe Straight Mechanical)

Thread Size
3/8-18 x 3/8-18

Max Pressure Rating
5000 PSI

Max Temperature Rating
1000 °F

Standards Met
ASME B1.20.1, SAE AS71051

Swivel Type
Non-Live (Assembly rotation only; non-rotating under pressure)

Parts & Accessories > Brass, Plastic, Steel, Stainless Hydraulic Fittings > Stainless Steel Fittings > Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI

Clean Storm SS1404-06-06, 316 Stainless Steel Pipe Swivel, 3/8" MNPT x 3/8" FNPSM Non-Live Adapter, 5000 PSI

Cross Reference SKUs

0107-6-6-SS

259-2045-6-6

PS6-6C

SS140466

Y-SS-1404-06-06

Availability: This product was added to our catalog on Friday 10 October, 2025