

>



Model Number: 39003KR

KleenRite 39003KR HeatRite In Line 1750 Watt Heater for Carpet Cleaners AX30 1627-0290

Manufacturer: KleenRite

\*\*\* Built to order, expect over 30 days to receive \*\*\*

HeatRite by KleenRite

The Hydro-Force Hot Shot Heater will make your carpet and upholstery cleaning more effective than ever. Turn your portable into a sizzling heater machine with the Hot Shot. FEATURES: 1750 watts (15 amp) Male 1/4" quick connect output 3' connector hose w/ male & female quick connects Female 1/4" quick connect input 25", 12/3 heavy duty power cord Single switch w/ red indicator light Heavy duty polyethylene casing 17500 watts of heat for carpet cleaning super cleaning! Uses one power cord to operate on a 15 amp breaker 115 volts.

HeatRite Plus® - up to 1750 watts of heat, 6 lb. heat exchanger, single cord operation at 15 amps.

HeatRite® Portable Heater

## Technical Data

1750 Watts 115VOLTS

15 AMPS MAIN CIRCUIT

Water Temp. at Heater Outlet: 190 degrees

Extension Hose: 40 inches

Weight: 25 pounds with case a cord

Compare to current or past OEM associations:

AX30

39003KR

1627-0290

The HeatRite Plus® external in-line heater hooks directly to any carpet extractor or truckmount solution line with a 1/4 inch quick disconnect.

- 1) Fill the fresh water tank with the hottest tap water available. For maximum heat, tap water should be between 120-130 degrees. If hot tap water is not available, cold water can be used, but 3-4 minutes should be allowed for initial heat-up time.
- 2) Hook up short extension hose from heater to female connector on extractor.
- 3) Hook up the solution line to the other brass connector on the heater.
- 4) Plug the heater into a 110-volt wall outlet. If using both heaters, plug both cords into separate circuits (separate from the outlet that the extractor is plugged into.)



- 5) Turn the heater(s) power switch to the "ON" position and prime the pump
- 6) Allow 60-90 seconds for the heated tap water to reach maximum temperature.

Always Made in the U.S.A.

Clean carpets with the added power of super hot water.

Warranty

<p>The HeatRite® In-Line Heater Unit provides additional heated power for cleaner carpets as well as faster drying times.</p> <p>housing</p>	<p>Warranty</p> <p>1 year on parts</p> <p>3 years on</p>
--	--

Choose any of three models to suit your needs:

- HeatRite® - 1750 watts of heat, 6 lb. heat exchanger, single cord operation at 15 amps.
- HeatRite 1® - up to 2250 watts of heat, 11 lb. heat exchanger, single cord operation at 15 or 20 amps.
- HeatRite 2® - up to 3250 watts of heat, 11 lb. heat exchanger, single or dual cord operation at 15/15 amps.

NOTE: Only use a solution hose that can handle up to 3000 p.s.i. at 190 degrees. A lesser grade solution hose could burst, causing serious injury to the operator or damage to surroundings.

Optional

>

## Magnetic Clamp-On Water Softener Descaler for Truckmount & Portable Carpet Cleaning Machines 20260425

- Helps prevent scale buildup in pipes, coils, heaters, and carpet cleaning heat exchangers
- Reduces or eliminates routine monthly descaling in many applications
- Clamp-on installation &mdash; no cutting, plumbing, salt, chemicals, or cartridge replacement
- Maintenance-free design &mdash; no salt, resin, plastic pellets, filters, or media to flush
- Improves heat transfer efficiency by helping keep mineral buildup off heater surfaces
- May improve water flow / GPM by helping reduce mineral restriction over time
- Only 4 inches long for installation in tight areas on portable and truckmount equipment
- Longer Equipment lifespan

20110703dc

*Availability: This product was added to our catalog on Sunday 03 July, 2011*