

>



Model Number: CV25-H

PMF CV25-H Internal Spray Crevice Tool, 19" CURVED HANDLE CREVICE TOOL, 500 PSI Brass Valve, Stainless Steel Hand Wand

Manufacturer: Production Metal Forming

NEW PMF CV25-H 19-Inch Curved-Handle Internal-Spray Crevice Tool with 500-PSI Brass Valve

Gain better control and leverage while cleaning narrow tracks, carpet edges, rug fringe and confined interior spaces. The new PMF CV25-H combines PMF's contained internal-spray crevice-tool design with a curved 19-inch stainless-steel handle. Its curved grip and padded assist handle provide improved positioning while guiding the narrow pickup through difficult cleaning areas.

Manufacturer: Production Metal Forming (PMF)

Part Number: CV25-H

Product Status: New model

Product Type: Curved-handle internal-spray extraction crevice tool

Approximate Overall Length: 19 inches

Vacuum-Tube Diameter: 1-1/2 inches

Valve: Trigger-operated brass valve rated up to 500 PSI

Spray Configuration: Internal spray

Handle Configuration: Curved handle with padded assist grip

Tool-Body Construction: Stainless steel

Manufactured In: USA

New Curved-Handle Design

The CV25-H offers the same basic internal-spray cleaning function as PMF's straight 18-inch CV25SB but adds a curved handle and approximately one additional inch of overall length.

The curved configuration changes the operator's hand position and provides additional leverage while following patio-door tracks, working along carpet edges or positioning the pickup over rug fringe. The padded assist handle provides a second control point for accurate placement and movement.

Contained Internal Spray and Immediate Recovery

The solution jet is positioned inside the vacuum chamber rather than exposed outside the tool. Cleaning solution is applied within the pickup area, where the vacuum can immediately recover loosened soil and moisture.

This internal-spray configuration helps reduce uncontrolled overspray around automobile interiors, furnishings, walls, baseboards and nearby dry surfaces.

Unlike a vacuum-only crevice attachment, the CV25-H applies cleaning solution and performs vacuum recovery through the same tool.

Common Applications

- Sliding-glass patio-door tracks and similar narrow channels
- Controlled extraction cleaning of Oriental-rug fringe
- Automotive carpet beside seats and center consoles
- Spaces between removable upholstery cushions
- Seat seams, pockets and narrow fabric channels
- Carpet edges and perimeter areas along baseboards
- Recreational vehicles, boats and transportation interiors

>

- Confined areas requiring solution application and vacuum recovery

Product Specifications

Brand
PMF / Production Metal Forming

Model / Part Number
CV25-H

Product Type
Professional curved-handle extraction crevice tool

Approximate Overall Length
19 inches

Handle Style
Curved stainless-steel handle

Assist Handle
Padded secondary grip

Vacuum-Tube Diameter
1-1/2 inches

Spray Configuration
Internal spray inside the vacuum chamber

Valve Type
Trigger-operated brass valve

Maximum Valve Rating
500 PSI

Tool-Body Material
Stainless steel

>

Country of Manufacture
USA

CV25-H Versus CV25SB

Feature
CV25-H
CV25SB

Approximate Overall Length
19 inches
18 inches

Handle Style
Curved handle with assist grip
Traditional straight handle

Spray Design
Internal spray
Internal spray

Valve Material
Brass
Brass

Maximum Valve Rating
500 PSI
500 PSI

Primary Advantage
Improved hand position, leverage and control
Traditional compact straight-handle configuration

Sliding-Glass Patio-Door Track Cleaning
The narrow pickup can be guided along sliding-glass patio-door tracks to apply cleaning solution and recover dirty water from the channel. The curved handle and assist grip help the operator follow the track while maintaining control of the pickup. Vacuum or remove loose sand, stones, glass and other debris before wet extraction.

>

Avoid directing water into wall cavities, finished wood, electrical components or areas where moisture cannot be completely recovered.

Oriental-Rug Fringe Cleaning

The internal-spray configuration can be used for controlled cleaning and extraction of Oriental-rug fringe. The curved handle helps the technician guide the pickup along a narrow section of fringe while recovering moisture through the same tool.

Fringe-Cleaning Caution: Fringe fibers, rug dyes and foundation materials can be sensitive to water, heat, alkalinity and aggressive pressure. Identify the fiber, inspect for pre-existing damage and test for colorfastness before cleaning. Use low pressure, suitable chemistry and controlled moisture.

The valve's 500-PSI maximum rating is not a recommended cleaning pressure for Oriental-rug fringe.

Important Pressure Information

The 500-PSI specification is the maximum pressure rating of the brass-valve configuration. It is not a recommendation to clean every material at 500 PSI. Begin at a low cleaning pressure and increase only as required for the material and soil conditions. Select pressure, water temperature and cleaning chemistry according to the material being cleaned. Never exceed the rating of the lowest-rated component in the complete extraction system.

What Is Included

- One PMF CV25-H 19-inch curved-handle internal-spray crevice tool
- Factory-installed 500-PSI brass trigger valve
- Internal solution-delivery components
- Curved stainless-steel handle with padded assist grip

No Quick Disconnect Included: The PMF CV25-H does not include a male or female quick-disconnect fitting. Purchase the connection required for your extractor and solution hose separately.

Most carpet-cleaning systems use a male quick-disconnect plug on the tool, but some systems use the opposite orientation. Verify the connection on your equipment before ordering.

Vacuum hose, solution hose, extractor, cleaning chemicals and optional accessories are not included.

Safe Setup and Operation

- Install a compatible quick-disconnect fitting using the appropriate thread sealant.
- Inspect the valve, solution line, fittings and internal jet before every use.
- Relieve stored solution pressure before connecting, disconnecting or servicing the tool.
- Test the pressure, spray direction, vacuum recovery and material colorfastness in an inconspicuous location.
- Keep the pickup moving and avoid unnecessary saturation.
- Flush chemical residue from the solution path after use and allow the tool to dry before storage.

New-Product Image Notice

Product images are provided for general configuration reference. Because the CV25-H is a new model, some photographs may illustrate the curved-handle concept using a similar PMF crevice tool. Orders from this page are fulfilled as PMF part

>

number CV25-H: the new 19-inch internal-spray crevice tool equipped with a 500-PSI brass valve.

Any quick-disconnect fitting visible in a reference photograph is not included with the CV25-H.

Specifications and product appearance are subject to change without notice. Match the PMF part number, valve rating, handle configuration and required connections before ordering.

Video

Optional

Horse Hair Brush with Comfort Grip Handle For Upholstery Cleaning

Availability: This product was added to our catalog on Thursday 10 September, 2026