

>



Model Number: CV56B-ST

PMF CV56B-ST Crevice Tool 56in Long 1000psi Valve External Open Spray

Manufacturer: Production Metal Forming

PMF CV56B-ST 56-Inch External-Spray Crevice Tool with 1000-PSI Stainless Valve Clean carpet edges and difficult-to-reach areas from a standing position. The PMF CV56B combines a 56-inch stainless-steel crevice wand with an exposed external spray jet, a 500-PSI brass trigger valve and a padded assist handle. Its long reach reduces repeated bending and kneeling while cleaning along walls, behind equipment and between fixed obstacles.

Manufacturer: Production Metal Forming (PMF)

Part Number: CV56B

Tool Type: Long-reach external-spray extraction crevice tool

Approximate Overall Length: 56 inches

Vacuum-Tube Diameter: 1-1/2 inches

Valve: Stainless trigger valve rated up to 1000 PSI

Spray Configuration: External/open spray

Solution Delivery: Stainless-steel solution line with brass VeeJet

Construction: Stainless-steel tool body

Manufactured In: USA

Long Reach for Edge and Detail Cleaning

The 56-inch body allows the operator to remain standing while guiding the narrow pickup along carpet edges and into spaces that a conventional carpet wand cannot reach. A padded assist handle provides a second control point, while the vinyl-covered grip helps protect the operator's hand from direct contact with hot metal. A thumb-operated vacuum-release slide allows the technician to reduce suction when the pickup seals too tightly against carpet or another surface.

Visible External Spray

The brass VeeJet is positioned outside the vacuum chamber, allowing the technician to see where cleaning solution is applied before the pickup recovers the loosened soil and moisture. This open-spray arrangement is useful when direct spray placement and visual control are preferred.

Overspray Notice: Because the jet is exposed, use controlled pressure and trigger operation around walls, finished wood, furnishings, electrical components and other moisture-sensitive surfaces.

Common Applications

- Carpet edges and perimeter areas along walls and baseboards
- Narrow spaces between fixed equipment and furnishings
- Areas behind radiators, appliances and permanently installed objects
- Commercial buildings, theaters, transportation interiors and facility maintenance
- Detailed extraction where a full-width carpet wand cannot fit
- Long-reach cleaning that would otherwise require repeated bending or kneeling

Product Specifications

Brand

>

PMF / Production Metal Forming

Model / Part Number
CV56B-ST

Product Type
Professional long-reach extraction crevice tool

Approximate Overall Length
56 inches

Vacuum-Tube Diameter
1-1/2 inches

Spray Configuration
External/open spray

Spray Jet
Brass VeeJet

Solution Line
Stainless steel

Valve Type
Trigger-operated brass valve

Maximum Valve Rating
1000 PSI

Vacuum Control
Thumb-slide vacuum release

Primary Grip
Heat-protective vinyl covering

Assist Handle
Padded secondary grip

>

Tool-Body Material
Stainless steel

Country of Manufacture
USA

Important Pressure Information

The 500-PSI specification is the maximum rating of the brass-valve configuration—not a recommendation to clean every surface at 500 PSI. Begin at low pressure and increase only as required for the material and soil conditions. The external spray is visible and direct, but excessive pressure can create unnecessary overspray or force moisture into areas that should remain dry. Never exceed the rating of the lowest-rated component in the complete extraction system.

What Is Included

- One PMF CV56B 56-inch external-spray crevice tool
- Factory-installed 1000-PSI Stainless trigger valve
- Stainless-steel solution line
- External brass VeeJet
- Thumb-slide vacuum release
- Vinyl hand grip and padded assist handle

No Quick Disconnect Included: The base CV56B does not include a male or female quick-disconnect fitting. Select the connection required for your extractor and solution hose from the available product options or purchase it separately.

Vacuum hose, solution hose, extractor, cleaning chemicals and optional accessories are not included.

CV56B Versus Other PMF Long Crevice Tools

Model
Spray Type
Valve
Primary Difference

CV56B
External
500-PSI brass
Visible open spray; model offered on this page

CV56B-ST
External
1,000-PSI stainless steel

>

Higher-pressure external-spray version

CV56SB

Internal

500-PSI brass

Spray is contained inside the vacuum chamber

CV56SB-ST

Internal

1,000-PSI stainless steel

Higher-pressure internal-spray version

Safe Setup and Operation

- Install a compatible quick-disconnect fitting using an appropriate thread sealant.
- Inspect the valve, stainless solution line, fittings and external jet before every use.
- Relieve stored solution pressure before connecting, disconnecting or servicing the tool.
- Test the spray direction and pressure away from people and moisture-sensitive property.
- Test the material in an inconspicuous area before cleaning.
- Flush chemical residue from the solution path after use and allow the tool to dry before storage.

Fitment Notice: Similar PMF long crevice tools use different spray arrangements and valve ratings. Match PMF part number CV56B-ST, the 56-inch length, external-spray configuration and 1000-PSI brass valve before ordering.

Availability: This product was added to our catalog on Thursday 10 September, 2026