

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters



Model Number: 20261022

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Manufacturer: Steambrite MFG

Steam-Brite 20261022 Hydraulic Hose Field Repair Kit 3/8" Reusable Male Pipe Hose Ends with Male and Female Swivel Adapters
4-Piece Hydraulic Hose Emergency Repair Kit for 3/8" ID Single-Wire Braided Pressure Hose

The Steam-Brite 20261022 Hydraulic Hose Field Repair Kit provides a convenient solution for repairing compatible 3/8" inside diameter hydraulic and high-pressure hose assemblies in the field.

This four-piece hydraulic hose repair bundle includes two reusable 3/8" male pipe hose repair ends, one male-to-female pipe swivel adapter, and one female-to-female pipe swivel adapter.

The combination allows service technicians to configure several different hydraulic hose end connections using a single repair kit.

Instead of carrying multiple complete hose assemblies, technicians can keep these reusable hose repair components available for compatible emergency hose repairs. Common search descriptions: Hydraulic hose field repair kit, reusable hydraulic hose ends, 3/8" hydraulic hose repair fittings, 3/8" pressure washer hose repair kit, male pipe hydraulic hose fittings, female pipe swivel adapters, field attachable hydraulic fittings, and emergency hydraulic hose repair fittings.

What Is Included in Steam-Brite Kit 20261022?

The Steam-Brite 20261022 bundle includes four individual components representing three different fitting designs.

Quantity	Part Number	Component Description
----------	-------------	-----------------------

2		
---	--	--

	20261338	
--	----------	--

		Reusable 3/8" male pipe hydraulic hose repair fitting for compatible 3/8" ID single-wire braided pressure hose.
--	--	---

Additional part references: 8.705-497.0 and G27100-0606.

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

1
000-052-019
3/8" Male Pipe x 3/8" Female Pipe steel swivel adapter.

Non-live swivel connection.

Additional part references: 6M-6UFS, PHY052-019, and 140466.

1
1405-0606
3/8" Female Pipe x 3/8" Female Pipe steel swivel adapter.

Non-live swivel connection.

Additional part references: 1405-6-6 and AD6FP-6FPX.

Total bundle quantity: 4 individual fitting components.
Steam-Brite bundle part number: 20261022.

Four Hydraulic Hose Connection Configurations from One Repair Kit

The Steam-Brite 20261022 repair kit provides multiple connection options for compatible 3/8" hydraulic and pressure hose assemblies.

Option 1: Fixed Male Pipe x Fixed Male Pipe

Use the two reusable male pipe hose repair ends to create a hose assembly with fixed male pipe connections on both ends.

Connection configuration: 3/8" Male Pipe x 3/8" Male Pipe.

Option 2: Swivel Male Pipe x Fixed Male Pipe

Use a reusable male pipe hose end together with the appropriate male-to-female swivel adapter to provide a male pipe connection with installation swivel capability.

Connection configuration: 3/8" Swivel Male Pipe x 3/8" Fixed Male Pipe.

Option 3: Swivel Female Pipe x Fixed Male Pipe

Use the female-to-female pipe swivel adapter with a reusable male pipe hose end to create a female pipe swivel connection.

Connection configuration: 3/8" Swivel Female Pipe x 3/8" Fixed Male Pipe.

Option 4: Swivel Female Pipe x Swivel Male Pipe

Combine the included reusable hose ends and swivel adapters to create a hose assembly with a female pipe swivel connection on one end and a male pipe swivel connection on the other.

Connection configuration: 3/8" Swivel Female Pipe x 3/8" Swivel Male Pipe.

Important: The adapters included in this kit are non-live swivel fittings. Their swivel function is intended to assist with installation and connection alignment. They are not designed for continuous rotation during equipment operation.

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Reusable 3/8" Hydraulic Hose Repair Ends

Part Number 20261338

The Steam-Brite 20261338 reusable hydraulic hose repair fitting provides a male pipe connection for compatible 3/8" ID single-wire braided pressure hose.

Unlike conventional permanently crimped hydraulic hose fittings, compatible field-attachable reusable hose fittings can be installed using the appropriate tools and approved installation procedures.

This makes reusable fittings particularly useful for equipment maintenance and certain emergency field repairs.

Related Part Numbers

- Steam-Brite 20261338
- Karcher 8.705-497.0
- 87054970
- G27100-0606
- G271000606

These numbers are provided for product identification and cross-reference searches. Verify fitting specifications and compatibility before substituting parts.

3/8" Male Pipe x Female Pipe Swivel Adapter

Part Number 000-052-019

The 000-052-019 steel hydraulic swivel adapter provides a 3/8" male pipe connection on one end and a 3/8" female pipe swivel connection on the opposite end.

This adapter allows a compatible fixed male pipe hose connection to be converted to a different connection configuration.

The non-live swivel design allows the connection to rotate during installation without requiring the entire hose assembly to rotate.

Related Part Numbers

- 000-052-019
- 000052019
- PHY052-019
- PHY052019
- 6M-6UFS
- 140466

Connection: 3/8" Male Pipe x 3/8" Female Pipe Swivel.

Swivel type: Non-live swivel.

3/8" Female Pipe x Female Pipe Swivel Adapter

Part Number 1405-0606

The 1405-0606 hydraulic pipe swivel adapter features a 3/8" female pipe connection on both ends.

This fitting is also commonly identified under the industry part number 1405-06-06.

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

The typical 1405-series configuration uses a fixed female NPTF connection and a female NPSM swivel connection.

This is a female pipe swivel adapter, not a JIC 37-degree flare fitting.

Related Part Numbers

- 1405-0606
- 1405-06-06
- 1405-6-6
- AD6FP-6FPX

Connection Specifications

- Nominal pipe size: 3/8"
- Fixed connection: 3/8" Female Pipe
- Swivel connection: 3/8" Female Pipe Swivel
- Typical fixed thread: 3/8"-18 NPTF
- Typical swivel thread: 3/8"-18 NPSM
- Configuration: Straight adapter
- Swivel design: Non-live
- Material: Steel

Important: Although both ends are commonly described as female pipe connections, the fixed and swivel ends may use different thread and sealing arrangements. Confirm the actual thread specifications and mating fitting requirements before installation.

Hydraulic Hose Repair Kit Cross-Reference Part Numbers

The following part numbers identify the Steam-Brite 20261022 bundle and the individual fitting components included in the kit.

Part Number
Identification

20261022
Complete Steam-Brite Hydraulic Hose Repair Bundle

20261338
Reusable 3/8" Male Pipe Hose Repair End

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

8.705-497.0

Related Karcher Hose Fitting Reference

G27100-0606

Related Reusable Hose Fitting Reference

000-052-019

Male Pipe x Female Pipe Swivel Adapter

PHY052-019

Related Male/Female Swivel Adapter Reference

6M-6UFS

Related Male/Female Swivel Adapter Reference

140466

Related Male/Female Swivel Adapter Reference

1405-0606

Female Pipe x Female Pipe Swivel Adapter

1405-06-06

Alternate Female Pipe Swivel Adapter Number

1405-6-6

Alternate Female Pipe Swivel Adapter Number

AD6FP-6FPX

Related Female Pipe Swivel Adapter Reference

Cross-reference disclaimer: These numbers refer to the individual components or related fitting configurations. They are not all replacement part numbers for the complete four-piece bundle.

Component interchangeability depends on the actual hose construction, dimensions, thread specifications, pressure rating, and sealing requirements.

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Hydraulic Hose Repair Applications

Field-repairable hydraulic hose fittings are commonly used by maintenance professionals working on industrial, commercial, and mobile equipment.

Potential applications for compatible hose assemblies include:

- Hydraulic hose emergency repairs
- Pressure washer hose maintenance
- High-pressure cleaning equipment repairs
- Industrial hydraulic equipment
- Hydraulic power units
- Mobile equipment service
- Construction equipment maintenance
- Agricultural equipment maintenance
- Equipment rental fleet maintenance
- Industrial maintenance departments
- Hydraulic hose service technicians
- Mobile equipment repair vehicles
- Compatible truckmount cleaning equipment hoses

Application suitability must be verified against the hose manufacturer's requirements, operating temperature, pressure, fluid type, and fitting specifications.

Why Keep a Hydraulic Hose Field Repair Kit?

Reduce Equipment Downtime

A damaged hydraulic or pressure hose can interrupt equipment operation.

Keeping compatible reusable hose repair fittings available may allow certain repairs to be completed without waiting for a replacement hose assembly.

Multiple Connection Options

The included swivel adapters provide several connection configurations using the same basic reusable male pipe hose ends.

Convenient for Mobile Service

The compact fitting assortment can be stored in a service vehicle, maintenance toolbox, or equipment repair inventory.

Useful for Emergency Repairs

When properly matched to an approved hose, field-attachable fittings may provide an alternative to replacing an entire hose assembly.

Safety reminder: An emergency field repair must still meet all applicable hose assembly pressure and safety requirements.

Reusable Hydraulic Hose Fittings vs. Permanent Crimp Fittings

Most commercially manufactured hydraulic hose assemblies use permanently attached crimp fittings.

Crimp fittings require specialized equipment to compress the fitting onto the hose.

Reusable hydraulic hose fittings are designed for assembly onto specifically approved hose types without a conventional hydraulic crimping machine.

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

This can be useful when a replacement hose assembly is not immediately available. However, reusable hose fittings are not universal. A fitting approved for one particular 3/8" hose construction may not be compatible with another hose having the same nominal inside diameter. Always follow the fitting and hose manufacturers' installation instructions.

Important Hose Compatibility Information

The reusable hose ends included in Steam-Brite kit 20261022 are identified for compatible 3/8" ID single-wire braided pressure hose.

Before installation, verify:

- Hose inside diameter
- Hose outside diameter
- Hose reinforcement construction
- Hose manufacturer and model
- Fitting-to-hose compatibility
- Thread size and thread type
- Pressure rating
- Temperature rating
- Hydraulic fluid or cleaning solution compatibility
- Required assembly and inspection procedures

Pressure rating: The product listing references applications up to 4000 PSI. The actual allowable working pressure of any repaired assembly must not exceed the lowest rated component, including the hose, fittings, and adapters.

Do not assume that every hose or connection configuration is approved for 4000 PSI.

Hydraulic Hose Repair Safety Information

High-pressure hydraulic and cleaning equipment hoses can present serious injury hazards when improperly assembled or repaired.

- Completely shut down equipment and relieve all system pressure before disconnecting or repairing a hose.
- Allow hot components and fluids to cool before handling.
- Never attempt to repair a pressurized hose.
- Never use your hands to locate a hydraulic fluid leak.
- Use only hose and fitting combinations approved for the application.
- Follow the manufacturer's assembly and inspection instructions.
- Inspect repaired assemblies before returning equipment to service.
- Never exceed the lowest working pressure rating of the complete assembly.
- Do not use non-live swivel fittings in applications requiring continuous rotation under pressure.

Warning: High-pressure fluid injection injuries can occur even through very small leaks. Seek immediate emergency medical treatment if fluid penetrates the skin.

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Frequently Asked Questions

What is included in the Steam-Brite 20261022 hydraulic hose repair kit?

The kit contains two reusable 3/8" male pipe hose repair ends, one 3/8" male pipe to female pipe swivel adapter, and one 3/8" female pipe to female pipe swivel adapter.

How many fittings are included?

The Steam-Brite 20261022 bundle includes four individual components.

What hose size does this kit fit?

The reusable hose ends are identified for compatible 3/8" inside diameter single-wire braided pressure hose.

Hose outside diameter and construction must also be verified.

Are these JIC hydraulic fittings?

No. The fittings in this kit are identified as pipe-thread connections.

The 1405-0606 female pipe swivel adapter is not a JIC 37-degree flare fitting.

What does non-live swivel mean?

A non-live swivel connection permits rotation during installation or connection alignment.

It is not designed for continuous rotation while equipment is operating.

Can these fittings be installed without a hydraulic hose crimper?

The reusable hose ends are intended for field attachment to compatible hose using the appropriate tools and manufacturer-approved procedures.

The installation requirements must be verified for the specific hose and fitting combination.

Can this kit repair pressure washer hoses?

It may be suitable for certain compatible pressure washer hose assemblies when the hose construction, temperature rating, pressure rating, and connection specifications are approved.

Not all pressure washer hoses are compatible with reusable hydraulic hose repair fittings.

Can this kit be used for 4000 PSI applications?

The product is listed for applications up to 4000 PSI, subject to verification of the hose, fitting, adapter, and complete assembly ratings.

The lowest rated component determines the maximum allowable working pressure.

What is the difference between 1405-0606 and 1405-06-06?

These are alternate formatting variations commonly used to identify the same 3/8" female pipe to female pipe swivel adapter configuration.

Can I purchase the components separately?

The kit components are identified individually as 20261338, 000-052-019, and 1405-0606.

Contact Steam-Brite or search the individual part numbers to check component availability.

Order Steam-Brite 20261022 Hydraulic Hose Field Repair Kit

The Steam-Brite 20261022 Hydraulic Hose Field Repair Kit provides reusable 3/8" male pipe hose repair ends and additional male and female pipe swivel connection options in one convenient bundle.

This kit is designed for technicians and maintenance professionals who need

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

compatible hydraulic hose repair components available for field service.

Bundle Part Number: 20261022

Bundle Contents: 4 individual fitting components

Hose Size: 3/8" ID compatible single-wire braided pressure hose

Connection Types: Male Pipe, Male Pipe Swivel, and Female Pipe Swivel

Available from: Steam-Brite, Inc.

For additional hydraulic hose repair fittings, pressure washer parts, and industrial equipment repair supplies, visit Steam-Brite.com.

Product Bundle Number: 20261022

Perfect for carpet cleaning machines, trucks, farm equipment, back hoes, forklifts.
Any item that uses hydraulic fluid or water at high pressure up to 4000 psi.

Bundle includes:

Steambrite 20261338 Reusable Hose Repair End 3/8in Mip X 3/8inID
Single Wire Braided Pressure Hose 8.705-497.0 G27100-0606
2 units

Clean Storm 000-052-019, 3/8in Mip X 3/8in Fip Steel Swivel Fitting,
Not live, 6M-6UFS, PHY052-019, 140466
1 unit

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Clean Storm 1405-0606, 3/8" FIP x 3/8" FIP Steel Swivel Hydraulic
Adapter Fitting, Non-Live, 1405-6-6, AD6FP-6FPX
1 units

Installation Instructions & Reusable 3/8" Hydraulic Hose Repair Fitting (20261338)

The Steam-Brite 20261338 reusable hydraulic hose fitting is designed for field installation on compatible 3/8" ID single-wire braided pressure hose. When installed correctly, this fitting allows a damaged hose end to be replaced without using a hydraulic hose crimping machine.

Step 1 ‐ Cut the Hose Square

Completely depressurize the hose and disconnect it from the equipment. Using a handheld grinder equipped with a suitable cutoff wheel, a hacksaw, or an appropriate hose-cutting tool, cut the damaged hose end off as straight and square as possible. Remove any loose rubber, metal reinforcement fragments, and cutting debris. Make sure the hose opening is clean, round, and free of obstructions.

Step 2 ‐ Install the Outer Reusable Collar

Slide the outer reusable fitting collar over the freshly cut hose end. Rotate the collar counterclockwise to thread it onto the outside of the hose.

Continue threading the collar onto the hose until the hose end reaches the internal stop at the bottom of the collar, following the fitting manufacturer's specified insertion depth.

Important: The outer collar uses left-hand threads. Turning clockwise may loosen or remove the collar rather than install it.

Step 3 ‐ Lubricate the Inner Threaded Insert

Apply a suitable lubricant compatible with the hose material and the fluid being conveyed to the threaded insert and the inside of the hose opening, as permitted by the fitting manufacturer.

Lubrication is important: The threaded insert is intentionally designed to fit very tightly inside the hose. Proper lubrication helps reduce installation friction and allows the insert to advance into the hose without excessive twisting or damage.

Step 4 ‐ Install and Tighten the Threaded Insert

Position the threaded insert squarely into the hose opening. Carefully engage the

Parts & Accessories > Hoses > Repair Hoses > Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

Steam-Brite 20261022 3/8" Hydraulic Hose Field Repair Kit 4000 PSI Reusable Male NPT Ends & Swivel Adapters

insert with the outer collar and rotate the insert clockwise to begin assembly, provided this matches the manufacturer's specified thread direction.

Using appropriate wrenches, hold the outer collar stationary while tightening the threaded insert. Continue until the fitting reaches the manufacturer's specified assembled position or tightening specification.

The insert should fit snugly. However, if excessive resistance occurs, stop and inspect the hose and fitting for incorrect sizing, misalignment, or damaged threads. Do not force the fitting together.

Step 5 – Inspect the Completed Repair

After assembly, inspect the fitting to confirm that the hose is properly seated, the collar has not shifted, and the threaded insert is fully installed according to the manufacturer's instructions.

Before returning the hose to service, follow the applicable manufacturer's inspection and pressure-testing procedures. Keep personnel clear of the hose and connections during testing.

Important Safety Information

- Use only with compatible 3/8" ID single-wire braided pressure hose approved for this fitting.
- Always completely relieve system pressure before cutting or repairing a hose.
- Wear appropriate eye and hand protection when cutting hose, especially when using a grinder or cutoff wheel.
- Remove all cutting debris from the hose before assembling the fitting.
- Use only a lubricant approved for the hose, fitting, and operating fluid.
- Never exceed the lowest rated working pressure of the hose, fittings, adapters, or complete assembly.
- Do not use damaged fittings, excessively worn hose, or hose with compromised reinforcement.
- Never use your hands to check for leaks in a pressurized hydraulic system.

Note: These are general installation guidelines for this style of reusable fitting. Always follow the fitting manufacturer's specific assembly dimensions, tightening requirements, and testing procedures.

Availability: This product was added to our catalog on Thursday 22 October, 2026