

>



Model Number: LWS40-24-81

Link Manufacturing Ramps LWS40 Series Lightweight Straight Ramp 24x81

Manufacturer: Link Manufacturing Ramps

24x81 Lightweight Straight Ramp---LWS40-24-81

All of our Ramp Systems provide protection for your employees and equipment by eliminating the danger of lifting in and out of vehicles. Our systems are proven to increase your job efficiency and reduce the cost of expensive equipment damage. Create for yourself a professional appearance with a Steam Brite Ramp System.

## FEATURES & BENEFITS

- Used for lightweight machines
- 30% lighter than the Model LS50 Ramp
- Rear or side loading
- General use ramp
- Portable
- Custom sizes available

## RAMP SELECTION CHART

Use this chart to choose the appropriate ramp length for your vehicle.

## Uses for Link Ramps

Link Ramps can be used for a variety of purposes. Wheelchair Ramps, Handicap Ramps, Portable Van Ramps, Cargo Van Ramps, Min Van Ramps, Moving Van Ramps, Used Van Ramps, Sprinter Van Ramps, Aluminum Van Ramps, Van Ramps For Wheelchairs, Aluminum Cargo Ramps, Truck Cargo Ramps, Portable Cargo Ramps, Folding Cargo Ramps, Van Cargo Ramps, Cargo Ramps For Trucks, Cargo Ramps for Vans, Pickup Cargo Ramps, SUV Cargo Ramps, Aluminum Utility Ramps, Truck Utility Ramps, Folding Utility Ramps, Utility Ramps, Loading Ramps, Portable Utility Ramps, Commercial Utility Ramps.

>

RAMP CAPACITY RATINGS

There are many methods that are used to give a ramp its loading capacity rating. Do not be fooled by the numbers. Our ramps are rated using a footprint 6" wide by 16" long.

Pressure is applied to the center of the ramp with this footprint. We then apply a three times safety factor to arrive at the weight our ramps are capable of loading safely. This gives you a true capacity rating that has the safety of you and your employees at heart.

Ask your ramp supplier how they arrive at their capacity rating.

LB10 Series  
Side Step Mount (Bifold Design)

Model Number (style-width-length)  
Capacity (lbs)  
Weight (lbs)

LB10-24-54  
1000  
64

LB10-24-72  
1000  
76

LB10-24-81  
1000  
82

LB10-30-54  
1000  
74

LB10-30-72  
1000  
86

LB10-30-81  
1000  
92

>

LB10-36-54  
1000  
84

LB10-36-72  
1000  
96

LB10-36-81  
1000  
102

LB20 Series  
Flat Mount (Bifold Design)

Model Number (style-width-length)  
Capacity (lbs)  
Weight (lbs)

LB20-24-54  
1000  
72

LB20-24-72  
1000  
84

LB20-24-81  
1000  
90

LB20-30-54  
1000  
82

>

LB20-30-72  
1000  
94

LB20-30-81  
1000  
100

LB20-36-54  
1000  
92

LB20-36-72  
1000  
104

LB20-36-81  
1000  
110

LT30 Series  
Flat Mount (Trifold Design)

Model Number (style-width-length)  
Capacity (lbs)  
Weight (lbs)

LT30-24-119  
1000  
110

LT30-30-119  
1000  
125

LT30-36-119  
1000

>

140

LS50 Series  
Heavy Duty Straight Design

Model Number (style-width-length)  
Capacity (lbs)  
Weight (lbs)

LS50-24-54  
1000  
37

LS50-24-63  
1000  
43

LS50-24-72  
1000  
49

LS50-24-81  
1000  
56

LS50-24-90  
1000  
62

LS50-24-99  
750  
69

LS50-24-108  
750  
75

>

LS50-24-117  
750  
81

LS50-24-126  
750  
88

LS50-24-135  
750  
94

LS50-30-54  
1000  
42

LS50-30-63  
1000  
49

LS50-30-72  
1000  
56

LS50-30-81  
1000  
64

LS50-30-90  
1000  
71

LS50-30-99  
750  
78

LS50-30-108  
750  
85

>

LS50-30-117  
750  
92

LS50-30-126  
750  
99

LS50-30-135  
750  
107

LS50-36-54  
1000  
47

LS50-36-63  
1000  
56

LS50-36-72  
1000  
64

LS50-36-81  
1000  
72

LS50-36-90  
1000  
80

LS50-36-99  
750  
88

LS50-36-108  
750  
96

>

LS50-36-117  
750  
105

LS50-36-126  
750  
113

LS50-36-135  
750  
121

Availability: This product was added to our catalog on Thursday 27 October, 2011