Shurflo 8007-543-850, 12 volt 45 psi, Positive Displacement 3 Chamber Diaphragm Pump



Model Number: 8007-543-850

Shurflo 8007-543-850, 12 volt 45 psi, Positive Displacement 3 Chamber Diaphragm Pump

Manufacturer: Shurflo

Positive Displacement 3 Chamber Diaphragm Pump

MODEL NUMBER: 8007-543-850
PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump
CAM: 3.0 Degree
MOTOR: Permanent Magnet, P/N 11-184-04, Fuse Protected, On/Off Switch, Connector
VOLTAGE: 12 VDC Nominal
PRESSURE SWITCH: None
LIQUID TEMPERATURE: 170 Degrees Fahrenheit (77 Degrees Centigrade) Max.
PRIME: Self-Priming Up To 11 Ft. Vertical,
Max. Inlet Pressure 30 PSI (2.1 Bar)
PORTS: 3/8"-18 NPT Female
MATERIAL OF CONSTRUCTION:
PLASTICS- Polypropylene
VALVES- Viton
DIAPHRAGM- Santoprene
FASTENERS- Cad or Zinc Plated Steel
NET WEIGHT: 4.6 Lbs (2.1 Kg)
DUTY CYCLE: Continuous (See Temperature Rise Chart
TYPICAL APPLICATIONS: Agricultural Spraying
BYPASS: 45 PSI

Model

8007-543-850

Description

1.8 GPM open flow, Viton valves, Santoprene diaphragm, 45 PSI Bypass with

Parts & Accessories > Pumps (Water Pumps) > Shurflo Water Pumps > Shurflo 8007-543-850, 12 volt 45 psi, Positive Displacement 3 Chamber Diaphragm Pump

Shurflo 8007-543-850, 12 volt 45 psi, Positive Displacement 3 Chamber Diaphragm Pump

Elect. Pkg., 3/8" NPT-Female ports. w/Manual Switch 2 Pin Connector and Fuse, Poly Housing

Voltage

12 VDC

20121004djc

Availability: This product was added to our catalog on Monday 09 April, 2012

Steambrite Supply