

>



Model Number: 84.519

Mosmatic 84.519, Car Wash Tire Cleaning System DYT, 18.5 in X 14 in

Manufacturer: Mosmatic Pressure Washing Equip

## TIRE CLEANER

The water pressure makes the rotor arm begin to turn on its own. The design is constructed so simply that any maintenance work can be carried out independently and very quickly. These products are found mainly in automatic car wash facilities in the area of rim/tyre cleaning and lateral finish cleaning. It is an efficient and reliable method of achieving optimal cleaning results.

## OPERATION

If water pressure is created, the rotar arm begins to turn on its own. This means that the arm is moved by the recoil force of the water stream alone and requires no additional drive. The housing with the rotar arm can be adjusted for height depending on the area in which it is being used.

## POLISHED STAINLESS STEEL (INOX)

A strong and visually elegant design are a priority for all Mosmatic products. We use polished stainless steel (INOX) for all our products protecting them from rust and extreme weather conditions.

## READY TO INSTALL

All Mosmatic tire cleaner are delivered pre-assembled. You can install the tire cleaner yourself by following the enclosed instructions. The cleaner is ready for immediate use after being connected to the media supply.

## BROCHURE

..Learn more about spinner and swivel options

## OTHER

High RPM Swivels

Swivel, triple bearing system

NW 1/4" - 3/8"

O-ring

4000

>

1000  
90  
DGL

Swivel, triple bearing system, with bulkhead fitting  
NW 1/4" - 3/8"  
4000  
1000  
90  
DGG

Swivel, triple bearing system, with flange  
NW 1/4" - 3/8"  
4000  
1000  
90  
DGF

Swivel, triple bearing system  
NW 1/4"  
Ceramic  
2500  
2000  
40-250  
DXL

Swivel, triple bearing system, with bulkhead fitting  
NW 1/4"  
2500  
2000  
40-250  
DXG

Swivel, triple bearing system, with flange  
NW 1/4"  
2500  
2000  
40-250  
DXF

Swivel, triple bearing system  
NW 1/4"  
Carbide  
4000

>

2000  
250  
DYL

Swivel, triple bearing system, with bulkhead fitting  
NW 1/4" - 3/8"  
4000  
2000  
250  
DYG

Swivel, triple bearing system, with flange  
NW 1/4"  
4000  
2000  
250  
DYF

Swivel, triple bearing system, light  
NW 1/4"  
5000  
2000  
250  
DYW

Swivel, triple bearing system, reinforced  
NW 1/4"  
5000/7300  
2000  
250  
DYC / DYD

Swivel, quadruple bearing system  
NW 1/4" - 3/8"  
5000/7300  
2000  
250  
DYT / DYU

>

*Availability: This product was added to our catalog on Wednesday 11 April, 2012*

Steambrite Supply