Aquatec 12695, 12 Volt 4.2 GPM 45 PSI AP63, Truck Mount Water Transfer Pump, Mytee C361



Model Number: 12695

Aquatec 12695, 12 Volt 4.2 GPM 45 PSI AP63, Truck Mount Water Transfer Pump, Mytee C361

Manufacturer: Aquatec

Aquatec 12695, 12 Volt 4.2 GPM 45 PSI AP63, Truck Mount Water Transfer Pump, Mytee C361

Description

This is the ultimate pump designed to answer all your truckmount transfer pump needs and issues. Also commonly used as a waste water transfer pump, this unit is now utilized on all brand-new professional truckmount installs.

Important Note: Does NOT come with a 3/8" fitting to connect to hoses. The shape of optional filters and/or provided water connection fittings are subject to change based on what the factory provides. We open boxes to verify components, but included items may change without notice. Made in USA.

Features

- Bypass Type 5-Chamber Diaphragm Pump: Effectively resolves the pressure switch failure problems common on typical water transfer pumps.
- Accumulator Compatibility: Works efficiently with or without accumulator tanks.
- Exceptional Motor Life: Permanent magnet (PM) motor features a carbon brush life of more than 1,200 hours.
- Self-Priming: Self-priming capability up to approximately 12 feet.
- Run-Dry Safe: Capable of running dry without damaging the pump.
- Auto Pump-Out Versatility: Can be used for waste auto pump-out systems when paired with a fine large debris filter and a 50-mesh inline filter.
- Protection & Rating: IP55 rated for dust and moisture protection. Thermally protected @ 212°F. 15-amp inline fuse protected (AGC-15A).
- Warranty: Backed by a 1-year limited warranty.

Specifications

Housing Material
Polypropylene

Valves
EPDM

Aquatec 12695, 12 Volt 4.2 GPM 45 PSI AP63, Truck Mount Water Transfer Pump, Mytee C361

Diaphragm
Santoprene

Max Liquid Temperature
140°F

Ports
½” quick disconnect ports (compatible with FLOJET VSD PUMP®)

Open Flow Rate
4.2 GPM @ 5 Amps

Bypass
45 PSI

Max Amps
14 Amp Max Draw (15 Amp recommended fuse protection)

Motor
12 VDC, permanent magnet totally enclosed, non-ventilated (TENV)

Max Motor Surface Temp
Should not exceed 150°F (66°C) for safety, performance, and longevity

Included Accessories
50-mesh inline filter & (2) ½” MPT straight QCPF

Cross Reference SKUs

Aquatec 12695

Steambrite Supply

Aquatec 12695, 12 Volt 4.2 GPM 45 PSI AP63, Truck Mount Water Transfer Pump, Mytee C361

HydroForce AP63

Mytee C361

550222C01-M638EL

Sapphire Scientific 68-002

Toico DDP550

Multi-Sprayer #5502-2C01-M

Multi-Sprayer #5502-2C07-M

5502C01-M638EL

Hydramaster 000-111-591

Optional

Flojet Johnson Pump Strainer Filter 40 Mesh 09-24653-03 Aquatec 25-181

Availability: This product was added to our catalog on Monday 16 July, 2012

Steambrite Supply