

>



Model Number: 3HTLPSQATHP

Little Giant 3HTLPSQATHP Heater 120000 BTU Hotomatic Cart System (High Pressure) **6 MONTH Backorder**

Manufacturer: Little Giant

Little Giant 3HTLPSQATHP Heater 120000 BTU Hotomatic Cart System (High Pressure)

The factory does not supply all the parts to make this a fully functioning system. Please visit link below

Little Giant 15 ft Solution and 6 ft Gas Hose Connection Kit Height pressure models (1000 psi) 20170515

The factory is only supplies the gas hose, the safety valve, and the regulator, the propane bottle, cart, brass "T" and nipple, and the heater. The connections parts are not included.

Little Giant Models 2HT, 3HT, and 4HT Hotomatic® Gas Water Heaters are designed specifically for heating water under pressure - perfect for carpet cleaning. The high capacity thermostat is located in the top coil header.

This cart system has the 3HT High pressure model (pressures up to 1000 psi) All cart system already include the gas hose, gas pressure regulator, striker, and pressure regulator.

The cold water inlet is also connected in the top header above the thermostat's temperature sensing probe. The heater's main burner ignites immediately when water is turned on at the wand. When the water is turned off at the wand the thermostat reacts quickly and turns off when the water reaches the temperature set on its dial. This prompt thermostat action prevents the buildup of very hot water in the wand hose. Tests in our laboratory show a maximum output hot water temperature of 200°F when the thermostat was set on 180°F; and a maximum of 180°F when the thermostat was set on 160°F. This close control of the maximum water temperature is very important.

Extreme water temperatures in the hose reduces its bursting pressure rating. Bursting of a hose by 250°F water at 450 PSI pressure is very dangerous. Extreme water temperature at high pressure will burst into live steam when released through the wand to atmospheric pressure. Live steam will not clean as well as hot water 180° - 200°F. The live steam is also capable of harming the carpet and backing.

The top water inlet is 1/4" Mip. No pressure hose or 90 degree elbow is provided. If you need a pressure hose or brass fitting to hook up your heater, please let us know.

- 120,000 BTU/Hr. Input

>

- Heats: 150 GPH (60°R) = 2.5 GPM (60°R) 90 GPH (100°R) = 1.5 GPM (100°R)

- 40# Tank Size 12" X 14"

with Fuel Gauge and Relief Valve

Holds 5 Gallons of LP Gas

Operating Time Approx. 7-1/2 Hrs.

- Package includes the tank and cart.

-

- Price includes the \$85 Copper surcharge from the factory. Our price saves you \$135 over purchasing factory direct.

- Be sure to check with your local state rules on using propane.

Always store and use propane bottles outside.

Read more about propane use at

<https://www.rrc.state.tx.us/media/8606/homesafehome.pdf>

.Ships in two boxes:

75lbs 19x23x36

88lbs 19x23x36

Little Giant Set Up Diagram

Little Giant Use Instructions

Optional

Propane and Natural Gasline Pipe Thread Sealing (Teflon) Tape 1/2 in X 260 inches 20170513

Availability: This product was added to our catalog on Tuesday 25 September, 2012