

>



Model Number: 8000-532-256

Shurflo 8000-532-256, Positive Displacement 3 Chamber Diaphragm Pump, 115V 100psi, 1.4Gpm
8.689-408.0, Freight Included

Manufacturer: Shurflo

Shurflo 8000-532-256 Positive Displacement 3 Chamber Diaphragm Pump

MODEL NUMBER: 8000-882-288

PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump

CHECK VALVE: (2-Way Op.) Prevents Reverse Flow & 6 Ft. Head Forward Flow

CAM: 2.5 Degree

MOTOR: Permanent Magnet, P/N 11-119-06

VOLTAGE: 115 VDC Nominal

PRESSURE SWITCH: Adjustable Shut-Off (Range 80-100 PSI)

Factory Set @ 100 PSI, Turn On 85 PSI 5 PSI

LIQUID TEMPERATURE: 180 Degrees Fahrenheit (82 Degrees Centigrade) Max.

PRIME: Self-Priming Up To 5.0 Ft. Vertical,

Max. Inlet Pressure 30 PSI (2.1 Bar)

PORTS: 3/8"-18 NPT Female

MATERIAL OF CONSTRUCTION:

PLASTICS- Nylon

VALVES- Viton

DIAPHRAGM- Viton (Switch), Santoprene (Main)

FASTENERS- Zinc Plated Steel

NET WEIGHT: 5.2 Lbs (2.36 Kg)

DUTY CYCLE: Continuous (See Temperature Rise Chart)

TYPICAL APPLICATIONS: Soil Extraction

BYPASS: 80 PSI

Compare to current or past OEM associations:

8.689-408.0

86894080

Availability: This product was added to our catalog on Tuesday 29 January, 2013