

> PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand



Model Number: CV25S-ST

PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

Manufacturer: Production Metal Forming

PMF CV25S-ST 18-Inch Internal-Spray Crevice Tool with 1,000-PSI Stainless-Steel Valve

The high-pressure stainless-valve version of PMF's professional internal-spray crevice tool. The PMF CV25S-ST applies cleaning solution inside the vacuum chamber and immediately recovers loosened soil and moisture. Its slim 18-inch stainless-steel body reaches beside automotive seats, between cushions, along carpet edges and into other confined areas that conventional hand tools cannot access.

Manufacturer: Production Metal Forming (PMF)

Part Number: CV25S-ST

Tool Type: Internal-spray extraction crevice tool

Approximate Overall Length: 18 inches

Vacuum-Tube Diameter: 1-1/2 inches

Valve: Stainless-steel valve rated up to 1,000 PSI

Solution Whip: 6-inch high-pressure hose rated up to 1,250 PSI

Construction: Stainless-steel tool body, solution tubing, jet, nuts and bolts

Manufactured In: USA

Upgraded Stainless-Steel Valve

The CV25S-ST uses a stainless-steel trigger valve rated up to 1,000 PSI. This is the principal upgrade over the PMF CV25SB, which uses a brass valve rated up to 500 PSI. The upgraded valve provides additional pressure capacity for technicians whose extractor and application require it.

The 1,000-PSI rating is the valve's maximum pressure rating—not a recommendation to clean every surface at 1,000 PSI. Select pressure according to the material, soil conditions and extractor manufacturer's instructions. Begin at a lower setting and increase only as necessary.

Contained Internal Spray

The stainless-steel spray jet is positioned inside the vacuum chamber rather than exposed outside the tool. Solution is directed into the pickup area, where the vacuum can recover it immediately. This contained configuration helps reduce uncontrolled overspray around consoles, seats, baseboards and nearby dry surfaces.

A thumb-operated vacuum-release slide allows the technician to reduce suction if the narrow tool seals too tightly against carpet or fabric. The vinyl-covered grip helps protect the operator's hand from direct contact with the metal tube.

Common Applications

- Automotive carpet beside seats and center consoles
- Spaces between removable upholstery cushions
- Seat seams, pockets and narrow fabric channels
- Carpet edges and perimeter areas along baseboards
- Sliding-glass patio-door tracks and similar narrow channels
- Controlled extraction cleaning of Oriental-rug fringe
- Recreational vehicles, boats and transportation interiors

> PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

- Confined areas requiring controlled solution application and vacuum recovery

Patio-Door Track Cleaning

The narrow pickup profile can be guided along sliding-glass patio-door tracks to apply solution, loosen embedded soil and recover dirty water from the channel. Vacuum or remove loose sand, stones and other debris before extraction. Avoid directing solution into wall cavities, finished wood, electrical components or areas where water cannot be completely recovered.

Oriental-Rug Fringe Cleaning

The internal-spray design can also be used for controlled cleaning and extraction of Oriental-rug fringe. It allows the operator to treat a narrow section of fringe while recovering moisture through the same tool.

Fringe-Cleaning Caution: Rug fringe, dyes and foundation fibers may be sensitive to water, heat, alkalinity and aggressive pressure. Identify the fiber, inspect for pre-existing damage and test for colorfastness before cleaning. Use low pressure, appropriate chemistry and controlled moisture. Do not assume the tool's 1,000-PSI maximum valve rating is a suitable cleaning pressure for fringe.

Product Specifications

Brand

PMF / Production Metal Forming

Model / Part Number

CV25S-ST

Product Type

Professional internal-spray extraction crevice tool

Approximate Overall Length

18 inches

Vacuum-Tube Diameter

1-1/2 inches

Spray Configuration

Internal; jet positioned inside the vacuum chamber

Jet / Solution Tube

Stainless-steel jet welded to stainless-steel tubing

> PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

Valve Type
Trigger-operated stainless-steel valve

Maximum Valve Rating
1,000 PSI

Solution Whip
6-inch high-pressure hose

Solution-Hose Rating
1,250 PSI maximum

Vacuum Control
Thumb-slide vacuum release

Grip
Protective vinyl covering

Tool Construction
Stainless steel, including nuts and bolts

Country of Manufacture
USA

CV25S-ST Versus CV25SB

Feature
CV25S-ST
CV25SB

Overall Length
18 inches
18 inches

> PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

Spray Design
Internal spray
Internal spray

Valve Material
Stainless steel
Brass

Maximum Valve Rating
1,000 PSI
500 PSI

Best Choice For
Higher-pressure capability and stainless-valve construction
Standard-pressure cleaning up to 500 PSI

What Is Included

- One PMF CV25S-ST internal-spray crevice tool
- Factory-installed 1,000-PSI stainless-steel trigger valve
- Internal stainless-steel solution tube and jet
- 6-inch, 1,250-PSI high-pressure solution whip

No Quick Disconnect Included: The CV25S-ST does not include a male or female quick-disconnect fitting. Purchase the connection required for your extractor and solution hose separately. Most carpet-cleaning systems use a male plug on the tool, but some systems use the opposite orientation; verify your equipment before ordering.

Vacuum hose, solution hose, extractor, cleaning chemicals and optional accessories are not included.

Safe Setup and Operation

- Confirm that the extractor pressure does not exceed the rating of the lowest-rated component in the complete system.
- Install the correct quick disconnect for your solution-hose configuration using an appropriate thread sealant.
- Inspect the valve, whip hose, fittings and internal jet before every use.
- Relieve stored solution pressure before connecting, disconnecting or servicing the tool.
- Test pressure, spray direction, vacuum recovery and material colorfastness in an inconspicuous area.
- Flush chemical residue from the solution path after use and allow the tool to dry before storage.

> PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand

Fitment Notice: Similar PMF crevice tools are offered with different spray arrangements and valve ratings. Match PMF part number CV25S-ST, the 18-inch internal-spray body, 1,000-PSI stainless-steel valve and required connections before ordering.

This is bested used between 200 and 500 psi but does have a vacuum release thumb slide if you would like to use with extractor under 200 psi.

Optional:

Clean Storm
AB08

Horse Hair Brush with Comfort Grip Handle For Upholstery Cleaning

Options available for PMF CV25S-ST Crevice Tool, 18in Long Internal spray, 1000psi Stainless Steel Valve, Hand Wand :

Quick Disconnect Coupler Needed

Female Stainless Pressure Washer Coupler Style Socket 3/8, Carpet Cleaning Stainless Steel 1/4" Male Quick Disconnect QD 104QDSS NA010, Female Brass Carpet Cleaners Style 1/4, Kaivac Male Quick Connect 1/4in MALE FLO-THRU Plug X BRASS 1/4" FPT [BR335], - None, Male 22mm Brass Plug Screw On, Carpet Cleaning QD35 1/8 inch Male Brass Quick Disconnect Plug Coupler 580-105 PAF03 PC10, Male Stainless Pressure Washer Style Plug 3/8, Carpet Cleaning Stainless Steel 1/4" Female Quick Disconnect QD 104QDSS-S, .Male Brass Carpet Cleaners Style (Default) 1/4, Female 22mm Brass Socket Screw On.

Valve Upgrade

Stainless Steel 1000psi.

Availability: This product was added to our catalog on Tuesday 12 March, 2013