

>



Model Number: VPX34

B-Air Movers VENT VPX34 Carpet Restoration Air Mover 115volt 2530cfm 60Hz [VPX34]

Manufacturer: B-Air Movers

B-air Movers VENT VPX34 Carpet Restoration Air Mover 115volt 2530cfm 60Hz

The B-Air Vent VP-33 was developed with the restoration contractor in mind – low amp, compact size and high CFM. The VP-33 is half the size of any air mover in its class.

The B-Air VP-33 delivers 2530 CFM while using only 2.9 amps. With its low amp draw and on-board GFCI outlet, the Vent VP-33 allows up to 4 units to be daisy chained to a single standard 15 amp household circuit.

The Vent's multipurpose design allows it to be used at 3 different angles (horizontally, 45° and 90°) to allow air flow in the desired direction.

The B-Air Vent housing is constructed of an extremely durable rotationally molded plastic. The powerful 1/3 HP motor in the VP-33 is completely enclosed preventing moisture from entering and damaging the motor's internal componentry. Like all B-Air restoration equipment, the Vent VP-33 is ETL certified for safety.

Due to its lightweight and compact size, the Vent is easy to carry and occupies less space when stored. With interlocking contact points at air intake grills and exhaust ports, the Vent line of air movers can safely and securely stack up to 4 units high. The built in sturdy handles on the Vent air movers not only serve as a proper power cord manager but can also be used to mount the Vent VP-33 in trucks and warehouse storage walls.

VP-33 MODEL SPECIFICATIONS

Voltage
115V

Cycle
60Hz

Max Air Volume
2530CFM

Amps
L 2.6A / H 2.9A

>

Max Static Pressure
1.7"

Weight Net/Gr
26/29 Lbs

Unit Size (LxWxH)
16"x 14.5"x 15.5"

Wheel Speed (RPM)
L1450 / M1620 / H1720

Motor
1/3 HP

Attached Cord (14 G)
25 Ft/14 AWG

Speeds
2

[Print Owner Manual](#)

Availability: This product was added to our catalog on Tuesday 21 May, 2013