Kohler PA-SH265-3056 Courage 6.5hp Horizontal Shaft Engine Shaft 0.78 Diameter x 2.82 PTO Length No Tank No Muffler



Model Number: PA-SH265-3056

Kohler PA-SH265-3056 Courage 6.5hp Horizontal Shaft Engine Shaft 0.78 Diameter x 2.82 PTO Length No Tank No Muffler

Manufacturer: Kohler

Kohler Courage 6.5hp Horizontal Shaft Engine PA-SH265-3056 3/4"X2.38 Shaft Gasoline Engine, 4 Cycle, 6.5 Hp, 3600 Engine Rpm, Gross Torque 6.5 Lbs Ft, Horizontal Shaft Orientation, Fuel Tank Capacity (qt.) 13.5, Overall Width (in.) 14.3, Overall Depth (in.)

6.5hp Kohler Courage Engine
Universal Replacement engine for Power Rakes, Truck Sprayers, Pressure Washers, Tillers, Brick Saws
Replacement engine for GX160
OHV, dual ball bearing PTO, cast iron cylinder liner, Recoil start
2 year consumer warranty, 90 day commercial warranty

Sales Brochure

Owners Manual

Service Manual

Standard Features:
• Overhead Valve Design
• Electronic Ignition
• Dual Element Air Cleaner (Unless otherwise mentioned)
• Dual Oil Fill Locations
• Dual Oil Drains
• Cast Iron Cylinder Liner
• 3.6 L Metal Fuel Tank with Strainer
• Fuel Shut-off Valve (Unless otherwise mentioned)
• Engine Mounted Throttle and Choke Controls, Remote Throttle Ready
• Oil SentryTM Switch Installed (No Light)
• Dual Ball Bearings, PTO and Flywheel
• Metal Blower Housing
• Indexable Recoil Starter
• PTO Face
• For engines with SAE crankshaft: 3.625” (92.08 mm) Diameter (4 + 1 Holes) 5/16-24 UNF-2B Thread.
• For engines with Metric crankshaft: 3.625” (92.08 mm) Diameter (4 + 1 Holes) M8x1.25-6H Thread.

Steambrite Supply

Parts & Accessories > Engines > Kohler 3000 Series 6.5hp PA-SH265 > Kohler PA-SH265-3056 Courage 6.5hp Horizontal Shaft Engine Shaft 0.78 Diameter x 2.82 PTO Length No Tank No Muffler

Kohler PA-SH265-3056 Courage 6.5hp Horizontal Shaft Engine Shaft 0.78 Diameter x 2.82 PTO Length No Tank No Muffler

• Large Capacity Muffler w/Heat Shield
• Multi-Lingual Owner’s Manual
• Color - Black with Cast Aluminum
• Important Compliance Information:
1.Specs containing -3XXX are CARB Tier III, EPA Phase 3 and RFI compliant (Can be sold globally)
2.Specs containing -0XXX are EU Stage 2 and RFI compliant (For sale in EU, Australia and New Zealand)
3.Specs containing -1XXX do not meet any compliance. These engine cannot be sold in US, Canada, EU,
Australia and New Zealand (For sale in rest of the world)
Ship Weight 40 lbs

Standard Features Plus:
• Crankshaft - 0.78” Diameter x 2.82” PTO Length, w/2.25” per foot taper, Fixed Speed 60 Hertz (3750 rpm HSNL)
• Low Profile Air Cleaner
• No Fuel Tank, No fuel shut-off valve
• No Muffler

Also marketed under part number SH265-0056 and SH265-1056

Availability: This product was added to our catalog on Saturday 20 July, 2013

Steambrite Supply