

>



Model Number: 31.902
Mosmatic 31.902 DGLI 303 AISI In-Line Stainless Swivel 3/8in Fip X 3/8in Mip Triple Bearing System
Manufacturer: Mosmatic Pressure Washing Equip
Mosmatic 31.902 DGLI In-Line 303 All Stainless Swivel 3/8" Fip X 3/8" Mip Triple Bearing Seal

Technical Specifications

Boom Compatible
Yes

Female NPTF
3/8" Fip X 3/8" Mip

Flange Type
Inline

Low RPM
No

Manufacturer
Mosmatic

PSI
4000

RPM
30

Swivel Type
DGL

Temp in Fartenheit

>

250

Technical data

Pressure
4000 psi

Temperature
90°F (at 1'000 rpm)
250°F (at 30 rpm)

RPM
max. 1'000 rpm

Body
DGL: brass, nickel plated
DGLI: all 303 stainless steel

Inner part
stainless steel

Seal
O-ring

Bearing
2x radial ball bearings
1x thrust ball bearing

Throughput medium
pH 3-12

Features

triple bearing system

>

stainless
live swivel
maintenance free
compact

Applications

self rotation applications
high pressure cleaning technology
part cleaners
tire cleaners

Sales Brochure

Availability: This product was added to our catalog on Friday 03 January, 2014