Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 31.657 DGL In-Line High Pressure Brass Stainless Swivel, 1/4in Fip X 18-1.5M, 275 bar, 4000 PSI, 120Â°C, 250Â°F, Male, Triple Bearing System

Mosmatic 31.657 DGL In-Line High Pressure Brass Stainless Swivel, 1/4in Fip X 18-1.5M, 275 bar, 4000 PSI, 120Â°C, 250Â°F, Male, Triple Bearing System



Model Number: 31.657

Mosmatic 31.657 DGL In-Line High Pressure Brass Stainless Swivel, 1/4in Fip X 18-1.5M, 275 bar, 4000 PSI, 120Â°C, 250Â°F, Male, Triple Bearing System

Manufacturer: Mosmatic

Mosmatic 31.657 DGL In-Line High Pressure Brass Stainless Swivel, 1/4in Fip X 18-1.5M, 275 bar, 4000 PSI, 120°C, 250°F, Male, Triple Bearing System
Description
Prevent tangled hoses and maximize your equipment's lifespan with the premium Mosmatic 31.657 In-Line Swivel. Engineered and manufactured in Switzerland, this heavy-duty rotary union offers smooth, live rotation even under maximum pressure load. Its robust stainless steel internal construction and advanced seal layout deliver maintenance-free operation and unmatched reliability in the most demanding car wash, pressure washing, and industrial fluid applications.
Applications

- Commercial Car Wash Systems
- Professional Pressure Washing
- Industrial Fluid Handling
- Self Rotation Applications
- High Pressure Cleaning Technology
- Part Cleaners
- Tire Cleaners

Features

- Live Rotation at Max Pressure: Allows independent, fluid rotation under a continuous operating pressure of up to 275 bar (approx. 4000 PSI).
- High Temperature Tolerance: Rated to withstand demanding hot water applications up to 120°C (250°F).
- Swiss Engineering: Crafted from ultra-durable, corrosion-resistant stainless steel components to prevent leaks and maximize longevity.

Mosmatic 31.657 DGL In-Line High Pressure Brass Stainless Swivel, 1/4in Fip X 18-1.5M, 275 bar, 4000 PSI, 120Â°C, 250Â°F, Male, Triple Bearing System

- Hose Protection: Significantly reduces wear and tear on expensive high-pressure lines by neutralizing torsional stress.

- Maintenance-Free Design: Built with pre-lubricated internal bearings and robust seals for long-lasting, hassle-free performance.

Specifications

Boom Compatible
Yes

Female NPTF
1/4" Fip X 18-1.5M Male

Flange Type
Inline

Low RPM
No

Manufacturer
Mosmatic

PSI
4000

RPM
30

Swivel Type
DGL

Temp in Fartenheit

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 31.657 DGL In-Line High Pressure Brass Stainless Swivel, 1/4in Fip X 18-1.5M, 275 bar, 4000 PSI, 120Â°C, 250Â°F, Male, Triple Bearing System

Mosmatic 31.657 DGL In-Line High Pressure Brass Stainless Swivel, 1/4in Fip X 18-1.5M, 275 bar, 4000 PSI, 120Â°C, 250Â°F, Male, Triple Bearing System

250

Additional Information
Sales Brochure

Availability: This product was added to our catalog on Saturday 04 January, 2014

Steambrite Supply