Mosmatic 32.082, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 5/16in Barb, 4000 psi



Model Number: 32.082

Mosmatic 32.082, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 5/16in Barb, 4000 psi

Manufacturer: Mosmatic

Mosmatic 32.082, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 5/16in Barb, 4000 psi

Description

The Mosmatic DGK Swivel 32.082 is a compact and durable nickel-plated brass and stainless steel swivel engineered for high-pressure guns, hydraulic systems, hose connections, and tangle-free applications. Designed for smooth rotation under pressure, this swivel delivers maintenance-free performance and exceptional durability.

Built with a thrust ball bearing and a robust O-ring NBR seal system (with optional EPDM or FKM), the DGK 32.082 enables live rotation even at maximum pressure, offering exceptional maneuverability for demanding cleaning and industrial environments.

Applications

- High-pressure guns and lances
- Hydraulic hose connections
- Ceiling booms and hose reels
- Tangle-free hose systems
- Compact industrial machinery

Features

- Model: Mosmatic DGK 32.082
- Material: Nickel-plated brass and stainless steel
- Thread IN (G1): 1/4" NPTM
- Seal System: O-ring NBR (optional EPDM or FKM)
- Bearing: 1x thrust ball bearing
- Low Torque: Smooth rotation under pressure
- Maintenance-Free: Sealed system, long service life

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.082, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 5/16in Barb, 4000 psi

Mosmatic 32.082, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 5/16in Barb, 4000 psi

- Diameter: 0.33"
- Overall Length: 2.63"
- Nominal Width (NW): 7/32"
- Wrench Size (SW): 0.94"
- Max Pressure: 4000 PSI
- Max RPM: 30
- Max Temperature: 250°F

Specification
Pressure: 4000 psi (27.5 MPa)
Temperature: 250°F
RPM: max 30 rpm
Material Type: Stainless steel, Brass, Nickel plated
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread In: G1 1/4" NPTM
S1: 5/16"
Nominal Width (NW): 7/32"
Wrench Size 1 (SW1): 0.94"
Length 1 (L1) (overall length) : 2.63"
Length 2 (L2): 0.39"
Diameter 1 (D1): 0.33"
Diameter 2 (D2): 0.34"
Diameter 3 (D3): 0.44"
Weight: 2.8 oz
Additional Information
Sales Brochure

Availability: This product was added to our catalog on Saturday 04 January, 2014

Steambrite Supply