Mosmatic 32.153, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 3/8in Mip, 4000 psi



Model Number: 32.153

Mosmatic 32.153, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 3/8in Mip, 4000 psi

Manufacturer: Mosmatic

Mosmatic 32.153, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 3/8in Mip, 4000 psi

Description

The Mosmatic DGK Swivel 32.153 is a compact, high-performance swivel engineered for high-pressure spray guns, hose connections, hydraulic systems, and tangle-free hose applications. Constructed from nickel-plated brass with stainless steel components, it delivers excellent corrosion resistance and long-term durability.

Equipped with a thrust ball bearing and O-ring NBR seal system (optional EPDM or FKM), this swivel enables live rotation at maximum pressure with very low torque. The maintenance-free design ensures reliability and smooth performance in even the most demanding settings.

Applications

- High-pressure spray guns
- Hose connection systems
- Hydraulic line installations
- Ceiling booms and wash bays
- Industrial and automotive cleaning setups

Features

- Model: Mosmatic DGK 32.153
- Material: Nickel-plated brass and stainless steel
- Thread IN: 3/8" NPTM
- Thread OUT: 3/8" NPTM
- Seal System: O-ring NBR (optional EPDM or FKM)
- Bearings: 1x thrust ball bearing
- Design: Compact, corrosion-resistant, low-torque rotation
- Live Rotation: At full operating pressure

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.153, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 3/8in Mip, 4000 psi

Mosmatic 32.153, DGK Inline Single Bearing Economy Swivel, 3/8in Mip X 3/8in Mip, 4000 psi

- Overall Length: 2.13"
- Nominal Width (NW): 1/4"
- Wrench Size (SW): 0.94"
- Max Pressure: 4000 PSI
- Max RPM: 30
- Max Temperature: 250°F

Specification
Pressure: 4000 psi (27.5 MPa)
Temperature: 250°F
RPM: max 30 rpm
Material Type: Stainless steel, Brass, Nickel plated
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread In: G1 3/8" NPTM
Thread In: G1 3/8" NPTM
Nominal Width (NW): 1/4"
Wrench Size 1 (SW1): 0.94"
Wrench Size 2 (SW2): 0.75"
Length 1 (L1) (overall length) : 2.13"
Length 2 (L2): 0.43"
Length 3 (L3): 0.47"
Weight: 4.2 oz
Additional Information
Sales Brochure

Availability: This product was added to our catalog on Saturday 04 January, 2014

Steambrite Supply