

>



Model Number: HTXS1812S

General Pump HTXS1812S, Emperor Run 3.2/3.8gpm 2000psi 1450/1750rpm, High Temperature

Manufacturer: General Pump

General Pump HTXS1812S

3.8gpm/ 1750 rpm or 3.2gpm/1450rpm

Emperor Run Dry

Handles super 185 degree F inbound hot water!

- Features patent-pending high tech packings
- Solid ceramic plungers
- Patent-pending inlet/outlet valve cage
- Nickel-plated inlet/outlet valve plugs
- Nickel-plated forged brass manifold with exclusive lifetime warranty
- Specifically designed to handle rigorous duty cycles, high temperatures and chemicals
- Ideal for use in carpet cleaning and other high pressure cleaning applications

## SPECIFICATIONS - HTX1812S

Maximum Volume  
3.8 gpm

Max. Discharge Pressure  
2500 psi

Maximum Pump Speed  
1750 rpm

Maximum Inlet Pressure  
125 psi

Maximum Inlet Vacuum  
3 ft. water (2.6 in Hg)

Bore  
.709 in / 18 mm

Stroke  
.512 in / 13 mm

>

Crankcase Oil Capacity  
14.0 oz

Maximum Fluid Temperature  
185&deg;F

Inlet Port Thread  
1/2-14 BSP-F

Discharge Port Thread  
3/8-19 BSP-F

Shaft Diameter  
.945 in / 24 mm

Weight  
18 lbs

Dimensions  
8.4 x 8.3 x 5.6 in

Also Marketed under part number AP56  
Inventory Part HTXS1812S  
UPC 682491043201  
General pump Maintenance Guide  
Sales Brochure

Used on the Sapphire Scientific 370SS Truckmount  
Sales tax collected in TX and CA

*Availability: This product was added to our catalog on Saturday 08 February, 2014*