

>



Model Number: 39011

KleenRite 39011 HeatRite 2 In Line Heater for Carpet Cleaners 3250 watts

Manufacturer: KleenRite

KleenRite 39011 HeatRite 2 In Line Heater for Carpet Cleaners 3250 watts

HeatRite 2 by KleenRite

When you don't own a truckmount carpet cleaning machine, this becomes your best friend. Super heat you portable carpet cleaning equipment outbound water.

3250 watts of heat for carpet cleaning super cleaning!

Uses two 15 amp cords on two different breakers.

HeatRite 2®; - up to 3250 watts of heat, 25 lb. heat exchanger, single or dual cord operation at 15/15 amps.

HeatRite 2®; Portable Heater

Technical Data

3250W 115VOLTS

15 AMPS MAIN CIRCUIT

12 AMPS AUX. HEATER

Water Temp. at Heater Outlet: 190 degrees

Extension Hose: 40 inches

Weight: 25 pounds

500 psi max pressure

Model No. 39011

The HeatRite 2®; external in-line heater hooks directly to any carpet extractor or truckmount solution line with a $\frac{1}{4}$ inch quick disconnect.

- 1) Fill the fresh water tank with the hottest tap water available. For maximum heat, tap water should be between 120-130 degrees. If hot tap water is not available, cold water can be used, but 3-4 minutes should be allowed for initial heat-up time.
- 2) Hook up short extension hose from heater to female connector on extractor.
- 3) Hook up the solution line to the other brass connector on the heater.
- 4) Plug the heater into a 110-volt wall outlet. If using both heaters, plug both cords into separate circuits (separate from the outlet that the extractor is plugged into.)
- 5) Turn the heater(s) power switch to the "ON" position and prime the pump
- 6) Allow 60-90 seconds for the heated tap water to reach maximum temperature. Please note that all electric heaters work best if you start out with hot water from the

>

customer's building.

Always Made in the U.S.A.

Clean carpets with the added power of
super hot water.

Warranty

The HeatRite 2®; In-Line Heater Unit
provides additional heated power for cleaner carpets
as well as faster drying times.
housing

Warranty
1 year on parts
3 years on

Choose any of three models to suit your needs:

- HeatRite®; - 1750 watts of heat, 6 lb. heat exchanger, single cord operation at 15 amps.
- HeatRite 1®; - up to 2250 watts of heat, 11 lb. heat exchanger, single cord operation at 15 or 20 amps.
- HeatRite 2®; - up to 3250 watts of heat, 11 lb. heat exchanger, single or dual cord operation at 15/15 amps.

NOTE: Only use a solution hose that can handle up to 3000 p.s.i. at 210 degrees. A lesser grade solution hose could burst, causing serious injury to the operator or damage to surroundings.

Availability: This product was added to our catalog on Sunday 06 February, 2005