


>



Model Number: Volcano 5600

Clean Storm Hot Box Volcano 5600 Watt Tankless Electric High Pressure Water Heater

Manufacturer: Clean Storm

Clean Storm Hot Box Volcano 5600 Watt Tankless Electric High Pressure Water Heater

The only electric heating system that hooks to your portable or truck mount extractor and has three times the heating capacity of standard 2000 watt heaters. When tested using a floor wand on wide open spray (never letting go), using cold water (65 degree F.), the Volcano 5600 will produced a full 100 degree temprature rise to 165 degrees. With squeezing trigger 50% of the time (like cleaning carpet) the Volcano 5600 produces a 150 degree temperature rise up to 210 degrees! Now that is Hot! We do not recommend that you clean carpet or feed this heater with cold water. This test was performed so you can see how well it works. Always fill your portable carpet cleaning machine with hot water.

You can operate this heater in the following wattage configurations.

1800 watt heater on one 15 amp outlet

3600 watt heater on two 15 amp outlets

2000 watt heater on one 20 amp outlet

3800 watt heater on one 20 and one 15 amp outlets (two total)

5600 watt heater on three 120 volt outlets (two 15's and one 20) or a standard electric close dryer with optional 240 to 120 converter set (plugs into either a 3 or 4 prong dryer outlet)

**** Product sent may differ from product shown. We are currently using a new plastic casing in order to increase life and functionality of product. Additionally, LED's and other aesthetic features may differ from product shown in video below.****

CAUTIONS:

DO NOT OPEN THE HEATER WITH THE UNIT PLUGGED IN.

DO NOT LEAVE UNIT UNATTENDED OR UNSUPERVISED.

DO NOT LEAVE UNIT ON DURING PERIODS OF NON USE

(IF YOU AREN'T CLEANING, TURN THE HEATER OFF)

DO NOT OPERATE HEATER IF IT IS NOT WORKING PROPERLY.

DO NOT OPERATE HEATER IF IT IS LEAKING WATER INTERNALLY OF EXTERNALLY.

DO NOT PLUG UNIT IN IF IT IS WET FOR ANY REASON.

DO NOT USE HEATER IF ANY OF THE ELECTRICAL OR PLUMBING CONNECTIONS ARE LOOSE.

DO NOT RUN FLAMMABLE SOLVENTS IN HEATER.

DO NOT USE AT PRESSURES OVER 500 PSI.

>

USE CAUTION AND COMMON SENSE WHEN HANDLING METAL HOSE ENDS AND FITTINGS ON THE HOT OR DISCHARGE SIDE OF THE HEATER. THESE METAL FITTINGS CAN BE HOT ENOUGH TO CAUSE SERIOUS DISCOMFORT AND BURNS.

USE 12-3 GAUGE POWER EXTENSION CORDS IF USING INDIVIDUAL EXTENSION CORDS (NOT INCLUDED)

PLACE OVER PRESSURIZATION HOSE BACK INTO SINK OR FRESH WATER TANK!

We combined our 3600 watt heater with our 2000 watt heater all inside one housing.

Factory installed

.Clean Storm Hot Box Volcano 2000 Watt In-line Compact Heater For Carpet Cleaning Equipment 120 volts for 20 amp breakers

Plus factory installed

Clean Storm Volcano 3600 Portable Heater Double Heat for Carpet Cleaning Equipment
All inside one housing!

New design allow for more ways to plug in. Use as much or little electricity that you have available. Now portable extractors have the power to clean tile and grout. What your portable can't make up in pressure, it will now make up in heat. A full 5600 watts of heat is built inside an insulated stainless steel heating system. It plugs into your customer's 3 or 4 prong electric dryer outlet (with optional adapter to plug into either one) or one, two or three standard 120 volt wall outlets (optional 12-3 power cords). Please note the 2000 watt heater should be plugged into a 20 amp breaker or the 20

>

amp side of the converter box. The other two power cords can be plugged into 15 amp outlets. Just use what ever power is available from your job site.

The flow of the water is the water travels through the 2000 watt heater first (photo of heat cylinder on far right side) and then splits and travels through the 3600 watt combo heater, then out to your wand. The water enters the heater on the thermostat side and then leaves the far (top) side. Each heating rod is controlled by two thermostats. Each thermostat must give permission that the outer casing is under 195 degrees before it is allowed to heat.

The Volcano 5600 features:

- a check valve for pump head back pressure,
- Compact design with lock and easy carry handle.
- a 1000 psi safety release valve,
- built in bank- 3 each- 20 amp circuit breaker system,
- insulated quick disconnect,
- 6 LED lights come on as each of the six heating rods cycle on to maintain the temperature,
- 3 led light come on as each heating system is on.
- Includes jumper hose from carpet cleaning extractor to heater with male and female QD and check valve.
- Includes over pressurization hose (place back in sink or fresh water tank)
- Use indoors (unlike propane)

Entire unit weighs only 25 lbs.

Measures 24" long, 13" deep, 6" tall.

Working range 50 to 500psi.

Six thermostat controls.

Heater and cord store inside a durable but light weight, sturdy metal housing.

Heat like propane, but without the dangers.

Turn your extractor into a steam cleaner today!

Estimated savings over LP / Propane 500 hours a year at \$3.50 per hour = \$1750 a year!

Even after you purchase this heat + extended warranty + three 12-3 power cords + 230 volt power cord and two adapters, return on investment is only one year!

(Tim Taylor The Tool Man would want this one - More Power!) One year parts warranty.

P.S. Please do not try to go through the airport with this heater as I am sure you will be detained!

Made from and with the following parts:

Factory Installed

>

Meters Lights Camera Storage 18" X 13" X 6" Aluminum Case

or similar

We are trying to only build in plastic housings from now on.

Factory Installed

3 units

Clean Storm Carpet Cleaners Heater Core Dual Element Stainless Steel
Housing Case

Factory Installed

3 units

Cord Male Pigtail 12-3 13 inches over all length

Factory Installed

AS56A 1/4in Fip Insulated Safety Female Quick Disconnect Foster QD
Samdx With Nipple Stop Carpet Cleaning Style

Factory Installed

Foster QD 1/4in Male Quick Disconnect B101 NA0801 PX5

>

Factory Installed
9 units
Circuit Locator Green Neon LED Light 120-240 volts AC 1/4in EZ Disconnects
SBM8359 1/2in Hole Mounting SBM8359

Factory Installed
2 units
Clean Storm 1000 Watt Heating Rod Element Heater repair 115 volts E519
10-1500-A Rotovac TE228100 [SBME519F]

Factory Installed
4 units
Clean Storm Rod Style Heating Element - 1750 -1800 watt Heater
replacement 12381.18

Factory Installed
3 units
Switch Toggle Stainless W/ Spade Connect Single Pole Single Throw
Approved for 20 amp 125 volts or 12 amps 250 volts

>

Factory Installed
6 units
Clean Storm Panel Mount 10 amp push button resettable breakers 420810

Optional

Electrical Converter 230 Volt 3 wire/prong 30 amp TO 115 Volt 3 Gang (6
Outlets) Adapter NEMA 10-30P to NEMA 5-20R Starter Package

Power Cord Adapter 230 Volt 4 Wire/Prong 30 amp 14-30P Converts TO 230
volt 3 Wire 30 amp Receptacle 10-30R

Extension Power Cord 12-3 25 feet Heavy duty Mytee E531 10-0860

Truckmount and Portable Pressure and Temperature "Billy" Gauge Tester

>

Clean Storm Truck Mount Portable temperature gauge 20130815
Thermometer

Clean Storm Portable Extractor & Dehumidifier Drip Tray

Availability: This product was added to our catalog on Sunday 06 February, 2005