

>



Model Number: 860432

Nikro 860432, 12in Adjustable Wall and Ceiling Mounting Flange, with Pole For Vent Registers

Manufacturer: Nikro

Nikro 860432 12in Adjustable Wall and Ceiling Mounting Flange  
Description

12" Adjustable Wall and Ceiling Mounting Flange Adjustable from 6' to 12' High. Allows you to connect your vacuum to wall and ceiling registers. The Flange has 2 1/2" and 1" ports. Includes adjustable pole!

**POGO POLE HOSE ADAPTER**The Pogo Pole hose adapter is the quickest way to attach an Air-Care Turbojet or other brand negative air machine to a ceiling or wall duct. The 20" x 20" molded poly adapter plate has a 2" foam seal that will protect delicate walls and ceiling during cleaning. The pole is spring-loaded

and has adjustable height to provide gentle, yet firm, pressure on most ceilings or wall connections and will often work well on acoustic drop ceiling vents. The durable molded poly adapter plate has a 4" access plug for Cobra brush air tools. This tool will save valuable time making the duct connection and is easily moved to a new location in less than a minute.

The Pogo Pole is adjustable for 5.5 to 12 foot ceilings and the plate swivels 45 degrees in both directions for placing it on high mounted wall duct openings. The bottom of the pole has an anti-slip protective rubber foot for tile and vinyl floors. The Pogo Pole hose adapter has a 12" collar that mates with the 12" Light Duty Mylar hose assembly. Item# CE1630D

#### 12" LIGHT DUTY MYLAR HOSE ASSEMBLY

12" light duty Mylar hose is clear vacuum hose with steel wire reinforcement. Includes: 12" x 12" hoses (2), hose clamps (4), hose coupler (1)

>

## OPTIONAL ACCESSORIES ITEM#

(1)

12" x 12.5' light duty mylar hose assembly  
Includes: 12" x 12.5' hoses (2), hose clamps(4), hose coupler

CE1339A

12" x 12.5' light duty mylar hose with clamps  
CE1341A

12.5" - 14.5" hose clamps  
2997A

12" hose coupler  
2000

## AIR HOSE

50' of 3/8" dia. high visibility PVC non-scuff hose with quick connectors. This heavy duty hose is rated at 300 PSI working pressure. The Sidewinder and other air-powered devices can be operated several hundred feet from the compressor. Long lengths of hose will act like auxiliary air storage and do not generally impair equipment performance. Includes (1) male & (1) female quick disconnect fittings. Item# CE1507

>

old web page above -->

---

*Availability: This product was added to our catalog on Tuesday 08 May, 2007*