

>



Model Number: F405

Drieaz F405 Sto and Go Ducting with storage bag Freight Included

Manufacturer: Drieaz

Drieaz Sto & Go Ducting F405 Stow

Item #F405

Sto & Go

Easily ventilate hard-to-reach spaces. Includes 25 feet of collapsible 12-inch ducting. Connect one or more sections of ducting to the Vortex Axial Fan for powerful ventilation.

Recommended for use with:

Nikro US4000 Duct Cleaner and Air Scrubber

Ebac PF400 Axial

Drieaz 2800i

Drieaz 3500i

Drieaz Air Wolf

Vortex Axial Fan

DriStorm Blast

STO & GO SPECS:

Model

F405 G1795726

5UNZ9

>

Temperature Range  
-20&deg;F to 180&deg;F / -29&deg;C to 82&deg;C

Material  
PVC Flame Retardant Vinyl

## Product Features

Built-in bag with sturdy handle contains and protects ducting during transport and storage  
Semi-rigid ducting constructed with spring steel wire helix resists collapse under negative pressure  
Black reinforcement strips protect internal wire to ensure long service life  
Made of PVC-coated polyester fabric  
Temperature range: -20 to 180 degree F  
ASIN: B00AB255L6  
Shipping Weight: 22 pounds

10130115djc

Drieaz Sto & Go Ducting F405 Stow

Drieaz AirWolf Hardwood Floor Drying Unit F228 230volt



AirWolf  
Item #F228-230V

AIRWOLF SPECS

Model  
F228

Height  
17" / 43 cm

Width  
21" / 53 cm

Depth  
16" / 41 cm

Weight  
35 lb / 16 kg

Motor

>

1.0 hp

Motor Speeds  
1-speed

Max. CFM  
(Free Air)  
800

Max. CFM (Full Load)  
450

Static Pressure  
(Free Air)  
7.75" / 19.7 cm

Static Pressure  
(Full Load)  
5" / 13 cm

Power (Free Air)  
11.6 amps

Power (Full Load)  
8.5 amps

Stackable  
Yes

UL Listed  
Yes

>

## AirWolf/WolfPack Hardwood Floor Drying System

### Dry Hardwoods Fast!

The AirWolf uses an unbeatable combination of CFM and static pressure to literally force water out of damaged hardwood floors. The WolfPack system directs the high-velocity airflow of the AirWolf into the flutes between the flooring and the subfloor. This way the floor actually dries from the bottom out.

### Avoid Refinishing Costs

The AirWolf/WolfPack can dry out a hardwood floor in as little as 3 days! By drying fast from beneath, the AirWolf/WolfPack system can help reduce or eliminate cupping and associated refinishing costs. This means no sanding! Now that's a valuable service to offer your customers.

The world's best hardwood floor drying system  
Up to 800 CFM and 7.75" of static pressure  
Powerful 1.0 hp motor  
Stack the AirWolf for storage  
Carrying case included for WolfPack attachments

-->

*Availability: This product was added to our catalog on Friday 08 February, 2008*