PMF CV25SB Internal Spray Crevice Tool, 18in Long, 500 PSI Brass Valve, Hand Wand, AW49 Stainless Steel Body



Model Number: CV25SB

PMF CV25SB Internal Spray Crevice Tool, 18in Long, 500 PSI Brass Valve, Hand Wand, AW49 Stainless Steel Body

Manufacturer: Production Metal Forming

PMF CV25SB 18-Inch Internal-Spray Crevice Tool with 500-PSI Brass Valve
Apply cleaning solution and recover it from narrow spaces while keeping the spray contained inside the tool. The PMF CV25SB is a professional stainless-steel extraction crevice tool designed for automotive interiors, upholstery seams, carpet edges and other confined areas that conventional hand tools cannot reach.
Manufacturer: Production Metal Forming (PMF)
Part Number: CV25SB
Alternate Distributor Number: AW49
Tool Type: Internal-spray extraction crevice tool
Approximate Overall Length: 18 inches
Vacuum-Tube Diameter: 1-1/2 inches
Valve: Brass valve rated for pressures up to 500 PSI
Construction: Stainless-steel tool body, tubing, jet, nuts and bolts
Manufactured In: USA
Contained Internal Spray for Tight-Area Extraction
The solution jet is located inside the vacuum chamber rather than outside the tool. This configuration directs cleaning solution into the pickup area, where the vacuum can immediately recover the loosened soil and moisture. It helps reduce uncontrolled overspray around seats, consoles, baseboards and nearby dry surfaces.
The narrow, extended stainless-steel body reaches into confined areas where a standard upholstery tool or carpet wand is too wide. A thumb-operated vacuum-release slide lets the technician reduce suction when the tool seals too tightly against fabric or carpet, while the vinyl-covered grip helps isolate the operator's hand from the metal tube.
Common Applications

- Automotive carpet beside seats and center consoles
- Spaces between removable upholstery cushions
- Seat seams, pockets and narrow fabric channels
- Carpet edges and perimeter areas along baseboards
- Recreational vehicles, boats and transportation interiors
- Confined areas requiring both solution application and vacuum recovery

Product Specifications

Brand
PMF / Production Metal Forming

Steambrite Supply

PMF CV25SB Internal Spray Crevice Tool, 18in Long, 500 PSI Brass Valve, Hand Wand, AW49 Stainless Steel Body

Model / Part Number
CV25SB

Alternate Number
AW49

Product Type
Professional internal-spray extraction crevice tool

Approximate Overall Length
18 inches

Vacuum-Tube Diameter
1-1/2 inches

Spray Configuration
Internal; jet positioned inside the vacuum chamber

Jet / Solution Tube
Stainless-steel jet welded to stainless-steel tubing

Valve Type
Trigger-operated brass valve

Maximum Valve Rating
500 PSI

Vacuum Control
Thumb-slide vacuum release

Grip
Protective vinyl covering

Tool Construction

Steambrite Supply

PMF CV25SB Internal Spray Crevice Tool, 18in Long, 500 PSI Brass Valve, Hand Wand, AW49 Stainless Steel Body

Stainless steel, including nuts and bolts

Country of Manufacture
USA

Important Pressure Information
The 500-PSI specification is the maximum rating of the CV25SB brass-valve configuration; it is not a recommendation to clean every material at 500 PSI. Begin at a low pressure and increase only as needed for the fabric, carpet and soil conditions. Test an inconspicuous area first and follow the material manufacturer's cleaning instructions.
For applications requiring a valve rated above 500 PSI, select PMF's separate CV25S-ST configuration with a stainless-steel valve rated up to 1,000 PSI. Do not operate the CV25SB above its 500-PSI valve rating.
What Is Included

- One PMF CV25SB internal-spray crevice tool
- Factory-installed brass trigger valve
- Internal stainless-steel solution tube and jet
- High-pressure solution whip

Not Included: A male quick-disconnect plug is not included with the CV25SB and must be purchased separately if needed. Quick-disconnect styles can vary among extractor systems, so select a compatible fitting for your solution hose. Vacuum hose, solution hose, extractor and cleaning chemicals are also not included.
CV25SB Versus External-Spray Crevice Tools
The CV25SB places its spray jet inside the vacuum chamber for more contained solution delivery. An external-spray model leaves the jet exposed, which offers a direct view of the spray but can create more overspray in confined interiors. Choose the configuration appropriate for the access area and material being cleaned.
Fitment and Operating Check

- Confirm that the extractor and solution hose use compatible 1-1/2-inch vacuum and solution connections.
- Inspect the valve, whip hose, fittings and internal jet before each use.
- Connect the vacuum hose and solution line only after relieving stored pressure.
- Test spray direction, vacuum recovery and material colorfastness in an inconspicuous location.
- Flush chemical residue from the solution path after use and allow the tool to dry before storage.
- Internal spray works best between 200- 450 psi water pressure.

Fitment Notice: Similar PMF crevice tools are offered with different spray

PMF CV25SB Internal Spray Crevice Tool, 18in Long, 500 PSI Brass Valve, Hand Wand, AW49 Stainless Steel Body

arrangements and valve ratings. Match PMF part number CV25SB, the 500-PSI brass valve and the required connections before ordering.
Video

Optional

Horse Hair Brush with Comfort Grip Handle For Upholstery Cleaning

---

Options available for PMF CV25SB Internal Spray Crevice Tool, 18in Long, 500 PSI Brass Valve, Hand Wand, AW49 Stainless Steel Body :

Add-ons

+ None, Install H58 Filter Next to QD.

Accessories

+ No Accessories, [BG] PMF Booted Glide For Crevice Toos.

Quick Disconnect Coupler Needed

Female Stainless Pressure Washer Coupler Style Socket 3/8, Carpet Cleaning Stainless Steel 1/4" Male Quick Disconnect QD 104QDSS NA010, Female Brass Carpet Cleaners Style 1/4, Kaivac Male Quick Connect 1/4in MALE FLO-THRU Plug X BRASS 1/4" FPT [BR335], - None, Male 22mm Brass Plug Screw On, Carpet Cleaning QD35 1/8 inch Male Brass Quick Disconnect Plug Coupler 580-105 PAF03 PC10, Male Stainless Pressure Washer Style Plug 3/8, Carpet Cleaning Stainless Steel 1/4" Female Quick Disconnect QD 104QDSS-S, .Male Brass Carpet Cleaners Style (Default) 1/4, Female 22mm Brass Socket Screw On.

Valve Upgrade

Stainless Steel 1000psi, 500psi Brass.

Availability: This product was added to our catalog on Thursday 26 June, 2008