

>



Model Number: 2088-443-144

Shurflo 2088-443-144, 12VoltsDC 30psi 3.5Gpm, Standard Demand Pump, Intermittent duty

Manufacturer: Shurflo

2088 Series Diaphragm Pump  
Standard Demand Pump  
(12VDC)

Model

2088-443-144

Description

3.5 GPM open flow, Santoprene® valves, Santoprene® diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports (1/2" - 14 National American Straight Pipe Thread, requires SHURflo swivel type fittings), Poly Housing

>

Voltage

12 VDC

PSI

10

20

30

40

BAR

0.7

1.4

2.1

2.8

GPM

2.83

2.56



2.31

2.02

L/min

10.7

9.7

8.7

7.6

Amps

5.8

7.0

8.0

9.1

Steambrite Supply

>

\* Additional technical information is available below in pdf format.  
Adobe Acrobat Reader is required to view these documents.

Product Data Sheet | Troubleshooting | Replacement Parts

Data Sheet

International shipping?

You can ship either one or two of these pumps for the same \$80 by the US Post Master to almost every country in the world.

Optional:

Shurflo 255-315 Swivel Nut Strainer filter X 1/2" Barbed Plastic

---

*Availability: This product was added to our catalog on Thursday 07 August, 2008*