Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark



Model Number: PA-CH680-3087

Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark

Manufacturer: Kohler

BACK ORDER 30 DAYS

Kohler 23Hp Command V-Twin Engine Electric Start CH22.5S CH680-3087 Exmark

Air Intake Group 10-24-295 CH18-750
Blower Housing Group 6-24-4 CH18-750
Crankcase Group 2-24-278 CH18-750
Crankshaft Group 1-24-28 CH18-750
Cylinder Head/ Breather Group 4-24-525 CH18-750
Decals 12-24-188
Engine Controls Group 9-24-140 CH18-750
Exhaust Group 11-24-6 CH18-750
Fuel System Group 8-24-505
Ignition/Electrical 5-24-372 CH18-750
Oil Pan/Lubrication 3-24-197 CH18-750
Starting Group 7-24-5 CH18-750

Supersedes CH22-66529 & CH23S-76513
1 inch x 2-3/4 inch Crankshaft
12 Volt Electric Starter
15 Amp Alternator
Includes Fuel Pump
Application: Exmark Lazer - PRO SERIES. Fits Exmark LZ22KCS523 and Toro Z253
1" x 2-25/32, Tapped 7/16-20, With full 1/4" keyway Crankshaft
Air Cleaner: Dual Element
Muffler: Muffler: 2406817S
Uses front stub shaft 24 755 08-S aka 2475508S

Steambrite Supply

Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark

Durable, Long Life Design.
Hydraulic valve lifters are oil pressurized, ensuring that push rods stay in constant contact with the rocker arms. Requiring no adjustment, the valve train is virtually maintenance-free. In addition, full-pressure lubrication delivers continuous lube to critical engine components, even at 25-degree angle of operation and optional oil cooler regulates the oil temperature extending oil-change intervals. Large capacity, in-line fuel filter provides extra protection against dirt particles that can clog fuel lines.
High Power Performance.
Overhead valve technology provides greater volumetric efficiency and a higher compression ratio. This produces more power, improved fuel economy and cooling and reduces oil consumption. In addition, there is virtually no carbon buildup, reducing overall maintenance costs. The variable speed, mechanical governor promises smooth performance, regardless of application or fluctuating demands for power.

Reliable Starting.
Kohler Command PRO® electronic ignition system generates a stronger spark at low cranking speed and Automatic Compression Release (ACR) allows compression to escape during cranking to reduce pull force.

User-Friendly Maintenance.

High Power Performance.

Reliability and Long Life Design.

Quiet, Smooth Operation.

Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark

Easy Dependable Starts.

Full pressure lubrication. 20 Amp alternator. Pulse fuel pump. Satellite exhaust valves with seat inserts and rotators. 1 7/16" X 4 29/64" shaft is drilled and tapped 5/8"-18: has 3/8" keyway. Two limited warranty.

Overhead Valve Design OHV
• Hydraulic Valve Lifters
• Cast-Iron Cylinder Liners
• Electronic Ignition
• Large Capacity Dual Element Air Cleaner
• High Efficiency Grass Screen and Fan
• Closed Breather System
• Stellite® Exhaust Valves
• Full Pressure Lubrication
• Large Capacity In-Line Fuel Filter
• Easy Access Valve Cover Oil Fill-Yellow
• Oil Level Dipstick-Yellow
• Large Capacity Oil Filter, Dual Oil Drain
• Oil Sentry™ (Switch Installed and Wired but Unconnected)
• Variable Speed Governor
• Fuel Shutdown Solenoid, Smart-Choke™ Carburetor
• Mechanical Fuel Pump
• High Performance Spark Plugs
• 12 Volt Solenoid Shift Starter
• 20 Amp Alternator, Regulated
• Crankshaft-1.437" (36 mm) Diameter x 4.453" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF
• PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep
Color Black with Cast Aluminum
7" (178mm) Diameter Pilot
Exact Specifications Subject To Change Without Notice
HP rating on sticker also marketed as 22.5 Hp.

Standard Features Plus:
• 3/16" Evaporative Emissions Connection

Steambrite Supply

Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark

Engine Type:

4-cycle, gasoline, OHV, cast iron cylinder liners, aluminum block

Model

Command PRO CH680

Max Power @3600 RPM hp (kW) 1
22.5 (16.8)

Displacement cu in (cc)
41.1 (674)

Bore in (mm)
3.2 (80)

Stroke in (mm)
2.6 (67)

Max Torque lbs. ft (Nm)1
36.8 (49.9)

Steambrite Supply

Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark

Compression Ratio
8.5:1

Dry Weight lbs (kg)
90 (41)

Oil Capacity U.S. quarts (L)
2 (1.9)

Lubrication
Full pressure w/full-flow filter

Dimensions L x W x H in
14 x 17.7 x 19.0

Backpressure Limit 2
50

J1995 Power hp (kW) 3
21.5 (16)

* Length is grass screen to PTO mounting face. Width is spark plug to spark plug. Height is top of air cleaner to mounting feet.
1 Max Power (hp) and Max Torque (lbs ft) specifications for Kohler general purpose engines are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed according to SAE J1995 without the air cleaner and muffler. Actual engine power and torque are lower and affected by accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed, ambient operating conditions (temperature, humidity and altitude) and other factors. This J1940 / J1995 rating provides consistent measurement to customers who may want to control the intake and exhaust features of the engine. For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.

2 Inches of H20 @ 3600 RPM WOT

Steambrite Supply

Parts & Accessories > Engines > Kohler Command Pro 22.5hp PA-CH680 > Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark

Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark

Service Manual

Sales Brochure

Quick Reference Parts Guide

Kohler Warranty

Owners Manual

106 lbs

Kohler 22.5-23Hp Command V-Twin Engine Electric Start CH22.5S CH680-3087 Exmark

---

Options available for Kohler PA-CH680-3087 23Hp Command Pro Horizontal Engine CH23S Exmark :

Shipping Surcharges

Home Delivery Needs Liftgate Curb Service Because No Forklift On Site (Required) No Appointment Provided, None Commercial Address Forklift / Loading Dock On Site No Appointment Provided, +Home Delivery Needs Liftgate Curb Service Because No Forklift On Site With Appointment Delivery Time, Commercial Address But Needs Liftgate Service Because No Forklift or Dock on Site No Appointment Provided.

Availability: This product was added to our catalog on Monday 02 June, 2014

Steambrite Supply