

>



Model Number: PA-CH742-3100

Kohler PA-CH742-3100 Command Pro Basic Supersedes PA-CH740-0001 GTIN N/A

Manufacturer: Kohler

Kohler Command Pro 25 hp CH740-0001 Marketing Basic

This model has been superseded by PA-CH742-3100

Placing an order on this page is placing an order for PA-CH742-3100

Specifications

Ignition Type: Electronic

HP: 25

Application: Golf Course Implements, Aerial Lift, Auger, Boaring Eq., Cable Layer, Compressor, Concrete Saw, Curber, Fire Pump, Hydraulic Power Pack, Material Handling Power Buggy, Mixer, Mud Pump, Roller, Rammer, Shredder, Sprayer, Yard Tractor, Light Tower, Welder

PTO Shaft Key (In.): 0.375

Gear Box: Internal

Overall W Facing PTO (In.): 18.5

Engine RPM: 3600

Start: Electric

Gross Torque: 36.5

4 Cycle Engine: yes

Shaft Dia. (In.): 1-7/16

Item: Gasoline Engine

Cylinders: 2

Overall Width (In.): 17.38

Includes: High Efficiency Grass Screen and Fan, Full Pressure Lubrication, 20A Alternator, Regulated Key Switch, Throttle and Choke Controls

RPM: 3600

Overall H Facing PTO (In.): 17.38

Maintenance Frequency: 100 Hours Air Filter and Change Oil, 200 Hours Air

>

and Oil Filter

PTO Shaft Dia. (In.): 1.437

Recommended Use: Golf Course Implements, Aerial Lift, Auger, Goaring Equipment, Cable Layer, Compressor, Concrete Saw, Curber, Fire Pump, Hydraulic Power Pack, Material Handling Power Buggy, Mixer, Mud Pump, Roller, Signal Board, Sprayer

Overall Depth (In.): 18.5

Shaft Key (In.): 0.375

Design: Overhead Valve, Hydraulic Valve Lifters, High Performance Spark Plugs

Shaft Height (In.): 6.125

Features: High Efficiency Grass Screen and Fan, Full Pressure Lubrication, Regulated Key Switch, Throttle and Choke Controls  
Muffler: No

PTO Shaft Height (In.): 6.125

Agency Compliance: EPA

Air Cleaner Type: Heavy Duty Cnister System

Function: Golf Course Implements, Aerial Lift, Auger, Goaring Equipment, Cable Layer, Compressor, Concrete Saw, Curber, Fire Pump, Hydraulic Power Pack, Material Handling Power Buggy, Mixer, Mud Pump, Roller, Signal Board, Sprayer

Starter Type: Electric

Overall Depth Facing PTO (In.): 25

Bearings: Sleeve

Shaft Configuration: Drilled and Tapped 1.5 Deep, 5/8-18 UNF

PTO Shaft Length (In.): 4.46

Shaft Orientation: Horizontal

Low Oil Shut Down: Pre Start Only

Air Filter: Pleated Paper

>

Rotation: CCW-SE  
Overall Height (In.): 25

Shaft Length (In.): 4-29/64  
Country of Origin (subject to change): United States

Links  
[Service Manual](#)  
[Owners Manual](#)  
[Sales Brochure](#)  
[Kohler Warranty](#)  
[Quick Reference to Parts Guide](#)

---

*Availability: This product was added to our catalog on Wednesday 04 June, 2014*