

>



Model Number: 56 URAI DSL

Dresser Roots 56 URAI DSL Blower T30360020

Manufacturer: Howden Roots Blowers

Dresser Roots 56 URAI DSL Blower

6- 8 Week Build time line.

See photo to the right showing the 8 different ways to order this vacuum blower.

In the check out screen comment box, please include how you want this item built.

Options:

- A) Top Drive shaft / Clock Wise Rotation /right side discharge
- B) Top Drive shaft / CCW Rotation / Left side discharge
- C) Bottom Drive Shaft / CW Rotation / Left side discharge
- D) Bottom Drive Shaft / CCW Rotation / Right side Discharge
- E) Right handed Crank / CW Rotation / Bottom Discharge
- F) Right handed Crank / CCW Rotation / Top Discharge
- G) Left hand Drive / CW Rotation / Top Discharge
- H) Left hand Drive shaft / CCW rotation / Bottom discharge

QUESTION: If I purchase a cross over blower and it does not fit, will Steambrite or the factory waive the 25% restocking fee?

ANSWER: No. To purchase a similar performing blower is your decision as it states on every webpage, "All other warranties, express or implied, including but not limited to, the implied warranties of merchantability and fitness for a particular purpose, are hereby disclaimed"

THANKS FOR YOUR UNDERSTANDING.

Max Flow: 580 CFM

Max Pressure: 10 psi

Max Vacuum: 15" Hg

Max Speed: 2850 RPM

MAX FLOW:

580

MAX PRESSURE:

10 psi

MAX VACUUM:

>

15" Hg

MAX SPEED:

2850 RPM

MANUFACTURER:

Howden Roots

Product Description

Roots Model 56 URAI DSL

Flow Range: to 580 CFM

Max Δ Pressure: 10 psi

Max Δ Vacuum: 15″ Hg

Max RPM: 2850

Min RPM: 763

Max ΔT: 225″F

Connection: 4″ FPT

Shaft Dia.: 1.125″

Drive End Lubrication: Oil

Gear End Lubrication: Oil

Required Oil Gear End Horizontal Unit: 27.6 ounces

Required Oil Drive End Horizontal Unit: 14.8 ounces

Required Oil Gear End Vertical Unit: 16 ounces

Required Oil Drive End Vertical Unit: 7.5 ounces

Unit Weight: 175 pounds (79.5 kg)

Shipping Box Size (LxWxH): 24.5″x19.5″x20″

(622mmx495mmx508mm)

Shipping Container: Cardboard Box with formed foam

NOTE: Default shaft orientation is LEFT HAND -- Unit can be mounted with top hand crank, bottom hand crank, left hand crank or right hand crank. Can be spun in either direction. Simply change the mounting feet and relocate the breather port to the top.

Common carrier is recommended

Compare Dresser Roots VS Tuthill VS Gardner Denver / Sutorbilt Blower - Crossover Charts

Installed on White Magic Pro-1200 Truckmounts

>

Compare to current or past OEM associations:
White Magic A1015
Gardner Denver 5MR-LHC GAEMCSA0084
Tuthill 5006-21L2

For faster shipping or even possible in stock option, please consider a cross over blower (similar size) in a different brand

Gardner Denver Sutorbilt Legend PD 5ML 5MP 5MS [5MR-LHC] Truck
Mount Vacuum Blower Pump GAEMCSA0084

Tuthill 5006-21L2 Competitor Blower 5006-21LC 5006-A6L2CV1-A
5006-21X2-7901

Important Option

Oil level must be topped off on new blowers
Oil level must be changed after 50 hour break in period.

>

Oil level must be changed every 200 hours after break in period.
Gardner Denver 28G46 Brand Blower Oil Aeon PD-XD Full Synthetic Formula
Extra Heavy Duty for High Heat Applications 28G47-QT
Add to your shopping cart now!

"These blower and vacuum pumps are for sale and use in the carpet cleaning industry only as some OEM configuration have special coatings, or even mounting holes drilled in them. Example These blowers won't work for Easy Air Package equipment as it is not drilled and tapped to mount a fan. All other applications for use outside the carpet cleaning industry cannot be guaranteed."

Howden Terms

http://store.tomlinequipment.com/index.php?main_page=index&cPath=8_1_3

-->

Availability: This product was added to our catalog on Monday 19 January, 2009