Parts & Accessories > Pumps (Water Pumps) > Shurflo Water Pumps > Shurflo 2088-594-154, Pump 45psi 3.3gpm 115volts, Santoprene Valves

Shurflo 2088-594-154, Pump 45psi 3.3gpm 115volts, Santoprene Valves



Model Number: 2088-594-154

Shurflo 2088-594-154, Pump 45psi 3.3gpm 115volts, Santoprene Valves

Manufacturer: Shurflo

Shurflo 2088-594-154 Pump 45psi 3.3gpm 115volts Santoprene Valves
Description
This SHURflo Industrial on-demand positive displacement, 3 chamber diaphragm pump has a permanent magnet, thermally protected 115V AC motor that delivers reliable performance in high-flow, moderate pressure applications. Self-priming up to 9ft. vertical. Max. 50 PSI; max. 30 PSI inlet pressure.

Shurflo water pump is designed to be used in various water delivery and transfer applications. It delivers efficient performance in moderate and high flow water pressure. With a flow rate of 3.3 GPM, the water pump can lift water up to 9 ft.

This fresh water pump maintains a smooth and uninterrupted supply of water. It features a poly housing that stands strong against the test of time, ensuring a longer serviceable life. Equipped with Santoprene valves and diaphragm, the water pump ensures the water remains safe for consumption.
Pentair 2088-594-154 water pump prevents the backflow of liquid through the pump. It can run dry without leading to damages or costly repairs. The delivery pump is flexible for installation, it can be mounted in small spaces in a vertical or horizontal position. Shurflo delivery pump requires a 115V electric connection for operation.

This pump does not include fittings for connecting to tubing.
Features

- Thermally protected 115V AC motor
- Auto shut-off pressure switch reacts to outlet pressure and interrupts power when it reaches the preset shutoff pressure level
- Positive displacement 3-chamber diaphragm
- Corrosion-resistant Santoprene® valves and diaphragm
- Robust poly housing
- Poly pump head
- Can run dry without damage
- Handles liquids up to 170°F
- NSF and CSA certified, UL listed

Shurflo 2088-594-154, Pump 45psi 3.3gpm 115volts, Santoprene Valves

Specification

Model	2088-594-154
Voltage	115 VAC
Diaphragm Materials	Santoprene
Port Size	1/2 in
PSI	45

Steambrite Supply

Shurflo 2088-594-154, Pump 45psi 3.3gpm 115volts, Santoprene Valves

GPM

3.3

Temp

170°F

Amps

0.90

Documation
Manual
Parts List
Product Data Sheet

Optional

Shurflo 255-315 Swivel Nut Strainer filter X 1/2" Barbed Plastic

Availability: This product was added to our catalog on Friday 13 February, 2009

Steambrite Supply