Parts & Accessories > Pumps (Water Pumps) > Annovi Reverberi Pumps > AR Industrial Triplex Plunger Pumps > XM/SXM Series > AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0



Model Number: XMA2G22E-F33 8.702-538.0

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Manufacturer: Annovi Reverberi Pumps

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0
Description
The Annovi Reverberi XMA2G22E-F33, E version 5/8" hollow shaft triplex pump is ready for direct or pulley driving. This pump is manufactured with a brass pump head suitable for a wide range of conditions. The XMA2G22E-F33 can produce up to 2200 Max PSI, 2.11 Max GPM, and is designed to operate at 1750 RPM. Constructed with frictionless aluminum connecting rods and ceramic pistons, the XMA2G22E-F33 weighs in at 15 lbs and boasts a sleek compact design.

Features

- Manifold:
- - Forged Brass: Strength and no porosity equals long life. Higher hydrostatic pressures, safety and performance.
- - Inlet and Discharge Ports: Heavy bosses for added strength.
- - Offset Discharge Ports: High efficiency, smooth flow.
- - Bolts: Eight bolts, 6mm, grade 12.9.
- Valves:
- - Ultra Form Cages: Durability, strength and long life.
- - Poppets, Seat and Spring: 303 and 400 series stainless steel.
- - Valve Caps: Machined brass – greater strength.
- Packing and Plungers:
- - High Pressure Packing: “V” style (D-1) Buna-N (cotton duct weave base) strong and tightens under load.
- - Low Pressure Seals: “U” cup double lip Buna-N, good positive seal.
- - Support Guides: Machined brass, two-piece construction to assure proper plunger alignment and to maximize packing and seal life.
- - Plungers: Are a special aluminum oxide blend, solid ceramic for long life, strong durability and more resilient.
- Bearings: Oversized for maximum life and load disbursement, needle bearing on the drive side and ball on the non-drive side. Each bearing is held in position on the crankshaft and crankcase by snap rings. This assures positive alignment and centering of the connecting rods and crankshaft in relation to the crankcase, it also eliminates the crankshaft from floating.
- Crankcase: Precision die-cast, large cooling fins and anodized (for maximum heat dissipation).
- Rear Cover: precision die-cast, O-ring sealed and bayonet style sight glass for positive sealing and locking (no threads to loosen).
- Plunger Rods: Stainless steel construction for strength (no plating to scrape off).

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

O-ring plunger sealing system.
• Rod Pins: Precision ground and hardened steel, oversized for load disbursement.
• Connecting Rods: One-piece special alloy aluminum based, oversized for maximum strength, load disbursement, and life. Heavy pin area construction, for added load strength.
• Crankshaft: Forged, precision ground and hardened for extremely long life and durability.
• Oil Seals and O-rings: All are constructed of Buna-N rubber. The O-rings have stainless steel garder springs to assure constant tension on the sealing surface.
• Oil Capacity: 14.5 oz., refer to parts breakdown.
• Dyno Proven: All pumps are dyno tested to assure the theoretical design meets the actual design.
• Valve Design: Each pump series has a valve design that optimizes its highest efficiency.
• Hot Water: High temperature kits are available to 180º F. Refer to breakdown
• Wet End Repair: Very simple no special tools are required.
• Mounting Bolt Pattern: Same on the top and bottom of the crankcase for simple drive side change.
• Design: Using advanced fluid handling design programs. Overall pump efficiency is increased.

Specifications

Normal
0

false
false
false

EN-US
X-NONE
X-NONE

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Steambrite Supply

DefSemiHidden="false" DefQFormat="false" DefPriority="99"
LatentStyleCount="376">

UnhideWhenUsed="true" QFormat="true" Name="heading 2" />

UnhideWhenUsed="true" QFormat="true" Name="heading 3" />

UnhideWhenUsed="true" QFormat="true" Name="heading 4" />

UnhideWhenUsed="true" QFormat="true" Name="heading 5" />

UnhideWhenUsed="true" QFormat="true" Name="heading 6" />

UnhideWhenUsed="true" QFormat="true" Name="heading 7" />

UnhideWhenUsed="true" QFormat="true" Name="heading 8" />

UnhideWhenUsed="true" QFormat="true" Name="heading 9" />

Name="index 1" />

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="index 2" />

Name="index 3" />

Name="index 4" />

Name="index 5" />

Name="index 6" />

Name="index 7" />

Name="index 8" />

Name="index 9" />

UnhideWhenUsed="true" Name="toc 1" />

UnhideWhenUsed="true" Name="toc 2" />

UnhideWhenUsed="true" Name="toc 3" />

UnhideWhenUsed="true" Name="toc 4" />

UnhideWhenUsed="true" Name="toc 5" />

UnhideWhenUsed="true" Name="toc 6" />

UnhideWhenUsed="true" Name="toc 7" />

UnhideWhenUsed="true" Name="toc 8" />

UnhideWhenUsed="true" Name="toc 9" />

Name="Normal Indent" />

Name="footnote text" />

Name="annotation text" />

Name="header" />

Name="footer" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="index heading" />

UnhideWhenUsed="true" QFormat="true" Name="caption" />

Name="table of figures" />

Name="envelope address" />

Name="envelope return" />

Name="footnote reference" />

Name="annotation reference" />

Name="line number" />

Name="page number" />

Name="endnote reference" />

Name="endnote text" />

Name="table of authorities" />

Name="macro" />

Name="toa heading" />

Name="List" />

Name="List Bullet" />

Name="List Number" />

Name="List 2" />

Name="List 3" />

Name="List 4" />

Name="List 5" />

Name="List Bullet 2" />

Name="List Bullet 3" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="List Bullet 4" />

Name="List Bullet 5" />

Name="List Number 2" />

Name="List Number 3" />

Name="List Number 4" />

Name="List Number 5" />

Name="Closing" />

Name="Signature" />

UnhideWhenUsed="true" Name="Default Paragraph Font" />

Name="Body Text" />

Name="Body Text Indent" />

Name="List Continue" />

Name="List Continue 2" />

Name="List Continue 3" />

Name="List Continue 4" />

Name="List Continue 5" />

Name="Message Header" />

Name="Salutation" />

Name="Date" />

Name="Body Text First Indent" />

Name="Body Text First Indent 2" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="Note Heading" />

Name="Body Text 2" />

Name="Body Text 3" />

Name="Body Text Indent 2" />

Name="Body Text Indent 3" />

Name="Block Text" />

Name="Hyperlink" />

Name="FollowedHyperlink" />

Name="Document Map" />

Name="Plain Text" />

Name="E-mail Signature" />

Name="HTML Top of Form" />

Name="HTML Bottom of Form" />

Name="Normal (Web)" />

Name="HTML Acronym" />

Name="HTML Address" />

Name="HTML Cite" />

Name="HTML Code" />

Name="HTML Definition" />

Name="HTML Keyboard" />

Name="HTML Preformatted" />

Name="HTML Sample" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="HTML Typewriter" />

Name="HTML Variable" />

Name="Normal Table" />

Name="annotation subject" />

Name="No List" />

Name="Outline List 1" />

Name="Outline List 2" />

Name="Outline List 3" />

Name="Table Simple 1" />

Name="Table Simple 2" />

Name="Table Simple 3" />

Name="Table Classic 1" />

Name="Table Classic 2" />

Name="Table Classic 3" />

Name="Table Classic 4" />

Name="Table Colorful 1" />

Name="Table Colorful 2" />

Name="Table Colorful 3" />

Name="Table Columns 1" />

Name="Table Columns 2" />

Name="Table Columns 3" />

Name="Table Columns 4" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="Table Columns 5" />

Name="Table Grid 1" />

Name="Table Grid 2" />

Name="Table Grid 3" />

Name="Table Grid 4" />

Name="Table Grid 5" />

Name="Table Grid 6" />

Name="Table Grid 7" />

Name="Table Grid 8" />

Name="Table List 1" />

Name="Table List 2" />

Name="Table List 3" />

Name="Table List 4" />

Name="Table List 5" />

Name="Table List 6" />

Name="Table List 7" />

Name="Table List 8" />

Name="Table 3D effects 1" />

Name="Table 3D effects 2" />

Name="Table 3D effects 3" />

Name="Table Contemporary" />

Name="Table Elegant" />

Name="Table Professional" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="Table Subtle 1" />

Name="Table Subtle 2" />

Name="Table Web 1" />

Name="Table Web 2" />

Name="Table Web 3" />

Name="Balloon Text" />

Name="Table Theme" />

Name="List Paragraph" />

Name="Intense Quote" />

Steambrite Supply

Parts & Accessories > Pumps (Water Pumps) > Annovi Reverberi Pumps > AR Industrial Triplex Plunger Pumps > XM/SXM Series > AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Steambrite Supply

Name="Subtle Emphasis" />

Name="Intense Emphasis" />

Name="Subtle Reference" />

Name="Intense Reference" />

UnhideWhenUsed="true" Name="Bibliography" />

UnhideWhenUsed="true" QFormat="true" Name="TOC Heading" />

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Steambrite Supply

Name="Grid Table 1 Light Accent 1" />

Name="Grid Table 6 Colorful Accent 1" />

Name="Grid Table 7 Colorful Accent 1" />

Name="Grid Table 1 Light Accent 2" />

Name="Grid Table 6 Colorful Accent 2" />

Name="Grid Table 7 Colorful Accent 2" />

Name="Grid Table 1 Light Accent 3" />

Name="Grid Table 6 Colorful Accent 3" />

Name="Grid Table 7 Colorful Accent 3" />

Name="Grid Table 1 Light Accent 4" />

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="Grid Table 6 Colorful Accent 4" />

Name="Grid Table 7 Colorful Accent 4" />

Name="Grid Table 1 Light Accent 5" />

Name="Grid Table 6 Colorful Accent 5" />

Name="Grid Table 7 Colorful Accent 5" />

Name="Grid Table 1 Light Accent 6" />

Name="Grid Table 6 Colorful Accent 6" />

Name="Grid Table 7 Colorful Accent 6" />

Name="List Table 1 Light Accent 1" />

Name="List Table 6 Colorful Accent 1" />

Name="List Table 7 Colorful Accent 1" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="List Table 1 Light Accent 2" />

Name="List Table 6 Colorful Accent 2" />

Name="List Table 7 Colorful Accent 2" />

Name="List Table 1 Light Accent 3" />

Name="List Table 6 Colorful Accent 3" />

Name="List Table 7 Colorful Accent 3" />

Name="List Table 1 Light Accent 4" />

Name="List Table 6 Colorful Accent 4" />

Name="List Table 7 Colorful Accent 4" />

Name="List Table 1 Light Accent 5" />

Name="List Table 6 Colorful Accent 5" />

Name="List Table 7 Colorful Accent 5" />

Name="List Table 1 Light Accent 6" />

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Name="List Table 6 Colorful Accent 6" />

Name="List Table 7 Colorful Accent 6" />

Name="Mention" />

Name="Smart Hyperlink" />

Name="Hashtag" />

Name="Unresolved Mention" />

Name="Smart Link" />

/* Style Definitions */
table.MsoNormalTable
{mso-style-name:"Table Normal";
mso-tstyle-rowband-size:0;
mso-tstyle-colband-size:0;
mso-style-noshow:yes;
mso-style-priority:99;
mso-style-parent:"";
mso-padding-alt:0in 5.4pt 0in 5.4pt;
mso-para-margin-top:0in;
mso-para-margin-right:0in;
mso-para-margin-bottom:8.0pt;
mso-para-margin-left:0in;
line-height:107%;
mso-pagination:widow-orphan;
font-size:11.0pt;
font-family:"Calibri",sans-serif;
mso-ascii-font-family:Calibri;
mso-ascii-theme-font:minor-latin;
mso-hansi-font-family:Calibri;
mso-hansi-theme-font:minor-latin;
mso-bidi-font-family:"Times New Roman";
mso-bidi-theme-font:minor-bidi;
mso-font-kerning:1.0pt;
mso-ligatures:standardcontextual;}
table.MsoTableGrid
{mso-style-name:"Table Grid";
mso-tstyle-rowband-size:0;

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

mso-tstyle-colband-size:0;
mso-style-priority:39;
mso-style-unhide:no;
border:solid windowtext 1.0pt;
mso-border-alt:solid windowtext .5pt;
mso-padding-alt:0in 5.4pt 0in 5.4pt;
mso-border-insideh:.5pt solid windowtext;
mso-border-insidev:.5pt solid windowtext;
mso-para-margin:0in;
mso-pagination:widow-orphan;
font-size:11.0pt;
font-family:"Calibri",sans-serif;
mso-ascii-font-family:Calibri;
mso-ascii-theme-font:minor-latin;
mso-hansi-font-family:Calibri;
mso-hansi-theme-font:minor-latin;
mso-bidi-font-family:"Times New Roman";
mso-bidi-theme-font:minor-bidi;
mso-font-kerning:1.0pt;
mso-ligatures:standardcontextual;}

Weight

15 lbs.

Pump Orientation

Horizontal

Pump Head Material

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Brass

Connecting Rods

Aluminum

Max GPM

2.11

Max L/Min

8

Max PSI

2200

Max Bar

150

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Power EBHP

3

Bore Dia. (mm)

15

Stroke (mm)

9.4

CSID Stamp

7

Inlet (in)

1/2” F

Outlet (in)

3/8” F

Steambrite Supply

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Max Temp

140° F

Oil Capacity (oz.)

14.5

RPM

1750

Shaft Size

5/8”

Shaft Version

Electric

Shaft Type

Steambrite Supply

Parts & Accessories > Pumps (Water Pumps) > Annovi Reverberi Pumps > AR Industrial Triplex Plunger Pumps > XM/SXM Series > AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

AR Pump XMA2G22E-F33 Pump: 2/2200 1750RPM Left Handed, 8.702-538.0

Hollow

Flange

F33

Market

Commercial

Pump Type

Tri-Plex Plunger

Availability: This product was added to our catalog on Friday 06 June, 2014

Steambrite Supply