

>



Model Number: TX1508G8

General Pump TX1508G8, 3400 3 Gpm 3400rpm, 8.702-738.0

Manufacturer: General Pump

General Pump, 300/3400 3.0 Gpm Tx1508g8 - 8.702-738.0

Fits 1" shaft engines

Direct bolt on design

This General Pump TX Series 63 Pressure Washer Pump boasts a Triplex Plunger Pump and 1" Hollow Shaft that is flanged for direct coupling to gasoline engines. Large, lightweight connecting rods, new long-life low- and high-pressure seals, oversized roller bearings and dual sight glasses highlight the quality and durability of this Pump Series. Their forged brass manifolds feature an exclusive lifetime warranty.

Features include:

- Oversized roller bearings
- Large, lightweight connecting rods
- New, long life low- and high-pressure seals
- Dual sight glasses
- Forged brass manifold with exclusive, lifetime warranty

Specifications:

- Horsepower: 9.2 GHP
- Maximum Volume: 3.0 GPM
- Maximum Discharge Pressure: 3000 PSI
- Maximum Pump Speed: 3400 RPM
- Maximum Inlet Pressure: 125 PSI
- Plunger Bore: .591 in. / 15 mm
- Plunger Stroke: .315 in. / 8.0 mm
- Crankcase Oil Capacity: 14 oz.
- Maximum Fluid Temperature: 165 F
- Inlet Port Thread: 1/2" - 14 BSP-F
- Discharge Port Thread: 3/8" - 19 BSP-F
- Shaft Diameter: 1.0 in. / 25.4 mm
- Weight: 18.0 lbs.
- Dimensions: 8.4" x 8.3" x 4.8"

sales tax collected in CA and TX

General pump Maintenance Guide

>

Availability: This product was added to our catalog on Thursday 26 June, 2014

Steambrite Supply