Mosmatic 38.358 DXFI 90-Degree Flange-Mount Swivel, 1/4in NPTF x 3/8in NPTM, 2000 RPM



Model Number: 38.358

Mosmatic 38.358 DXFI 90-Degree Flange-Mount Swivel, 1/4in NPTF x 3/8in NPTM, 2000 RPM

Manufacturer: Mosmatic

RECOMMENDED PRODUCT NAME / H1:
Mosmatic 38.358 DXFI 90-Degree Flange-Mount Swivel, 1/4in NPTF x 3/8in NPTM, 2000 RPM

RECOMMENDED META TITLE:
Mosmatic 38.358 DXFI 90Â° Flanged Swivel | Steam-Brite

RECOMMENDED META DESCRIPTION:
Shop the Mosmatic 38.358 DXFI 90-degree flange-mount rotary union with 1/4-inch NPT female inlet, 3/8-inch NPT male outlet, ceramic seal and 2,000 RPM rating.

IMPORTANT EDITOR NOTE â€" REMOVE AFTER CONFIRMATION:
The former Steam-Brite listing states nickel-plated, 4,000 PSI, 200Â°F and 4â€“10 GPM.
Current Mosmatic professional listings for part 38.358 state stainless steel, 2,500 PSI and 250Â°F.
The customer-facing copy below follows the current 38.358 specification. Confirm the label,
packaging or current Mosmatic data sheet for the inventory being shipped before publishing.
-->

Mosmatic 38.358 DXFI 90-Degree Flange-Mount Swivel
1/4 in NPT Female Inlet × 3/8 in NPT Male Outlet | 2,000 RPM
The Mosmatic 38.358 is a compact, high-speed 90-degree rotary union engineered for self-rotating high-pressure cleaning equipment. Its flange-mount design provides a secure installation, while the stainless-steel construction, ceramic sealing system and three-bearing arrangement support smooth rotation in demanding commercial applications.
Before ordering: Match manufacturer part number 38.358, the 90-degree flange configuration and both thread sizes. The inlet is 1/4 in NPT female; the outlet is 3/8 in NPT male.
Product Highlights

- 90-degree fluid path for compact equipment layouts
- Flange mounting for a stable, secure installation
- Three-bearing design: two radial ball bearings plus one thrust ball bearing
- Ceramic sealing system for high-speed, high-pressure service
- Integrated weep holes provide a visible early indication of seal leakage
- Stainless-steel construction for strength and corrosion resistance

Steambrite Supply

Mosmatic 38.358 DXFI 90-Degree Flange-Mount Swivel, 1/4in NPTF x 3/8in NPTM, 2000 RPM

- Suitable for water in the pH 3–12 range when filtered to 10 microns

Specifications

Manufacturer
Mosmatic

Manufacturer Part Number
38.358

Series / Type
DXFI 90-degree rotary union / swivel

Mounting
Flange mount

Inlet Thread (G1)
1/4 in NPT female

Outlet Thread (G2)
3/8 in NPT male

Nominal Width
1/4 in

Maximum Pressure
2,500 PSI

Maximum Speed
2,000 RPM

Operating Temperature
40°F to 250°F

Steambrite Supply

Mosmatic 38.358 DXFI 90-Degree Flange-Mount Swivel, 1/4in NPTF x 3/8in NPTM, 2000 RPM

Body / Internal Material
Stainless steel

Seal Type
Ceramic

Overall Diameter
2.36 in

Overall Length
1.49 in

Weight
Approximately 14.2 oz

Common Applications

- Commercial and industrial surface cleaners
- Tire and wheel washing equipment
- Parts washers and degreasing systems
- Other high-speed, self-rotating cleaning assemblies

Optional 1/8-Inch Inlet Adapter
If your equipment uses a 1/8-inch male inlet connection, add the Clean Storm 110A-BA 1/4 in MIP × 1/8 in FIP brass bushing adapter. The adapter is sold separately.
Installation and Selection Notes

- Confirm thread type, thread direction, flange dimensions and available clearance before ordering.
- Flush new hoses and plumbing before installation; contamination can damage precision seals.
- Use only a thread sealant approved for the operating pressure, temperature and cleaning solution.
- Do not clamp or wrench across precision sealing surfaces. Tighten only at the designated wrench flats.
- Never exceed the lowest pressure, temperature or speed rating of any component in the complete system.

Steambrite Supply

Mosmatic 38.358 DXFI 90-Degree Flange-Mount Swivel, 1/4in NPTF x 3/8in NPTM, 2000 RPM

Fitment responsibility: Product photographs are for reference. Orders are fulfilled by manufacturer part number 38.358. Because equipment may have been modified and similar swivels use different threads or mounts, the buyer must verify compatibility before installation.
Frequently Asked Questions
Is this a straight-through swivel?
No. Mosmatic 38.358 has a 90-degree body configuration.
Are the two connections the same size?
No. The inlet is 1/4-inch NPT female and the outlet is 3/8-inch NPT male.
Does the 1/8-inch adapter come with the swivel?
No. The optional 110A-BA brass bushing adapter is sold separately.
What does leakage from a weep hole mean?
It can indicate seal wear or failure. Stop operation, depressurize the system and inspect the swivel before returning the equipment to service.
Specifications may change without notice. Verify current manufacturer specifications and the markings on the supplied component before installation. Professional installation is recommended for high-pressure rotating equipment.

Mosmatic 38.358 Flanged Swivel 90
1/4" Fip X 3/8" Mip

Nickel Plated 2500 PSI / 4-10 GPM
200F / 2000 RPM

Optional

If you need a 1/8" inbound connection, use this fitting
1/4" Mip X 1/8" Fip Brass Bushing Adaptor 110A-BA

Availability: This product was added to our catalog on Thursday 07 August, 2014

Steambrite Supply