

>



Model Number: 20140930

Little Giant 20140930, Propane Extreme Pressure Water Heater, 2200psi Starter Bundle, 120000BTU 3HTLPSQXP

Manufacturer: Little Giant

Little Giant 20140930 Propane Extreme Pressure Water Heater 2200psi Complete Starter Package 120000 BTU 3HTLPSQXP

Includes both the items below:

Little Giant 3HTLPSQXP 120,000 BTU Propane Heater (Extreme Pressure) 2200psi Basic Starter Package 34214356

Little Giant Solution 1/4 In Id Hose 15 ft Connection Kit 20141428

Description

Perfect for even pressure washing!

These high pressure propane heaters are just what you need to get your Truck Mount or portable extractor steamin' like you like it! Just add the bottle and the propane regulator and you are in business. Ready to melt grease, tar, gum, wax, and other heavy traffic lane soil away effortlessly. 3HTLPSQXP-Extreme pressure model 2200psi Heater only (2000 psi relief valve). We Have Been Making Water Heaters Since 1904. This long tradition of efficient performance is the result of rigid control of manufacturing details and the use of the finest materials and craftsmanship available. Little Giant Water Heaters have proven to be dependable under the true test of constant daily use. They will provide long, care free service and the maximum is

>

satisfaction.

Important Note

It is extremely necessary that the Gas Pressure Regulator used to supply the heater with LP Gas has a capacity rating higher than the consumption of the heater. Too small a regulator will decrease the gas flow, the gas pressure and the amount of hot water produced. The Model #204­00 Regulator is rated at 140,000 BTU/Hr., which is sufficiently sized to supply the gas for Models #1, #2 or #3 Hotomatic® heaters. The Model LV4403C9 Regulator is rated at 575,000 BTU/Hr., which is the model we recommend for the #4 HT Hotomatic. The top water inlet is 1/4" Mip. No pressure hose or 90 degree elbow is provided. If you need a pressure hose or brass fitting to hook up your heater, please let us know.

A gas supply hose that is too small will reduce the flow rate of the LP Gas. This reduces the gas pressure at the burner and the amount of hot water produced. Use a 1/2" I.D. Hose minimum for the #1, #2 or #3 HT Hotomatic heaters. Use a 3/4" I.D. Hose for the #4 HT Hotomatic heater.

More Information about this heater.

Availability: This product was added to our catalog on Tuesday 30 September, 2014