

>



Model Number: 4230SGF-20G3

Pressure Pro Stationary HOT Washer 4230SGF-20G3 Natural Gas LP 3.8gpm 2000psi 6hp 230v 3ph 16 amp General Pump

Manufacturer: Pressure Pro

Pressure Pro Stationary HOT Washer 4230SGF-20G3 Natural Gas LP 3.8gpm 2000psi 6hp 230v 3ph 16 amp General Pump

Specify either LP (liquid propane) or NG (natural gas) when ordering.

STANDARD FEATURES

Rugged powder coated steel frame, enclosed pump/motor compartment w/ hinged lid

Super efficient schedule 80 coil

Factory Installed

Pressure Pro PCA750-10 Replacement Burner Coil for 2-3 Gpm Pressure

Washers

Stainless steel coil wrapper,

Factory Installed

Pressure Pro Stainless Coil Wrap PCA750-6 Fits Hot Shot Vertical 2-3

GPM Models

Control panel,
Float tank

Factory Installed

Pressure Pro Float Tank Assembly YFLOATTANK 1.05 gallons

>

Robert Shaw LP/NG electronic ignition 24 volt controls

Factory Installed
Robertshaw Natural Gas and Propane Valve

Commercial/Industrial grade motor

Factory Installed
Baldor Motor CEM3615T 5 Hp 3 Phase 3450 RPM 184T Frame 230 /460
Volts 6.7 Amps

Low speed V-belt driven General pump

Factory Installed
General Pump HTXS1812S Emperor Run 3.2/3.8gpm 2000psi
1450/1750rpm High Temperature

or similar

High limit over temp protection

Factory Installed
225 Degree Switch Sensor 1/2" Mip with 3 Wire Leads

Controls water temperature.

>

Vacuum switch

Factory Installed
Mecline Vacuum Switch MVVS2.5

Used to control solenoids, Relays, and Low and No water safety switches.

Safety pressure relief valve

Factory Installed
Pressure Pro 22533A-4600 5000psi 3/8Mip 6 gpm 140 degree Pressure
Relief Valve

Protects coil from over pressurization.

10' power cord (no plug)

NOTE: All units are completely factory assembled, tested in the USA, and delivered ready to operate.

STANDARD ACCESSORIES

Gun/wand assembly with insulated grip and quick connects

Factory Provided
Pressure Pro AGUD3621290C Washer Lance and Gun Combo 4060 psi
Insulated Grip 36 in w Couplers

>

50' high pressure hose w/quick connects

Factory Provided
Pressure Pro AHS330 Double Wire 50 ft Washer Hose 3/8 In 6000psi With
Couplers Installed Black

Maxi-Flo 20% chemical injector assembly w/quick connects

Factory Provided
Pressure Pro ACI005 General Pump 100775 Maxi-Flow Fixed 20%
Chemical Injector 3-5 gpm

4 color-coded QC spray nozzles

Factory Provided
Pressure Washing Nozzles, and Repair Parts

1 color-coded QC chemical soap injection nozzle

General pump Maintenance Guide

Owners Manual

Factory Warranty

Factory Brochure

Cleaning Units/Speed: 15,200
AVAILABLE OPTIONS

98-010 Panel Mount Thermostat \$100

>

General Pump 100538 Dial Thermostat 86 - 250 Degrees F. 781999

Parts plus labor to be added

98-011 Hour Meter

Factory Installed

Digital Hour Meter 120 Volts, EI 24-277 Ac/Dc 50/60 Hz - 8.749-316.0

Perfect for oil change and descaling intervals

98-101 10" Draft Diverter \$185.83

98-102 Soap Solenoid w/ Panel Mount Switch \$106.56

98-104 Time-delay Shutdown w/ Adjustable Timer \$308.00

98-105 Single Remote Station w/ Start/Stop/Burner \$201.86

98-106 Multi Remote Stations w/ Start/Stop/Burner/Soap \$344.82

98-107 Add'l Remote Stations \$265.12

98-108 Oil Fired Option \$238.69

Optional Factory installed

Beckett 240 Volt AFG Oil Burner 8.709-326.0 Pressure Pro301 VMG202

98-130 By-Pass Thermal Shutdown \$89.66

98-510 18/5 Cable, Single Remote Station \$1.16 per ft

98-512 18/7 Cable, Multi Remote Stations \$1.39 per ft

General Pump Oil

General Pump Oil Case 24 units

>

Required at 50 hours and then every 200 hours

Descaler

Shazaam: Descaler System Maintainer - 1 Gallon

Required every 100 hours of use.

All Stainless Steel Frame Models Available – consult sales rep

Availability: This product was added to our catalog on Saturday 24 January, 2015