Parts & Accessories > Brass, Plastic, Steel, Stainless Hydraulic Fittings > Brass Fitting > Threaded X Barbed > Clean Storm 32023, 3/4" MIP x 3/4" Barbed Brass Fitting, Straight, 32-023, BR023

Clean Storm 32023, 3/4" MIP x 3/4" Barbed Brass Fitting, Straight, 32-023, BR023



Model Number: 32023

Clean Storm 32023, 3/4" MIP x 3/4" Barbed Brass Fitting, Straight, 32-023, BR023

Manufacturer: Clean Storm

Clean Storm 32023, 3/4" MIP x 3/4" Barbed Brass Fitting, Straight, 32-023, BR023
Description
The Clean Storm 32023 is a heavy-duty, industrial-grade straight brass hose fitting designed for reliable, leak-free connections. Featuring a 3/4" Male Iron Pipe (MIP) thread on one end and a 3/4" Hose Barb on the other, this fitting provides a secure transfer point between rigid piping and flexible tubing or hose.

Manufactured from high-quality CA360 brass for barstock durability and CA377 brass for forged elements, it is built to withstand rigorous temperature and pressure demands across commercial, industrial, and cleaning applications. Intended for use with standard hose clamps, crimped ferrules, or similar locking mechanisms.
Features

- Durable Brass Construction: Precision-crafted from CA360 barstock and CA377 forged brass for superior strength and corrosion resistance.
- Dual Connection Type: Converts 3/4" MIP threaded connections to a secure 3/4" barbed hose fitting.
- High Thermal & Pressure Resilience: Operates efficiently across extreme temperature ranges up to 150 PSI maximum pressure.
- Versatile Application: Ideal for pressure washing equipment, water supply lines, pneumatic hose setups, and industrial fluid transfer.

Specifications

Brand
Clean Storm

Part Number
32023 / 32-023

Fitting Type
Straight Male Adapter (MIP x Hose Barb)

Connection Size
3/4" MIP Thread x 3/4" Hose Barb

Clean Storm 32023, 3/4" MIP x 3/4" Barbed Brass Fitting, Straight, 32-023, BR023

Material
CA360 Brass (Barstock) / CA377 Brass (Forged)

Max Working Pressure
150 PSI maximum

Temperature Range
-40°F to +160°F (-400°F to +1600°F rating reference)

Tolerance
± .02 on all dimensions (subject to minor batch variance)

Recommended Clamp Type
Hose Clamp, Similar Clamp, or Crimped Ferrule

Assembly Instructions

- Cut the hose cleanly and squarely to the desired length.
- Slide the hose clamp over the end of the hose.
- Lubricate the hose interior or fitting barb as needed. Push hose onto the fitting barb until it bottoms against the stop ring or hex shoulder.
- Position the hose clamp properly over the barbed area and secure tightly using a screwdriver or wrench. Maintain proper "A" dimension alignment for full clamp positioning.

Cross Reference SKUs

32023

32-023

Mid 32-023

Steambrite Supply

Parts & Accessories > Brass, Plastic, Steel, Stainless Hydraulic Fittings > Brass Fitting > Threaded X Barbed > Clean Storm 32023, 3/4" MIP x 3/4" Barbed Brass Fitting, Straight, 32-023, BR023

Clean Storm 32023, 3/4" MIP x 3/4" Barbed Brass Fitting, Straight, 32-023, BR023

BR023

Availability: This product was added to our catalog on Friday 06 February, 2015

Steambrite Supply