

>



Model Number: RSV3G34D-F40

AR Pump RSV3G340D-F40, 3500psi 3gpm, Horizontal Bolt On 1 Inch Shaft, Limited Freight

Manufacturer: Annovi Reverberi Pumps

AR Pump RSV3G340D-F40 3500psi 3gpm Horizontal Bolt On 1 Inch Shaft

3 gpm

3500 psi

10,500 cleaning units/ speed

Direct Bolt on to 1 inch horizontal engine shafts

weight 14 lbs

Bore Dia: 15mm

Stroke: 7.6mm

Built in unloader and chemical injector.

Typically installed on 9 HP engines.

3400PSI, 3.0GPM AR Direct Drive Pump with Unloader

SKU: RSV3G34D-F40

Brand: Annovi Reverberi - AR North America

This Annovi Reverberi / AR North America RSV series pumps are designed to direct drive on gasoline engines ranging from 8 – 13 h.p. Intended use for medium to heavy tasks; this triplex plunger pump features the latest in design and technology. Life tested over 500 hours at maximum performance. The RSV is a result of our combined 60 years of pumps building experience and expertise

Features

- • Features a compact and efficient intergraded unloader valve and fixed chemical injector
- • Thermal relief valve included at no cost
- • Forged brass head & amp; valve covers
- • Ceramic coated stainless steel plungers

>

- Direct drive with 4 bolt gas mounting flange

Specifications

- Max. Volume: 3.0 GPM
- Max. Discharge Pressure: 3,400 PSI
- Max. Pump Speed: 3,400 RPM
- Shaft Diameter: 1" Hollow
- Max. Horsepower Requirements: 9.3 GHP
- Max. Fluid Temp.: 140°F
- Inlet Port: 3/8" FPT
- Outlet Port: 3/8" Male NPT
- Oil capacity: 16 oz
- Weight: 14.0 lb.

Compare to Pressure Pro SLPRSV3G32

Freight charges will be applied to ALL orders. (Including local pickup in San Antonio TX)

Availability: This product was added to our catalog on Saturday 04 July, 2015