AR Pump RCV25G27D-F7, 2700psi 2.5 gpm Gas Bolt On 3/4 Shaft 3400rpm



Model Number: RCV2.5G27D-F7

AR Pump RCV25G27D-F7, 2700psi 2.5 gpm Gas Bolt On 3/4 Shaft 3400rpm

Manufacturer: Annovi Reverberi Pumps

AR Pump RCV2G2500D-F7
RCV2.5G27D-F7 series pumps are designed for a wide variety of high pressure washing applications. They are constructed with die-cast bodies and feature a brass head. Internal components include special thick solid ceramic plungers for long life and durability. Precision cast cooling fins are anodized for maximum heat dissipation. Oversized needle bearings on the drive side, and ball on the non-drive side together with the precision supports assure positive alignment and centering in relation to the crankcase. Valve cages of special designed Ultra-Form provide positive seating and extended life. Ball bearings on both sides of solid shaft drive pumps. One-piece connecting rods are special alloy aluminum, oversized for strength and load disbursement.

Features
Manifold: High strength forged brass for long term use.
Bolts: Eight 6mm.
Plungers: NEW Ceramic Plungers, thicker wall to help prevent thermal shock.
Valves: Stainless Steel, valve seat o-ring is side mounted.
Seals: High quality high pressure seals. NEW low-pressure seal with a built in scraper.
Piston Guides: Two piece piston guides.
Drive End: NEW connecting rod with 12% more load surface.
Large side cover sight glass, oversized bearing. Rear cover oil drain.
Crankshaft: Forged, precision ground.
RCV2.5G27D-F7 series pumps are designed for a wide variety of high pressure washing applications. They are constructed with die-cast bodies and feature a brass head. Internal components include special thick solid ceramic plungers for long life and durability. Precision cast cooling fins are anodized for maximum heat dissipation. Oversized needle bearings on the drive side, and ball on the non-drive side together with the precision supports assure positive alignment and centering in relation to the crankcase. Valve cages of special designed Ultra-Form provide positive seating and extended life. Ball bearings on both sides of solid shaft drive pumps. One-piece connecting rods are special alloy aluminum, oversized for strength and load disbursement.

Features

Steambrite Supply

AR Pump RCV25G27D-F7, 2700psi 2.5 gpm Gas Bolt On 3/4 Shaft 3400rpm

Manifold: High strength forged brass for long term use.
Bolts: Eight 6mm.
Plungers: NEW Ceramic Plungers, thicker wall to help prevent thermal shock.
Valves: Stainless Steel, valve seat o-ring is side mounted.
Seals: High quality high pressure seals. NEW low-pressure seal with a built in scraper.
Piston Guides: Two piece piston guides.
Drive End: NEW connecting rod with 12% more load surface.
Large side cover sight glass, oversized bearing. Rear cover oil drain.
Crankshaft: Forged, precision ground.

2700 psi
2.5 gpm
Gas Bolt On 3/4 Hollow Shaft
11 lbs
3400 rpm
Bore Dia:15mm
Stroke: 5.6 mm

Pressure Washer Pumps & Parts - RCV2.5G27D-F7
FEATURES -

- Manifold: High strength forged brass for long term use.
- Bolts: Eight 6mm.
- Plungers: NEW Ceramic Plungers, thicker wall to help precent thermal shock.
- Valves: Stainless Steel, valve seat o-ring is side mounted.
- Seals: High quality high pressure seals. NEW low-pressure seal with a built in scraper.
- Piston Guides: Two piece guides.
- Drive End: NEW connecting rid with 12% more load surface. Large side cover sight glass, over sized bearing. Rear cover oil drain.
- Crankshaft: Forged, precision ground.

Factory Brochure

SPECIFICATIONS -

Maximum Volume
Max. Discharge Pressure
Max. Horsepower
Stroke
Maximum Fluid Temperature
Inlet Port Thread

Steambrite Supply

Parts & Accessories > Pumps (Water Pumps) > Annovi Reverberi Pumps > AR Industrial Triplex Plunger Pumps > RC Series > AR Pump RCV25G27D-F7, 2700psi 2.5 gpm Gas Bolt On 3/4 Shaft 3400rpm

AR Pump RCV25G27D-F7, 2700psi 2.5 gpm Gas Bolt On 3/4 Shaft 3400rpm

Maximum Inlet Vacuum	• 2.5 gpm
Maximum Inlet Pressure	• 2700 psi
Bore	• 4.6 EBHP
Weight	• 5.6 mm
Crankcase Oil Capacity	• 140°F
Discharge Port Thread	• 1/2 F
	• 8.0 LMP
	• 170 psi
	• 15 mm
	• 11 lbs.
	• 9.81 oz
	• 3/8 F

.

Freight charges will be applied to ALL orders. (Including local pickup in San Antonio, TX)
20150727

Availability: This product was added to our catalog on Saturday 04 July, 2015

Steambrite Supply