Parts & Accessories > Jets Nozzles TeeJets VeeJets Cone Spray M-Style Rotary Lazer > Rotary Turbo Nozzles > Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For Pressure Washing

Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For Pressure Washing



Model Number: 20707015

Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For Pressure Washing

Manufacturer: Clean Storm

Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle - 5100 PSI 7.0 GPM

Description

The Clean Storm 20707015 A-Plus+ Heavy Duty Rotary Turbo Nozzle is engineered for high-performance commercial and industrial pressure washing applications. Operating efficiently across pressures from 500 to 5100 PSI with a 7.0 GPM flow rate, this heavy-duty nozzle delivers the deep-cleaning impact of a zero-degree stream while rotating in a wide 25-degree pattern at up to 5000 RPM. Built with upgraded seals and a thick-walled, durable housing, it features a gearless, toothless, and bearingless design that minimizes startup impact and mechanical wear, ensuring exceptional longevity in both hot and cold water environments up to 212°F.

Features

- Heavy-duty construction featuring upgraded seals specifically engineered to withstand hot water up to 212°F and pressures up to 5100 PSI.
- Combines the pinpoint cleaning power of a 0-degree spray stream with a wide 25-degree rotation pattern operating at up to 5000 RPM.
- Gearless, toothless, and bearingless internal design minimizes startup impact, wear, and mechanical failure.
- Versatile compatibility with both hot and cold pressure washers across an operating range of 500 to 5100 PSI.
- Thicker wall construction provides enhanced durability and impact resistance against accidental drops or strikes against hard surfaces.

Specifications

Brand / Series
Clean Storm / A-Plus+

Model / Part Number
20707015

Flow Rate
7.0 GPM (calculated at 4000 PSI)

Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For Pressure Washing

Operating Pressure Range
500 PSI to 5100 PSI

Maximum Water Temperature
212°F (100°C) at the tip

Spray Pattern
0° stream rotating at 25° (up to 5000 RPM)

Default Color
Black (color not guaranteed)

Question and Answer

- Question: If my hot pressure washer is set to 240 degrees F, is it OK to use this nozzle?
- Answer: Yes, the water cools down up to 30 degrees through most 100 ft hose runs and this is still OK to use. The nozzle is designed for water up to 5100 psi @ 212 degrees F (100 degrees C) at the tip.
- Question: What is the difference between the 3000, 4000, and 5100 psi units?
- Answer: For the 5000 psi turbo nozzle, it could work in the higher pressure situation and its material is thicker than 3000 psi and 4000 psi turbo nozzle. 5000 psi turbo nozzle's weight is much heavier. Overall a much longer lasting design with better safety in both hot water situations and higher pressures. The added thickness of the design also makes it better for impact situations if the nozzle hits the ground or some other object.
- Question: Can I use this 5100 psi HOT for cold water and low pressure situations?
- Answer: Yes.

Tips

- Start turbo nozzles in the downward position and then raise lance to higher level.

- Please note turbo nozzles can harm you if you get near any body parts/ skin. Will also cut through wood and shoes!
- Please note the filter is highly recommended with use on HOT pressure washers as rust in the nozzle with jam up the rotary action.

Steambrite Supply

Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For Pressure Washing

- Caution: Not for use on painted or softer surfaces (example car's exterior)

Videos

Pictures

Optional

Rotary Nozzle Inline Filter High Pressure 1/4in QD X 1/4"Mip Brass 8.709-979.0 Landa Legacy Hotsy Shark 342042

Installs directly into the back of the turbo nozzle and filters rust from water protecting your rotary nozzle.

QD Coupler 1/4" Mip X 1/4 Male Nipple Plug Stainless Steel 8.707-140.0 - Landa Legacy Hotsy Shark

Installs directly into the back of the turbo nozzle for quick coupler action at the end of your lance

Legacy 1/4 Inch Female Socket Quick Coupler X 1/4" Fip Connection 4000 psi 98021640

Used to convert the end of your lance into quick coupler jet and nozzle change out.

Options available for Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For

Steambrite Supply

Parts & Accessories > Jets Nozzles TeeJets VeeJets Cone Spray M-Style Rotary Lazer > Rotary Turbo Nozzles > Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For Pressure Washing

Clean Storm 20707015, A-Plus+ Water Rotary Turbo Laser Nozzle, 5100 PSI, 7.0 gpm, Hot, For Pressure Washing

Pressure Washing :

Add-ons

Filtered QD Connection With Male Plug [87099790], + None, 1/4in Mip X Standard Stainless QD Male Plug [87071400].

Availability: This product was added to our catalog on Thursday 15 October, 2015

Steambrite Supply