

>



Model Number: EM4106T
Baldor Motor EM4106T - 20Hp Triple Phase 3450 RPM 256T Frame 230/460Volts 23 Amps
Manufacturer: Baldor Motors
Baldor Motor EM4106T - 20Hp - Triple Phase - 3450 RPM - 256T Frame - 230/460Volts - 23 Amps
259lbs

Output	20.000 hp
Phase	3
Synchronous Speed	3,600 rpm
Frequency	60 Hz
Voltage	230 V -- 460 V
Enclosure	TEFC
Frame Material	Iron
Frame	256T
XP Division	Not Applicable
Brand	Baldor-Reliance
Agency Approvals	CSA -- CSA EEV -- UR
Ambient Temperature	40 °C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	RG
Bearing Grease Type	POLYREX EM (-20F +300F)
Blower	None
Current	50.0 A @ 208 V -- 46.0 A @ 230 V -- 23.0 A @ 460 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0%
Electrically Isolated Bearing	No electrically isolated
Feedback Device	No feedback
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No heater
High Voltage Full Load Amps	23.0 A
Insulation Class	F
Inverter Code	Inverter ready

>

KVA Code	H
Lifting Lugs	Std Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	KO Box
Motor Lead Quantity/Wire Size	9 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0936M
Number of Poles	2
Overall Length	23.28 in
Power Factor	89
Product Family	General Purpose
Pulley End Bearing Type	Ball Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	No Rodent Screen
Service Factor	1.15
Shaft Diameter	1.625 in
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3,520 rpm
Speed Code	Single Speed
Starting Method	DOL
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Availability: This product was added to our catalog on Thursday 04 February, 2016