

>



Model Number: 77027045031

Liquid Nails Silicone Premium Universal Sealant LS-205 77027045031 0022078400735
348039899

Manufacturer: PPG Paints

Liquid Nails Silicone Premium Universal Sealant is a high performance

Description

Clear 100% . Silicone Premium Universal Sealant (LS-205) is a high performance sealant for outstanding water resistance and flexibility. Won't shrink or crack. Withstands harsh temperatures.

Features

- Permanently flexible
- Gives a mildew resistant seal
- Waterproof seal
- Ideal for high moisture areas
- Excellent durability
- Won't crack or shrink
- Great for kitchen & bath

Recommended For

Sealing

- Window and door frames
- Siding and trim
- Carpet cleaning machines and carpet wands
- Chair railings
- Sinks, bathtubs and showers
- Molding, baseboards, and siding
- Vanities
- Pipes and plumbing fixtures
- Tiles

Adheres

- Plaster (primed)
- Painted surfaces
- Concrete (primed)
- brick (primed)
- stone (primed)

>

- Masonry (primed)
- Aluminum
- Vinyl
- Wood
- Stucco
- Glass
- Metal
- Fiberglass (primed)

Not Recommended For

Non-adhesive

- Unprimed concrete, brick, masonry, plaster & stone
- Use below the water-line
- Wet, green or oily lumber
- Aquariums
- Marble
- Fireplaces
- Automotive uses
- Stove pipes

Specifications

- 10.1 oz
- Indoor/Outdoor
- Base: Silicone rubber
- Type: Acetoxy cure
- Colors: Clear and White
- Appearance: Smooth
- Application Temperature: 10–100° F (-12–38° C)
- Service Temperature: -62–450° F (-52–232° C)
- Extrudability: Good
- Durability: 50 year
- Elongation: 400%
- Flexibility: Excellent
- Volume Shrinkage: Less than 5%
- Slump: Max 0.15”

>

- Shore "A"; Hardness: 25
- Total Joint Movement: 25%
- Water Resistance: Excellent
- Exterior Weathering: Excellent
- Aging: Excellent
- Freeze-Thaw Stable: Passes 5 cycles
- Bleed: None
- Staining: None
- Odor: Slightly acidic
- Tack Free Time:
- Tack at drying time - 15 minutes
- Tack at 24 hours - none
- Drying Time: Sets in 24
- Weight Per Gallon: 8.7 pounds (3.94 kg)
- Viscosity: 400,000 CPS
- Solids: 100%
- Flammability: Nonflammable
- Flash Point: 100° - 110° F (38° - 43° C)
- Coverage: 30 lineal ft. (9.14 lineal meters) using 1/4" (.64cm) bead
- Shelf Life: One year from date of purchase
- VOC: <3% by wt. - White <50% by wt. - Clear
- MSDS
- Tech Data

Will not paint over. Keep from freezing during transport, so it might not be recommended to ship year around.

Compare to current or past OEM associations:

LS-205

77027045031

0022078400735

348039899

Availability: This product was added to our catalog on Thursday 17 November, 2016