Parts & Accessories > Swivels Pressure Rotary Union > 90 Degree Pressure Swivels Rotary Union > Mosmatic 32.543, DGK Swivel-90Â°, Single-Bearing-System, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

Mosmatic 32.543, DGK Swivel-90Â°, Single-Bearing-System, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi



Model Number: 32.543

Mosmatic 32.543, DGK Swivel-90Â°, Single-Bearing-System, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

Manufacturer: Mosmatic

Mosmatic 32.543, DGK Swivel-90°, Single-Bearing-System, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi
Description
The Mosmatic DGK Swivel 32.543 – 90 Degrees is a compact, high-precision swivel ideal for high-pressure guns, hose connections, and hydraulic systems where smooth, tangle-free operation is critical. Constructed with a stainless steel/brass body and protected by nickel plating, this 90° swivel delivers live rotation under full pressure and long-lasting durability.

Featuring a low-torque thrust ball bearing and a dependable O-ring NBR seal system (optional upgrades: EPDM or FKM), this swivel is maintenance-free and engineered to perform consistently in demanding environments.
Applications

- High-pressure gun swivels
- Hose and hydraulic connections
- Industrial tangle-free setups
- Cleaning equipment & car washes
- Spray tools and mobile wash systems

Features

- Material: Stainless steel/brass, nickel plated
- Thread IN (G1): 1/4" NPTM
- Thread OUT (G2): 1/4" NPTF
- Design: 90-degree compact swivel
- Overall Length: 0.94"
- Nominal Width (NW): 1/4"
- Wrench Size (SW): 0.94"
- Max Pressure: 4000 PSI

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > 90 Degree Pressure Swivels Rotary Union > Mosmatic 32.543, DGK Swivel-90Â°, Single-Bearing-System, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

Mosmatic 32.543, DGK Swivel-90Â°, Single-Bearing-System, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

- Max RPM: 30
- Max Temperature: 250°F
- Bearings: 1x thrust ball bearing
- Seal System: O-ring NBR (EPDM/FKM available)
- Performance: Low torque, live rotation, corrosion resistant

Specification
Pressure: 4000 psi (27.5 MPa)
Temperature: 250°F
RPM: max 30 rpm
Material Type: Stainless steel, Brass, Nickel plated
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread In: G1 1/4" NPTM
Thread Out: G2 1/4" NPTF
Nominal Width (NW): 1/4"
Wrench Size 1 (SW1): 0.94"
Length 1 (L1) (overall length) : 0.94"
Length 2 (L2): 0.39"
Weight: 5.6 oz
Additional Information

Availability: This product was added to our catalog on Friday 20 January, 2017