Mosmatic 32.549, DGK Swivel-90Â°, Single-Bearing-System, 3/8 in. NPT M 3/8 in. NPT F, 4000 psi



Model Number: 32.549

Mosmatic 32.549, DGK Swivel-90Â°, Single-Bearing-System, 3/8 in. NPT M 3/8 in. NPT F, 4000 psi

Manufacturer: Mosmatic

Mosmatic 32.549, DGK Swivel-90°, Single-Bearing-System, 3/8 in. NPT M 3/8 in. NPT F, 4000 psi
Description
The Mosmatic DGK Swivel 32.549 – 90 Degrees is designed for high-performance pressure cleaning, hydraulic systems, and hose connections. Built with a durable stainless steel/brass body and nickel-plated finish, this swivel delivers exceptional corrosion resistance and longevity in industrial environments.

Featuring a thrust ball bearing and a reliable O-ring NBR seal system (optional EPDM or FKM), this swivel supports live rotation under full pressure with minimal torque. Its 90-degree compact design ensures easy integration into tight setups while keeping hoses tangle-free.
Applications

- High-pressure spray guns
- Hydraulic hose assemblies
- Wash bays and ceiling booms
- Tangle-free hose connection systems
- Industrial pressure cleaning tools

Features

- Material: Stainless steel/brass with nickel plating
- Thread IN (G1): 3/8" NPTM
- Thread OUT (G2): 3/8" NPTF
- Overall Length: 1.06"
- Nominal Width (NW): 1/4"
- Wrench Size (SW): 0.94"
- Maximum Pressure: 4000 PSI
- Maximum RPM: 30

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > 90 Degree Pressure Swivels Rotary Union > Mosmatic 32.549, DGK Swivel-90Â°, Single-Bearing-System, 3/8 in. NPT M 3/8 in. NPT F, 4000 psi

Mosmatic 32.549, DGK Swivel-90Â°, Single-Bearing-System, 3/8 in. NPT M 3/8 in. NPT F, 4000 psi

- Max Temperature: 250°F
- Seal System: O-ring NBR (EPDM or FKM optional)
- Bearing System: 1x thrust ball bearing
- Design: 90° swivel for optimized directional flow
- Performance: Maintenance free, low torque, high durability

Specification
Pressure: 4000 psi (27.5 MPa)
Temperature: 250°F
RPM: max 30 rpm
Material Type: Stainless steel, Brass, Nickel plated
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread In: G1 3/8" NPTM
Thread Out: G2 3/8" NPTF
Nominal Width (NW): 1/4"
Wrench Size 1 (SW1): 0.94"
Length 1 (L1) (overall length) : 1.06"
Length 2 (L2): 0.39"
Weight: 5.8 oz
Additional Information

Availability: This product was added to our catalog on Friday 20 January, 2017