Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.752, DGVI Swivel, Single-Bearing-System, Stainless Steel, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

Mosmatic 32.752, DGVI Swivel, Single-Bearing-System, Stainless Steel, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi



Model Number: 32.752

Mosmatic 32.752, DGVI Swivel, Single-Bearing-System, Stainless Steel, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

Manufacturer: Mosmatic

Mosmatic 32.752, DGVI Swivel, Single-Bearing-System, Stainless Steel, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi
Description
The Mosmatic DGVI Swivel 32.752 is engineered for high-performance in HP-Guns, hydraulic systems, and high-pressure hose reels. Built entirely from stainless steel, this swivel offers live rotation under maximum pressure and is designed to handle intense working conditions while remaining maintenance-free.

Its single thrust ball bearing system and O-ring NBR seal (optional EPDM or FKM) deliver reliable rotation, corrosion resistance, and leak prevention. This swivel is ideal for professionals needing compact strength and maximum durability in demanding environments.
Applications

- High-pressure hose reels
- HP-Guns and pressure washer systems
- Hydraulic applications
- Tangle-free hose systems
- Industrial cleaning equipment

Features

- Material: Full stainless steel construction
- Thread IN (G1): 1/4" NPTM
- Thread OUT (G2): 1/4" NPTF
- Overall Length: 2.60"
- Nominal Width (NW): 1/4"
- Wrench Size (SW): 0.94"

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.752, DGVI Swivel, Single-Bearing-System, Stainless Steel, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

Mosmatic 32.752, DGVI Swivel, Single-Bearing-System, Stainless Steel, 1/4 in. NPT M 1/4 in. NPT F, 4000 psi

- Max Pressure: 7300 PSI
- Max RPM: 30
- Max Temperature: 250°F
- Bearing System: 1x thrust ball bearing
- Seal System: O-ring NBR (optional EPDM or FKM)
- Benefits: Live rotation, corrosion resistance, compact, maintenance free

Specification
Pressure: 7300 psi (50 MPa)
Temperature: 250°F
RPM: max 30 rpm
Material Type: Stainless steel
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread In: G1 1/4" NPTM
Thread Out: G2 1/4" NPTF
Nominal Width (NW): 1/4"
Wrench Size 1 (SW1): 0.94"
Wrench Size 2 (SW2): 0.75"
Length 1 (L1) (overall length) : 2.60"
Length 2 (L2): 0.39"
Weight: 5.2 oz
Additional Information

Availability: This product was added to our catalog on Friday 20 January, 2017

Steambrite Supply