Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.764, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT F

Mosmatic 32.764, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT F



Model Number: 32.764

Mosmatic 32.764, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT F

Manufacturer: Mosmatic

Mosmatic 32.764, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT F
Description
The Mosmatic DGVI Swivel 32.754 is a precision-engineered stainless steel swivel designed for high-pressure hose reels, HP-Guns, and hydraulic applications. Featuring a live-rotation design and robust stainless steel construction, this swivel is built to perform under maximum pressure with zero maintenance required.

With a single thrust ball bearing and O-ring NBR seal system (upgradable to EPDM or FKM), this swivel ensures smooth rotation, excellent seal integrity, and corrosion resistance in the toughest industrial environments.
Applications

- High-pressure hose reels
- Hydraulic tools and lines
- HP-Guns and industrial washdown systems
- Tangle-free hose management
- Pressure cleaning machinery

Features

- Material: 100% stainless steel for maximum durability
- Thread IN (G1): 3/8" NPTM
- Thread OUT (G2): 3/8" NPTF
- Overall Length: 2.75"
- Nominal Width (NW): 1/4"
- Wrench Size (SW): 0.94"
- Max Pressure: 7300 PSI
- Max RPM: 30

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.764, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT F

Mosmatic 32.764, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT F

- Max Temperature: 250°F
- Bearing System: 1x thrust ball bearing
- Seal System: O-ring NBR (optional EPDM or FKM)

Benefits

- Live Rotation
- Compact Build
- Maintenance-free
- Corrosion-resistant

Specifications
Pressure: 7300 psi (50 MPa)
Temperature: 250°F
RPM: max 30 rpm
Material Type: Stainless steel
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread In: G1 3/8" NPTM
Thread Out: G2 3/8" NPTF
Nominal Width (NW): 1/4"
Wrench Size 1 (SW1): 0.94"
Wrench Size 2 (SW2): 0.87"
Length 1 (L1) (overall length) : 2.75"
Length 2 (L2): 0.43"
Weight: 6.4 oz
Additional Information

Availability: This product was added to our catalog on Friday 20 January, 2017

Steambrite Supply