

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.763, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT M

Mosmatic 32.763, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT M



Model Number: 32.763

Mosmatic 32.763, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT M

Manufacturer: Mosmatic

Mosmatic 32.763, DGVI Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT M

Description

The Mosmatic DGVI Swivel 32.763 delivers exceptional performance in high-pressure applications. Crafted from durable stainless steel, this swivel is built for HP-guns, hydraulic systems, and tangle-free hose reel setups. Its single bearing system with a thrust ball bearing ensures smooth live rotation under pressure.

Designed for durability and reliability, this swivel includes an O-ring NBR seal system (optional EPDM or FKM), supports up to 7300 PSI, and offers maintenance-free operation. Perfect for professionals needing compact power in a corrosion-resistant form factor.

Applications

- High-pressure hose reels
- Hydraulic systems
- Pressure washer guns (HP-Guns)
- Industrial cleaning equipment
- Tangle-free hose applications

Features

- Material: Stainless steel construction
- Thread IN: 3/8" NPTM
- Thread OUT: 3/8" NPTM
- Overall Length: 2.48"
- Nominal Width (NW): 1/4"
- Wrench Size (SW): 0.94"
- Max Pressure: 7300 PSI

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.763, DGVl Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT M

Mosmatic 32.763, DGVl Swivel, Single-Bearing-System, Stainless Steel, 3/8 in. NPT M 3/8 in. NPT M

- Max RPM: 30
- Max Temperature: 250°F
- Bearing System: 1x thrust ball bearing
- Seal System: O-ring NBR (optional EPDM or FKM)

Advantages

- Compact
- Corrosion resistant
- Maintenance free
- Live rotation under full load

Specifications

Pressure: 7300 psi (50 MPa)

Temperature: 250°F

RPM: max 30 rpm

Material Type: Stainless steel

Inner Part: Stainless steel

Seal: O-ring NBR (optional: EPDM or FKM)

Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)

Thread In: G1 3/8" NPTM

Thread Out: G2 3/8" NPTM

Nominal Width (NW): 1/4"

Wrench Size 1 (SW1): 0.94"

Wrench Size 2 (SW2): 0.75"

Length 1 (L1) (overall length) : 2.48"

Length 2 (L2): 0.43"

Length 3 (L3): 0.47"

Weight: 5.4 oz

Additional Information

Availability: This product was added to our catalog on Friday 20 January, 2017