Mosmatic 32.906, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/8 in. NPT M, 4000 psi



Model Number: 32.906

Mosmatic 32.906, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/8 in. NPT M, 4000 psi

Manufacturer: Mosmatic

Mosmatic 32.906, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/8 in. NPT M, 4000 psi
Description
The Mosmatic 32.906 DGVI Swivel is a high-performance swivel joint engineered to enhance the flexibility and handling of paint spray guns, HP-guns, and multi-directional hose setups. Constructed from brass, nickel-plated components, and stainless steel, this swivel ensures long-lasting durability and smooth operation in high-pressure environments.

Designed with a 1/4" NPTF inlet and 1/8" NPTM outlet, the swivel offers a nominal width of 1/4" and a compact length of 4.17". It features a single thrust ball bearing system, a reinforced inner shaft, and a maintenance-free design. The NBR O-ring seal (optional EPDM or FKM) ensures leak-free performance, while its full 360° articulation supports up to 4000 PSI, 30 RPM, and 250°F, making it ideal for professional applications.
Applications

- Paint spray guns and airless spraying systems
- HP-guns for pressure washing
- Multi-directional hose assemblies
- Industrial and automotive refinishing equipment
- High-pressure fluid delivery in confined or mobile setups

Features

- Made from brass, nickel-plated, and stainless steel
- Thread Inlet: 1/4" NPTF | Thread Outlet: 1/8" NPTM
- Overall Length: 4.17" | Nominal Width: 1/4"
- Rated for 4000 PSI, 30 RPM, and 250°F max temperature
- Includes NBR O-ring seal system
- Single thrust ball bearing for smooth swivel action
- Reinforced inner shaft for added strength

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.906, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/8 in. NPT M, 4000 psi

Mosmatic 32.906, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/8 in. NPT M, 4000 psi

- Maintenance-free, full 360° swivel design

Specifications
Pressure: 4000 psi
Temperature: 250°F
RPM: max 30 rpm
Material Type: Brass, Nickel plated, Stainless Steel
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread IN: 1/4"NPTF
Thread OUT: 1/8"M
Nominal Width (NW): 1/4"
Wrench Size 1 (SW1): 0.75
Wrench Size 2 (SW2): 0.40
Length 1 (L1) (overall length) : 4.17
Length 2 (L2): 0.60
Length 3 (L3): 2.00
Weight: 13.8 oz
Additional Information

Availability: This product was added to our catalog on Friday 20 January, 2017

Steambrite Supply