Mosmatic 32.915, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/4 in. NPT M



Model Number: 32.915

Mosmatic 32.915, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/4 in. NPT M

Manufacturer: Mosmatic

Mosmatic 32.915, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/4 in. NPT M
Description
The Mosmatic 32.915 DGVI Swivel is a precision-engineered swivel designed to improve hose mobility and reduce operator fatigue in paint spray guns, HP-guns, and multi-directional cleaning systems. Built from brass, nickel-plated components, and stainless steel, it ensures high durability and consistent performance in high-pressure environments.

This swivel features a 1/4" NPTF inlet, 1/4" NPTM outlet, a nominal width of 1/4", and an overall length of 4.45". It includes a single thrust ball bearing, a reinforced inner shaft, and is maintenance-free for extended reliability. The integrated NBR O-ring seal (with optional EPDM or FKM) delivers leak-free operation. Rated up to 4000 PSI, 30 RPM, and 250°F, this swivel is ideal for heavy-duty, multi-angle usage.
Applications

- Paint spray guns and industrial coating systems
- HP-guns for pressure washing
- Multi-directional hose assemblies
- Automotive, marine, and industrial cleaning setups
- High-pressure fluid delivery systems requiring flexibility

Features

- Thread Inlet: 1/4" NPTF | Thread Outlet: 1/4" NPTM
- Overall Length: 4.45" | Nominal Width: 1/4"
- Made from brass, nickel-plated components, and stainless steel
- 360° swivel articulation for full-range hose mobility
- Single thrust ball bearing for smooth rotation
- Reinforced inner shaft for added strength
- Maintenance-free design for long-term performance

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > In Line Pressure Swivels Rotary Union > Mosmatic 32.915, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/4 in. NPT M

Mosmatic 32.915, DGVI Z-Swivel Reinforced, 1/4 in. NPT F 1/4 in. NPT M

- NBR O-ring seal (EPDM/FKM optional)
- Rated up to 4000 PSI, 30 RPM, and 250°F

Specifications
Pressure: 4000 psi
Temperature: 250°F
RPM: max 30 rpm
Material Type: Brass, Nickel plated, Stainless Steel
Inner Part: Stainless steel
Seal: O-ring NBR (optional: EPDM or FKM)
Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
Thread IN: 1/4"NPTF
Thread OUT: 1/4"M
Nominal Width (NW): 1/4"
Wrench Size 1 (SW1): 0.75
Wrench Size 2 (SW2): 0.67
Length 1 (L1) (overall length) : 4.45
Length 2 (L2): 0.90
Length 3 (L3): 2.00
Weight: 15.0 oz
Additional Information

Availability: This product was added to our catalog on Friday 20 January, 2017

Steambrite Supply