Parts & Accessories > Swivels Pressure Rotary Union > Large Pipe In Line Hi-Flow Swivels Rotary Union > Mosmatic 34.752, DGEI-10 Swivel Hi-Flo, Single Bearing-System, Stainless Steel, 3/8 in. NPT F 3/8 in. NPT M, 5000psi

Mosmatic 34.752, DGEI-10 Swivel Hi-Flo, Single Bearing-System, Stainless Steel, 3/8 in. NPT F 3/8 in. NPT M, 5000psi



Model Number: 34.752

Mosmatic 34.752, DGEI-10 Swivel Hi-Flo, Single Bearing-System, Stainless Steel, 3/8 in. NPT F 3/8 in. NPT M, 5000psi

Manufacturer: Mosmatic

Mosmatic 34.752, DGEI-10 Swivel Hi-Flo, Single Bearing-System, Stainless Steel, 3/8 in. NPT F 3/8 in. NPT M, 5000psi
Description
The Mosmatic DGE Swivel - 34.752 is a premium-grade stainless steel swivel designed to withstand thrust and radial forces in high-pressure and high-flow applications. Engineered for use in pharmaceutical, food service, automatic car wash, and industrial environments, this swivel delivers excellent performance and reliability. It features 1x thrust ball bearing and 2x sliding bearings for stable, smooth operation. Built with corrosion-resistant materials and rated for up to 5000 PSI and 250°F, it's ideal for demanding, continuous-use systems.
Applications

- Pharmaceutical production and processing
- Food and beverage sanitation systems
- Automatic car wash and rinse equipment
- Industrial washdown and fluid transfer

Features

- Heavy-duty stainless steel construction for superior corrosion resistance
- With 1x thrust ball bearing and 2 x sliding bearings
- High-flow design for efficient pressure handling
- Supports both thrust and radial loads

Specifications

- Pressure: 5000 psi
- Temperature: 250°F

Steambrite Supply

Parts & Accessories > Swivels Pressure Rotary Union > Large Pipe In Line Hi-Flow Swivels Rotary Union > Mosmatic 34.752, DGEI-10 Swivel Hi-Flo, Single Bearing-System, Stainless Steel, 3/8 in. NPT F 3/8 in. NPT M, 5000psi

Mosmatic 34.752, DGEI-10 Swivel Hi-Flo, Single Bearing-System, Stainless Steel, 3/8 in. NPT F 3/8 in. NPT M, 5000psi

- RPM: Max. 30
- Material Type: Stainless Steel
- Inner Part: Stainless Steel
- Seal: O-ring NBR
- Throughput/medium: ph 3-12 / filtered 10 microns, compressed air (290 psi)
- Thread In: G1 3/8"NPTF
- Thread Out: G2 3/8"NPTM
- Nominal Width (NW): 3/8"
- Wrench Size 1 (SW1): 0.87
- Wrench Size 2 (SW2): 1.38
- Diameter (D1): 1.65"
- Length 1 (L1) (overall length): 2.87"
- Length 2 (L2): 2.05
- Length 3 (L3): 0.43
- Weight: 18.9oz

Availability: This product was added to our catalog on Friday 20 January, 2017

Steambrite Supply